

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: November 7, 2011

M. Douglass  
RPI  
May 6, 2011

Link Extension to Icalendar  
draft-douglass-link-extension-01

Abstract

This specification introduces new iCalendar property LINK to provide ancillary information for iCalendar components and changes RELATED-TO to define temporal relationships.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 7, 2011.

Copyright Notice

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	3
1.1. Conventions Used in This Document . . . . .	3
2. Typed References . . . . .	3
3. Reference Types . . . . .	4
4. Link Relation Types . . . . .	4
5. Redefined Relation Type Value . . . . .	4
6. New Property Parameters . . . . .	6
6.1. Rel . . . . .	6
6.2. Gap . . . . .	6
6.3. Title . . . . .	7
7. New Parameter Values . . . . .	7
8. New Properties . . . . .	7
8.1. Link . . . . .	7
9. Redefined RELATED-TO Property . . . . .	9
9.1. RELATED-TO . . . . .	9
10. Security Considerations . . . . .	11
11. IANA Considerations . . . . .	11
12. Acknowledgements . . . . .	11
13. Normative References . . . . .	11
Author's Address . . . . .	12

## 1. Introduction

The currently existing iCalendar standard [RFC5545] lacks a general purpose method for referencing additional, external information relating to calendar components.

This document proposes a method for referencing typed external information that can provide additional information about an iCalendar component. This new LINK property is closely aligned to the LINK header defined in [RFC5988]

In addition the RELTYPE parameter is extended to take new values defining temporal relationships, a GAP parameter is defined to provide lead and lag values and RELATED-TO is extended to allow URI values. These changes allows the RELATED-TO property to define a richer set of relationships useful for project management.

### 1.1. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

## 2. Typed References

The LINK property defines a typed reference or relation to external meta-data or related resources. By providing type and format information as parameters, clients and servers are able to discover interesting references and make use of them, perhaps for indexing or the presentation of interesting links for the user.

It is often necessary to relate calendar components. The current RELATED-TO property only allows for a UID which is inadequate for many purposes. Allowing other types may help but might raise a number of backward compatibility issues. The link property can link components in different collections or even on different servers.

When publishing events it is useful to be able to refer back to the source of that information. The actual event may have been consumed from a feed or an ics file on a web site. A LINK property can provide a reference to the originator of the event.

Project management tools often need to be able to specify the relationships between the various events and tasks which make up a project. This specification defines relation types for those purposes.

### 3. Reference Types

The actual reference value can take three forms specified by the type parameter

URI: The default type. This is a URI referring to the target.

UID: This allows for linking within a single collection and the value is assumed to be another component within that collection.

REFERENCE: An xpointer. In an XML environment it may be necessary to refer to an external XML artifact. The XPointer is defined in [W3C.WD-xptr-xpointer-20021219] and allows addressing portions of XML documents.

### 4. Link Relation Types

[RFC5988] defines two form of relation types, registered and extension. Registered relation types are added to a registry defined by [RFC5988] while extension relation types are specified as unique unregistered URIs, (at least unregistered in the [RFC5988] registry).

The relation types defined here will be registered with IANA in accordance with the specifications in [RFC5988].

### 5. Redefined Relation Type Value

Relationship parameter type values are defined in section 3.2.15. of [RFC5545]. This specification redefines that type to include the new values FINISHTOSTART, FINISHTOFINISH, STARTTOFINISH and STARTTOSTART.

Format Definition:

This property parameter is defined by the following notation:

```
reltypeparam      = "RELTYPE" "="
                   ("PARENT"      ; Parent relationship - Default
                    / "CHILD"      ; Child relationship
                    / "SIBLING"    ; Sibling relationship
                    / "FINISHTOSTART"
                    / "FINISHTOFINISH"
                    / "STARTTOFINISH"
                    / "STARTTOSTART"
                    / iana-token   ; Some other IANA-registered
                                   ; iCalendar relationship type
                    / x-name)     ; A non-standard, experimental
                                   ; relationship type
```

Description: This parameter can be specified on a property that references another related calendar. The parameter may specify the hierarchical relationship type of the calendar component referenced by the property when the value is PARENT, CHILD or SIBLING. It defines the temporal relationship when the value is one of FINISHTOSTART, FINISHTOFINISH, STARTTOFINISH or STARTTOSTART. If this parameter is not specified on an allowable property, the default relationship type is PARENT. Applications MUST treat x-name and iana-token values they don't recognize the same way as they would the PARENT value.

RELTYPE=PARENT: Identifies the referenced calendar component is a superior of calendar component

RELTYPE=CHILD: Indicates that the referenced calendar component is a subordinate of the calendar component.

RELTYPE=SIBLING: Indicates that the referenced calendar component is a peer of the calendar component.

RELTYPE=FINISHTOSTART: As soon as the Predecessor Interval finishes, the Successor Interval starts. For example, when sanding is complete, painting begins.

RELTYPE=FINISHTOFINISH: The Successor Interval continues as long as the Predecessor Interval. For example, the concession stand stops serving 20 minutes after the end of the game.

RELTYPE=STARTTOFINISH: The start of the Predecessor controls the finish of the Successor. For example, the start of Attendee Check-in controls the end of the interval "Set up registration booth."

RELTYPE=STARTTOSTART: The Predecessor Interval triggers the start of the second task. The Gap indicates the lag time. For example, 20 minutes after the caterer begins work, the dining lines are open.

## 6. New Property Parameters

### 6.1. Rel

Parameter name: REL

Purpose: To specify the relationship of data referenced by a LINK property.

Format Definition:

This parameter is defined by the following notation:

```
relparam      = "REL" "="  
                ("SOURCE"          ; Link to source of this component  
                / DQUOTE uri DQUOTE  
                / x-name           ; Experimental reference type  
                / iana-token)     ; Other IANA registered type
```

Description: This parameter MUST be specified on all LINK properties, and defines the type of reference. This allows programs consuming this data to automatically scan for references they support. In addition to the values defined here any value defined in [RFC5988] may be used. There is no default relation type.

REL=SOURCE: identifies the source of the event information.

Registration: These relation types are registered in [RFC5988]

### 6.2. Gap

Parameter name: GAP

Purpose: To specify the length of the gap, positive or negative between two temporally related components.

Format Definition:

This parameter is defined by the following notation:

```
gapparam      = "GAP" "=" dur-value
```

Description: This parameter MAY be specified on the RELATED-TO property, and defines the duration of time between the predecessor and successor in an interval.

### 6.3. Title

Parameter name: TITLE

Purpose: To provide a human readable title.

Format Definition:

This parameter is defined by the following notation:

```
titleparam      = "TITLE" "=" text
```

Description: This parameter MAY be specified on all LINK properties, and provides a human readable label, perhaps for icons or links..

## 7. New Parameter Values

This specification defines a new value to be used with the VALUE property parameter:

UID VALUE=UID indicates that the associated value is the UID for a component.

REFERENCE VALUE=REFERENCE indicates that the associated value is an xpointer referencing an associated XML artifact.

## 8. New Properties

### 8.1. Link

Property name: LINK

Purpose: This property provides a reference to external information about a component.

Value type: URI, TEXT or REFERENCE

Property Parameters: Non-standard, reference type or format type parameters can be specified on this property.

Conformance: This property MAY be specified in any iCalendar component.

Description: When used in a component the value of this property points to additional information related to the component. For example, it may reference the originating web server.

Format Definition:

This property is defined by the following notation:

```
link          = "LINK" linkparam ":" ( ":" uri ) /
              (
                ";" "VALUE" "=" "REFERENCE"
                ":" text
              )
              CRLF
```

```
linkparam    = *(
              ; the following is MANDATORY
              ; and MAY occur more than once

              (";" relparam) /

              ; the following are MANDATORY
              ; but MUST NOT occur more than once

              (";" gapparam) /
              (";" fmttypeparam) /
              (";" titleparam) /

              ; the following is OPTIONAL
              ; and MAY occur more than once

              (";" xparam)

              )
```

Example:

The following is an example of this property. It points to a server acting as the source for the event.

```
LINK;REL=SOURCE;TITLE=The Egg:
  http://example.com/events
```



## 9. Redefined RELATED-TO Property

### 9.1. RELATED-TO

Property name: RELATED-TO

Purpose: This property is used to represent a relationship or reference between one calendar component and another. The definition here extends the definition in Section 3.8.4.5. of [RFC5545] by allowing URI values and a GAP parameter.

Value type: URI or TEXT

Property Parameters: Non-standard, reference type, gap, value or format type parameters can be specified on this property.

Conformance: This property MAY be specified in any iCalendar component.

Description: By default or when VALUE=UID is specified, the property value consists of the persistent, globally unique identifier of another calendar component. This value would be represented in a calendar component by the "UID" property.

By default, the property value points to another calendar component that has a PARENT relationship to the referencing object. The "RELTYPE" property parameter is used to either explicitly state the default PARENT relationship type to the referenced calendar component or to override the default PARENT relationship type and specify either a CHILD or SIBLING relationship or a temporal relationship.

The PARENT relationship indicates that the calendar component is a subordinate of the referenced calendar component. The CHILD relationship indicates that the calendar component is a superior of the referenced calendar component. The SIBLING relationship indicates that the calendar component is a peer of the referenced calendar component.

The FINISHTOSTART, FINISHTOFINISH, STARTTOFINISH or STARTTOSTART relationships define temporal relationships as specified in the reltype parameter definition.

Changes to a calendar component referenced by this property can have an implicit impact on the related calendar component. For example, if a group event changes its start or end date or time, then the related, dependent events will need to have their start and end dates changed in a corresponding way. Similarly, if a

PARENT calendar component is cancelled or deleted, then there is an implied impact to the related CHILD calendar components. This property is intended only to provide information on the relationship of calendar components. It is up to the target calendar system to maintain any property implications of this relationship.

#### Format Definition:

This property is defined by the following notation:

```
related      = "RELATED-TO" relparam ( ":" text ) /
              (
                ";" "VALUE" "=" "UID"
                ":" uid
              )
              (
                ";" "VALUE" "=" "URI"
                ":" uri
              )
              CRLF
```

```
relparam     = *(
              ;
              ; The following are OPTIONAL,
              ; but MUST NOT occur more than once.
              ;
              (";" reltypeparam) /
              (";" gapparam) /
              ;
              ; The following is OPTIONAL,
              ; and MAY occur more than once.
              ;
              (";" other-param)
              ;
              )
```

#### Example:

The following are examples of this property.

```
RELATED-TO:jsmith.part7.19960817T083000.xyzMail@example.com
```

```
RELATED-TO:19960401-080045-4000F192713-0052@example.com
```

```
RELATED-TO;VALUE=URI;RELTYPE=STARTTOFINISH:
http://example.com/caldav/user/jb/cal/
19960401-080045-4000F192713.ics
```

## 10. Security Considerations

Applications using the LINK property need to be aware of the risks entailed in using the URIs provided as values. See [RFC3986] for a discussion of the security considerations relating to URIs.

## 11. IANA Considerations

## 12. Acknowledgements

The author would like to thank Chuck Norris of eventful.com for his work which led to the development of this RFC.

The author would also like to thank the members of the Calendaring and Scheduling Consortium public events technical committee and the following individuals for contributing their ideas and support:

Cyrus Daboo, Dan Mendell

The authors would also like to thank the Calendaring and Scheduling Consortium for advice with this specification.

## 13. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, January 2004.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005.
- [RFC5545] Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", RFC 5545, September 2009.
- [RFC5988] Nottingham, M., "Web Linking", RFC 5988, October 2010.
- [W3C.REC-xml-20060816] Yergeau, F., Paoli, J., Sperberg-McQueen, C., Maler, E., and T. Bray, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", World Wide Web Consortium FirstEdition REC-xml-20060816, August 2006,

<<http://www.w3.org/TR/2006/REC-xml-20060816>>.

[W3C.WD-xptr-xpointer-20021219]

DeRose, S., Daniel, R., and E. Maler, "XPointer xpointer()  
Scheme", World Wide Web Consortium WD WD-xptr-xpointer-  
20021219, December 2002,  
<<http://www.w3.org/TR/2002/WD-xptr-xpointer-20021219>>.

#### Author's Address

Michael Douglass  
Rensselaer Polytechnic Institute  
110 8th Street  
Troy, NY 12180  
USA

Email: [douglm@rpi.edu](mailto:douglm@rpi.edu)  
URI: <http://www.rpi.edu/>