

WS-SecureConversation 1.3

Committee Draft 01, 06 September 2006

Artifact Identifier:

ws-secureconversation-1.3-spec-cd-01

Location:

Current: docs.oasis-open.org/ws-sx/ws-secureconversation/200512

This Version: docs.oasis-open.org/ws-sx/ws-secureconversation/200512

Previous Version: n/a

Artifact Type:

specification

Technical Committee:

OASIS Web Services Secure Exchange TC

Chair(s):

Kelvin Lawrence, IBM

Chris Kaler, Microsoft

Editor(s):

Anthony Nadalin, IBM

Marc Goodner, Microsoft

Martin Gudgin, Microsoft

Abbie Barbir, Nortel

Hans Granqvist, VeriSign

OASIS Conceptual Model topic area:

[Topic Area]

Related work:

NA

Abstract:

This specification defines extensions that build on [WS-Security] to provide a framework for requesting and issuing security tokens, and to broker trust relationships.

Status:

This document was last revised or approved by the WS-SX TC on the above date. The level of approval is also listed above. Check the current location noted above for possible later revisions of this document. This document is updated periodically on no particular schedule.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/ws-sx>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/ws-sx/ipr.php>).

The non-normative errata page for this specification is located at <http://www.oasis-open.org/committees/ws-sx>.

Notices

Copyright © OASIS Open 2006. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

Table of Contents

1	Introduction	4
1.1	Goals and Non-Goals	4
1.2	Requirements	4
1.3	Namespace	4
1.4	Schema File	5
1.5	Terminology	5
1.5.1	Notational Conventions	6
1.6	Normative References	7
1.7	Non-Normative References	8
2	Security Context Token (SCT)	9
3	Establishing Security Contexts	12
3.1	SCT Binding of WS-Trust	13
3.2	SCT Request Example without Target Scope	13
3.3	SCT Request Example with Target Scope	15
3.4	SCT Propagation Example	16
4	Amending Contexts	17
5	Renewing Contexts	19
6	Canceling Contexts	21
7	Deriving Keys	23
7.1	Syntax	24
7.2	Examples	26
7.3	Implied Derived Keys	28
8	Associating a Security Context	29
9	Error Handling	31
10	Security Considerations	32
A.	Sample Usages	33
A.1	Anonymous SCT	33
A.2	Mutual Authentication SCT	34
B.	Token Discovery Using RST/RSTR	35
C.	Acknowledgements	36

1 Introduction

The mechanisms defined in [WS-Security] provide the basic mechanisms on top of which secure messaging semantics can be defined for multiple message exchanges. This specification defines extensions to allow security context establishment and sharing, and session key derivation. This allows contexts to be established and potentially more efficient keys or new key material to be exchanged, thereby increasing the overall performance and security of the subsequent exchanges.

The [WS-Security] specification focuses on the message authentication model. This approach, while useful in many situations, is subject to several forms of attack (see Security Considerations section of [WS-Security] specification).

Accordingly, this specification introduces a security context and its usage. The context authentication model authenticates a series of messages thereby addressing these shortcomings, but requires additional communications if authentication happens prior to normal application exchanges.

The security context is defined as a new [WS-Security] token type that is obtained using a binding of [WS-Trust].

Compliant services are NOT REQUIRED to implement everything defined in this specification. However, if a service implements an aspect of the specification, it MUST comply with the requirements specified (e.g. related "MUST" statements).

1.1 Goals and Non-Goals

The primary goals of this specification are:

- Define how security contexts are established
- Describe how security contexts are amended
- Specify how derived keys are computed and passed

It is not a goal of this specification to define how trust is established or determined.

This specification is intended to provide a flexible set of mechanisms that can be used to support a range of security protocols. Some protocols may require separate mechanisms or restricted profiles of this specification.

1.2 Requirements

The following list identifies the key driving requirements:

- Derived keys and per-message keys
- Extensible security contexts

1.3 Namespace

The [URI] that MUST be used by implementations of this specification is:

<http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512>

Table 1 lists XML namespaces that are used in this specification. The choice of any namespace prefix is arbitrary and not semantically significant.

Table 1: Prefixes and XML Namespaces used in this specification.

Prefix	Namespace	Specification(s)
S11	http://schemas.xmlsoap.org/soap/envelope/	[SOAP]
S12	http://www.w3.org/2003/05/soap-envelope	[SOAP12]
wsu	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd	[WS-Security]
wsse	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd	[WS-Security]
wst	http://docs.oasis-open.org/ws-sx/ws-trust/200512	[WS-Trust]
wsc	http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512	This specification
wsa	http://www.w3.org/2005/08/addressing	[WS-Addressing]
ds	http://www.w3.org/2000/09/xmldsig#	[XML-Signature]
xenc	http://www.w3.org/2001/04/xmlenc#	[XML-Encrypt]

1.4 Schema File

The schema [XML-Schema1], [XML-Schema2] for this specification can be located at:

```
http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512/ws-secureconversation.xsd
```

In this document, reference is made to the `wsu:Id` attribute in the utility schema. These were added to the utility schema with the intent that other specifications requiring such an ID or timestamp could reference it (as is done here).

1.5 Terminology

Claim – A *claim* is a statement made about a client, service or other resource (e.g. name, identity, key, group, privilege, capability, etc.).

Security Token – A *security token* represents a collection of claims.

Security Context – A *security context* is an abstract concept that refers to an established authentication state and negotiated key(s) that may have additional security-related properties.

Security Context Token – A *security context token (SCT)* is a wire representation of that security context abstract concept, which allows a context to be named by a URI and used with [\[WS-Security\]](#).

Signed Security Token – A *signed security token* is a security token that is asserted and cryptographically endorsed by a specific authority (e.g. an X.509 certificate or a Kerberos ticket).

Proof-of-Possession Token – A *proof-of-possession (POP) token* is a security token that contains secret data that can be used to demonstrate authorized use of an associated security token. Typically, although not exclusively, the proof-of-possession information is encrypted with a key known only to the recipient of the POP token.

Digest – A *digest* is a cryptographic checksum of an octet stream.

Signature – A *signature* [\[XML-Signature\]](#) is a value computed with a cryptographic algorithm and bound to data in such a way that intended recipients of the data can use the signature to verify that the data has not been altered and/or has originated from the signer of the message, providing message integrity and authentication. The signature can be computed and verified with symmetric key algorithms, where the same key is used for signing and verifying, or with asymmetric key algorithms, where different keys are used for signing and verifying (a private and public key pair are used).

Security Token Service – A *security token service (STS)* is a Web service that issues security tokens (see [\[WS-Security\]](#)). That is, it makes assertions based on evidence that it trusts, to whoever trusts it (or to specific recipients). To communicate trust, a service requires proof, such as a signature, to prove knowledge of a security token or set of security token. A service itself can generate tokens or it can rely on a separate STS to issue a security token with its own trust statement (note that for some security token formats this can just be a re-issuance or co-signature). This forms the basis of trust brokering.

Request Security Token (RST) – A *RST* is a message sent to a security token service to request a security token.

Request Security Token Response (RSTR) – A *RSTR* is a response to a request for a security token. In many cases this is a direct response from a security token service to a requestor after receiving an RST message. However, in multi-exchange scenarios the requestor and security token service may exchange multiple RSTR messages before the security token service issues a final RSTR message. One or more RSTRs are contained within a single RequestSecurityTokenResponseCollection (RSTRC).

1.5.1 Notational Conventions

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

Namespace URIs of the general form "some-URI" represents some application-dependent or context-dependent URI as defined in [\[URI\]](#).

This specification uses the following syntax to define outlines for messages:

The syntax appears as an XML instance, but values in italics indicate data types instead of literal values.

Characters are appended to elements and attributes to indicate cardinality:

- "?" (0 or 1)

- "*" (0 or more)
- "+" (1 or more)

The character "|" is used to indicate a choice between alternatives.

The characters "(" and ")" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.

The characters "[" and "]" are used to call out references and property names.

Ellipses (i.e., "...") indicate points of extensibility. Additional children and/or attributes MAY be added at the indicated extension points but MUST NOT contradict the semantics of the parent and/or owner, respectively. By default, if a receiver does not recognize an extension, the receiver SHOULD ignore the extension; exceptions to this processing rule, if any, are clearly indicated below.

XML namespace prefixes (see Table 1) are used to indicate the namespace of the element being defined.

Elements and Attributes defined by this specification are referred to in the text of this document using XPath 1.0 expressions. Extensibility points are referred to using an extended version of this syntax:

- An element extensibility point is referred to using {any} in place of the element name. This indicates that any element name can be used, from any namespace other than the namespace of this specification.
- An attribute extensibility point is referred to using @{any} in place of the attribute name. This indicates that any attribute name can be used, from any namespace other than the namespace of this specification.

In this document reference is made to the `wsu:Id` attribute and the `wsu:Created` and `wsu:Expires` elements in a utility schema (<http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd>). The `wsu:Id` attribute and the `wsu:Created` and `wsu:Expires` elements were added to the utility schema with the intent that other specifications requiring such an ID type attribute or timestamp element could reference it (as is done here).

1.6 Normative References

- [RFC2119]** S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119, Harvard University, March 1997.
<http://www.ietf.org/rfc/rfc2119.txt> .
- [RFC2246]** IETF Standard, "The TLS Protocol", January 1999.
<http://www.ietf.org/rfc/rfc2246.txt>
- [SOAP]** W3C Note, "SOAP: Simple Object Access Protocol 1.1", 08 May 2000.
<http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>.
- [SOAP12]** W3C Recommendation, "SOAP 1.2 Part 1: Messaging Framework", 24 June 2003.
<http://www.w3.org/TR/2003/REC-soap12-part1-20030624/>
- [URI]** T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax", RFC 3986, MIT/LCS, Day Software, Adobe Systems, January 2005.
<http://www.ietf.org/rfc/rfc3986.txt>

- [WS-Addressing]** W3C Recommendation, "Web Services Addressing (WS-Addressing)", 9 May 2006.
<http://www.w3.org/TR/2006/REC-ws-addr-core-20060509>.
- [WS-Security]** OASIS Standard, "OASIS Web Services Security: SOAP Message Security 1.0 (WS-Security 2004)", March 2004.
<http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>
 OASIS Standard, "OASIS Web Services Security: SOAP Message Security 1.1 (WS-Security 2004)", February 2006.
<http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf>
- [WS-Trust]** OASIS Committee Draft, "WS-Trust 1.3", September 2006
<http://docs.oasis-open.org/ws-sx/ws-trust/200512>
- [XML-Encrypt]** W3C Recommendation, "XML Encryption Syntax and Processing", 10 December 2002.
<http://www.w3.org/TR/2002/REC-xmlenc-core-20021210/>.
- [XML-Schema1]** W3C Recommendation, "XML Schema Part 1: Structures Second Edition", 28 October 2004.
<http://www.w3.org/TR/2004/REC-xmlschema-1-20041028/>.
- [XML-Schema2]** W3C Recommendation, "XML Schema Part 2: Datatypes Second Edition", 28 October 2004.
<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>.
- [XML-Signature]** W3C Recommendation, "XML-Signature Syntax and Processing", 12 February 2002.
<http://www.w3.org/TR/2002/REC-xmlenc-core-20021210/>

1.7 Non-Normative References

- [WS-MEX]** "Web Services Metadata Exchange (WS-MetadataExchange)", BEA, Computer Associates, IBM, Microsoft, SAP, Sun Microsystems, Inc., webMethods, September 2004.
- [WS-Policy]** W3C Member Submission, "Web Services Policy 1.2 - Framework", 25 April 2006.
<http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/>
- [WS-PolicyAttachment]** W3C Member Submission, "Web Services Policy 1.2 - Attachment", 25 April 2006.
<http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/>

2 Security Context Token (SCT)

While message authentication is useful for simple or one-way messages, parties that wish to exchange multiple messages typically establish a security context in which to exchange multiple messages. A security context is shared among the communicating parties for the lifetime of a communications session.

In this specification, a security context is represented by the `<wsc:SecurityContextToken>` security token. In the [WS-Security] and [WS-Trust] framework, the following URI is used to represent the token type:

```
http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512/sct
```

The Security Context Token does not support references to it using key identifiers or key names. All references MUST either use an ID (to a `wsu:Id` attribute) or a `<wsse:Reference>` to the `<wsc:Identifier>` element.

Once the context and secret have been established (authenticated), the mechanisms described in [Derived Keys](#) can be used to compute derived keys for each key usage in the secure context.

The following illustration represents an overview of the syntax of the `<wsc:SecurityContextToken>` element. It should be noted that this token supports an open content model to allow context-specific data to be passed.

```
<wsc:SecurityContextToken wsu:Id="..." xmlns:wsc="..." xmlns:wsu="..." ...>
  <wsc:Identifier>...</wsc:Identifier>
  <wsc:Instance>...</wsc:Instance>
  ...
</wsc:SecurityContextToken>
```

The following describes elements and attributes used in a `<wsc:SecurityContextToken>` element.

`/wsc:SecurityContextToken`

This element is a security token that describes a security context.

`/wsc:SecurityContextToken/wsc:Identifier`

This required element identifies the security context using an absolute URI. Each security context URI MUST be unique to both the sender and recipient. It is RECOMMENDED that the value be globally unique in time and space.

`/wsc:SecurityContextToken/wsc:Instance`

When contexts are renewed and given different keys it is necessary to identify the different key instances without revealing the actual key. When present this optional element contains a string that is unique for a given key value for this `wsc:Identifier`. The initial issuance need not contain a `wsc:Instance` element, however, all subsequent issuances with different keys MUST have a `wsc:Instance` element with a unique value.

`/wsc:SecurityContextToken/@wsu:Id`

225 This optional attribute specifies a string label for this element.

226 /wsc:SecurityContextToken/@{any}

227 This is an extensibility mechanism to allow additional attributes, based on schemas, to be added
228 to the element.

229 /wsc:SecurityContextToken/{any}

230 This is an extensibility mechanism to allow additional elements (arbitrary content) to be used.

231
232 The <wsc:SecurityContextToken> token elements MUST be preserved. That is, whatever
233 elements contained within the tag on creation MUST be preserved wherever the token is
234 used. A consumer of a <wsc:SecurityContextToken> token MAY extend the token by
235 appending information. Consequently producers of <wsc:SecurityContextToken> tokens
236 should consider this fact when processing previously generated tokens. A service
237 consuming (processing) a <wsc:SecurityContextToken> token MAY fault if it discovers an
238 element or attribute inside the token that it doesn't understand, or it MAY ignore it. The
239 fault code wsc:UnsupportedContextToken is RECOMMENDED if a fault is raised. The
240 behavior is specified by the services policy [WS-Policy] [WS-PolicyAttachment]. Care should
241 be taken when adding information to tokens to ensure that relying parties can ensure the
242 information has not been altered since the SCT definition does not require a specific way to
243 secure its contents (which as noted above can be appended to).

244
245 Security contexts, like all security tokens, can be referenced using the mechanisms
246 described in [WS-Security] (the <wsse:SecurityTokenReference> element referencing the
247 wsu:Id attribute relative to the XML base document or referencing using the
248 <wsc:Identifier> element's absolute URI). When a token is referenced, the associated
249 key is used. If a token provides multiple keys then specific bindings and profiles must
250 describe how to reference the separate keys. If a specific key instance needs to be
251 referenced, then the global attribute wsc:Instance is included in the <wsse:Reference>
252 sub-element (only when using <wsc:Identifier> references) of the
253 <wsse:SecurityTokenReference> element as illustrated below:

```
254 <wsse:SecurityTokenReference xmlns:wsse="..." xmlns:wsc="...">  
255 <wsse:Reference URI="uuid:..." wsc:Instance="..."/>  
256 </wsse:SecurityTokenReference>
```

257
258 The following sample message illustrates the use of a security context token. In this
259 example a context has been established and the secret is known to both parties. This
260 secret is used to sign the message body.

```
261 (001) <?xml version="1.0" encoding="utf-8"?>  
262 (002) <S11:Envelope xmlns:S11="..." xmlns:ds="..." xmlns:wsse="..."  
263         xmlns:wsu="..." xmlns:wsc="...">  
264 (003)   <S11:Header>  
265 (004)     ...  
266 (005)     <wsse:Security>  
267 (006)       <wsc:SecurityContextToken wsu:Id="MyID">  
268 (007)         <wsc:Identifier>uuid:...</wsc:Identifier>  
269 (008)       </wsc:SecurityContextToken>  
270 (009)     <ds:Signature>  
271 (010)       ...  
272 (011)       <ds:KeyInfo>  
273 (012)         <wsse:SecurityTokenReference>  
274 (013)           <wsse:Reference URI="#MyID"/>
```

```

275      (014)          </wsse:SecurityTokenReference>
276      (015)          </ds:KeyInfo>
277      (016)          </ds:Signature>
278      (017)          </wsse:Security>
279      (018)          </S11:Header>
280      (019)          <S11:Body wsu:Id="MsgBody">
281      (020)              <tru:StockSymbol
282                          xmlns:tru="http://fabrikam123.com/payloads">
283                          QQQ
284                      </tru:StockSymbol>
285      (021)          </S11:Body>
286      (022) </S11:Envelope>

```

287

288 Let's review some of the key sections of this example:

289 Lines (003)-(018) contain the SOAP message headers.

290 Lines (005)-(017) represent the `<wsse:Security>` header block. This contains the security-
 291 related information for the message.

292 Lines (006)-(008) specify a [security token](#) that is associated with the message. In this case
 293 it is a security context token. Line (007) specifies the unique ID of the context.

294 Lines (009)-(016) specify the digital signature. In this example, the signature is based on
 295 the security context (specifically the secret/key associated with the context). Line (010)
 296 represents the typical contents of an XML Digital Signature which, in this case, references
 297 the body and potentially some of the other headers expressed by line (004).

298

299 Lines (012)-(014) indicate the key that was used for the signature. In this case, it is the
 300 security context token included in the message. Line (013) provides a URI link to the
 301 security context token specified in Lines (006)-(008).

302 The body of the message is represented by lines (019)-(021).

3 Establishing Security Contexts

A security context needs to be created and shared by the communicating parties before being used. This specification defines three different ways of establishing a security context among the parties of a secure communication.

Security context token created by a security token service – The context initiator asks a security token service to create a new security context token. The newly created security context token is distributed to the parties through the mechanisms defined here and in [WS-Trust]. For this scenario the initiating party sends a `<wst:RequestSecurityToken>` request to the token service and a `<wst:RequestSecurityTokenResponseCollection>` containing a `<wst:RequestSecurityTokenResponse>` is returned. The response contains a `<wst:RequestedSecurityToken>` containing (or pointing to) the new security context token and a `<wst:RequestedProofToken>` pointing to the "secret" for the returned context. The requestor then uses the security context token (with [WS-Security]) when securing messages to applicable services.

Security context token created by one of the communicating parties and propagated with a message – The initiator creates a security context token and sends it to the other parties on a message using the mechanisms described in this specification and in [WS-Trust]. This model works when the sender is trusted to always create a new security context token. For this scenario the initiating party creates a security context token and issues a signed unsolicited `<wst:RequestSecurityTokenResponse>` to the other party. The message contains a `<wst:RequestedSecurityToken>` containing (or pointing to) the new security context token and a `<wst:RequestedProofToken>` pointing to the "secret" for the security context token. The recipient can then choose whether or not to accept the security context token. As described in [WS-Trust], the `<wst:RequestSecurityTokenResponse>` element MAY be in the `<wst:RequestSecurityTokenResponseCollection>` within a body or inside a header block. It should be noted that unless delegation tokens are used, this scenario requires that parties trust each other to share a secret key (and non-repudiation is probably not possible). As receipt of these messages may be expensive, and because a recipient may receive multiple messages, the `.../wst:RequestSecurityTokenResponse/@Context` attribute in [WS-Trust] allows the initiator to specify a URI to indicate the intended usage (allowing processing to be optimized).

Security context token created through negotiation/exchanges – When there is a need to negotiate or participate in a sequence of message exchanges among the participants on the contents of the security context token, such as the shared secret, this specification allows the parties to exchange data to establish a security context. For this scenario the initiating party sends a `<wst:RequestSecurityToken>` request to the other party and a `<wst:RequestSecurityTokenResponse>` is returned. It is RECOMMENDED that the framework described in [WS-Trust] be used; however, the type of exchange will likely vary. If appropriate, the basic challenge-response definition in [WS-Trust] is RECOMMENDED. Ultimately (if successful), a final response contains a

`<wst:RequestedSecurityToken>` containing (or pointing to) the new security context and a `<wst:RequestedProofToken>` pointing to the "secret" for the context.

If an SCT is received, but the key sizes are not supported, then a fault SHOULD be generated using the `wsc:UnsupportedContextToken` fault code unless another more specific fault code is available.

3.1 SCT Binding of WS-Trust

This binding describes how to use [WS-Trust] to request and return SCTs. This binding builds on the issuance binding for [WS-Trust] (note that other sections of this specification define new separate bindings of [WS-Trust]). Consequently, aspects of the issuance binding apply to this binding unless otherwise stated. For example, the token request type is the same as in the issuance binding.

When requesting and returning security context tokens the following Action URIs [WS-Addressing] are used (note that a specialized action is used here because of the specialized semantics of SCTs):

```
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT
```

As with all token services, the options supported may be limited. This is especially true of SCTs because the issuer may only be able to issue tokens for itself and quite often will only support a specific set of algorithms and parameters as expressed in its policy.

SCTs are not required to have lifetime semantics. That is, some SCTs may have specific lifetimes and others may be bound to other resources rather than have their own lifetimes.

Since the SCT binding builds on the issuance binding, it allows the optional extensions defined for the issuance binding including the use of exchanges. Subsequent profiles MAY restrict the extensions and types and usage of exchanges.

3.2 SCT Request Example without Target Scope

The following illustrates a request for a SCT from a security token service. The request in this example contains no information concerning the Web Service with whom the requestor wants to communicate securely (e.g. using the `wsp:AppliesTo` parameter in the RST). In order for the security token service to process this request it must have prior knowledge for which Web Service the requestor needs a token. This may be preconfigured although it is typically passed in the RST. In this example the key is encrypted for the recipient (security token service) using the token service's X.509 certificate as per XML Encryption [XML-Encrypt]. The encrypted data (using the encrypted key) contains a `<wsse:UsernameToken>` token that the recipient uses to authorize the request. The request is secured (integrity) using the X.509 certificate of the requestor. The response encrypts the proof information using the requestor's X.509 certificate and secures the message (integrity) using the token service's X.509 certificate. Note that the details of XML Signature and XML Encryption have been omitted; refer to [WS-Security] for additional details. It should be noted that if the requestor doesn't have an X.509 this scenario could be achieved using a TLS [RFC2246] connection or by creating an ephemeral key.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wst="..." xmlns:xenc="...">
  <S11:Header>
    ...
```

```

394     <wsa:Action xmlns:wsa="...">
395     http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT
396     </wsa:Action>
397     ...
398     <wsse:Security>
399         <xenc:EncryptedKey>
400             ...
401             </xenc:EncryptedKey>
402             <xenc:EncryptedData Id="encUsernameToken">
403                 ... encrypted username token (whose id is myToken) ...
404             </xenc:EncryptedData>
405             <ds:Signature xmlns:ds="...">
406                 ...
407                 <ds:KeyInfo>
408                     <wsse:SecurityTokenReference>
409                         <wsse:Reference URI="#myToken"/>
410                     </wsse:SecurityTokenReference>
411                 </ds:KeyInfo>
412             </ds:Signature>
413         </wsse:Security>
414         ...
415     </S11:Header>
416     <S11:Body wsu:Id="req">
417         <wst:RequestSecurityToken>
418             <wst:TokenType>
419                 http://docs.oasis-open.org/ws-sx/ws-
420 secureconversation/200512/sct
421             </wst:TokenType>
422             <wst:RequestType>
423                 http://docs.oasis-open.org/ws-sx/ws-trust/200512/Issue
424             </wst:RequestType>
425         </wst:RequestSecurityToken>
426     </S11:Body>
427 </S11:Envelope>

```

```

428
429 <S11:Envelope xmlns:S11="..."
430     xmlns:wst="..." xmlns:wsc="..." xmlns:xenc="...">
431     <S11:Header>
432         ...
433         <wsa:Action xmlns:wsa="...">
434         http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT
435         </wsa:Action>
436         ...
437     </S11:Header>
438     <S11:Body>
439         <wst:RequestSecurityTokenResponseCollection>
440             <wst:RequestSecurityTokenResponse>
441                 <wst:RequestedSecurityToken>
442                     <wsc:SecurityContextToken>
443                         <wsc:Identifier>uuid:...</wsc:Identifier>
444                     </wsc:SecurityContextToken>
445                 </wst:RequestedSecurityToken>
446                 <wst:RequestedProofToken>
447                     <xenc:EncryptedKey Id="newProof">
448                         ...
449                     </xenc:EncryptedKey>
450                 </wst:RequestedProofToken>
451             </wst:RequestSecurityTokenResponse>
452         </wst:RequestSecurityTokenResponseCollection>
453     </S11:Body>
454 </S11:Envelope>

```

3.3 SCT Request Example with Target Scope

There are scenarios where a security token service is used to broker trust using SCT tokens between requestors and Web Services endpoints. In these cases it is typical for requestors to identify the target Web Service in the RST.

In the example below the requestor uses the element <wsp:AppliesTo> with an endpoint reference as described in [WS-Trust] in the SCT request to indicate the Web Service the token is needed for.

In the request example below the <wst:TokenType> element is omitted. This requires that the security token service know what type of token the endpoint referenced in the <wsp:AppliesTo> element expects.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wst="..." xmlns:xenc="..." xmlns:wsp="..." xmlns:wsa="...">
  <S11:Header>
    ...
    <wsa:Action xmlns:wsa="...">
      http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT
    </wsa:Action>
    ...
    <wsse:Security>
      ...
    </wsse:Security>
    ...
  </S11:Header>
  <S11:Body wsu:Id="req">
    <wst:RequestSecurityToken>
      <wst:RequestType>
        http://docs.oasis-open.org/ws-sx/ws-trust/200512/Issue
      </wst:RequestType>
      <wsp:AppliesTo>
        <wsa:EndpointReference>
          <wsa:Address>http://example.org/webService</wsa:Address>
        </wsa:EndpointReference>
      </wsp:AppliesTo>
    </wst:RequestSecurityToken>
  </S11:Body>
</S11:Envelope>
```

```
<S11:Envelope xmlns:S11="..."
  xmlns:wst="..." xmlns:wsc="..." xmlns:xenc="..." xmlns:wsp="..."
  xmlns:wsa="...">
  <S11:Header>
    <wsa:Action xmlns:wsa="...">
      http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT
    </wsa:Action>
    ...
  </S11:Header>
  <S11:Body>
    <wst:RequestSecurityTokenResponseCollection>
      <wst:RequestSecurityTokenResponse>
        <wst:RequestedSecurityToken>
          <wsc:SecurityContextToken>
            <wsc:Identifier>uuid:...</wsc:Identifier>
          </wsc:SecurityContextToken>
        </wst:RequestedSecurityToken>
        <wst:RequestedProofToken>
          <xenc:EncryptedKey Id="newProof">
            ...
          </xenc:EncryptedKey>
        </wst:RequestedProofToken>
      </wst:RequestSecurityTokenResponse>
    </wst:RequestSecurityTokenResponseCollection>
  </S11:Body>
</S11:Envelope>
```



```

513         </wst:RequestedProofToken>
514         <wsp:AppliesTo>
515             <wsa:EndpointReference>
516                 <wsa:Address>http://example.org/webService</wsa:Address>
517             </wsa:EndpointReference>
518         </wsp:AppliesTo>
519     </wst:RequestSecurityTokenResponse>
520 </wst:RequestSecurityTokenResponseCollection>
521 </S11:Body>
522 </S11:Envelope>

```

3.4 SCT Propagation Example

The following illustrates propagating a context to another party. This example does not contain any information regarding the Web Service the SCT is intended for (e.g. using the `wsp:AppliesTo` parameter in the RST).

```

528 <S11:Envelope xmlns:S11="..."
529     xmlns:wst="..." xmlns:wsc="..." xmlns:xenc="..." >
530     <S11:Header>
531         ...
532     </S11:Header>
533     <S11:Body>
534         <wst:RequestSecurityTokenResponse>
535             <wst:RequestedSecurityToken>
536                 <wsc:SecurityContextToken>
537                     <wsc:Identifier>uuid:...</wsc:Identifier>
538                 </wsc:SecurityContextToken>
539             </wst:RequestedSecurityToken>
540             <wst:RequestedProofToken>
541                 <xenc:EncryptedKey Id="newProof">
542                     ...
543                 </xenc:EncryptedKey>
544             </wst:RequestedProofToken>
545         </wst:RequestSecurityTokenResponse>
546     </S11:Body>
547 </S11:Envelope>

```

4 Amending Contexts

When an SCT is created, a set of claims is associated with it. There are times when an existing SCT needs to be amended to carry additional claims (note that the decision as to who is authorized to amend a context is a service-specific decision). This is done using the SCT Amend binding. In such cases an explicit request is made to amend the claims associated with an SCT. It should be noted that using the mechanisms described in [WS-Trust], an issuer MAY, at any time, return an amended SCT by issuing an unsolicited (not explicitly requested) SCT inside an RSTR (either as a separate message or in a header).

The following Action URIs are used with this binding:

```
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Amend
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Amend
```

This binding allows optional extensions but DOES NOT allow key semantics to be altered.

Proof of possession of the key associated with the security context MUST be proven in order for context to be amended. It is RECOMMENDED that the proof of possession is done by creating a signature over the message body and key headers using the key associated with the security context.

Additional claims to amend the security context with MUST be indicated by providing signatures over the security context signature created using the key associated with the security context. Those additional signatures are used to prove additional security tokens that carry claims to augment the security context.

This binding uses the request type from the issuance binding.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wst="..." xmlns:wsc="...">
  <S11:Header>
    ...
    <wsa:Action xmlns:wsa="...">
      http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Amend
    </wsa:Action>
    ...
    <wsse:Security>
      <xx:CustomToken wsu:Id="cust" xmlns:xx="...">
        ...
      </xx:CustomToken>
      <ds:Signature xmlns:ds="...">
        ...signature over #sig1 using #cust...
      </ds:Signature>
      <wsc:SecurityContextToken wsu:Id="sct">
        <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
      </wsc:SecurityContextToken>
      <ds:Signature xmlns:ds="..." Id="sig1">
        ...signature over body and key headers using #sct...
      </ds:Signature>
      <ds:KeyInfo>
        <wsse:SecurityTokenReference>
          <wsse:Reference URI="#sct"/>
        </wsse:SecurityTokenReference>
      </ds:KeyInfo>
      ...
    </ds:Signature>
```

```

597     </wsse:Security>
598     ...
599 </S11:Header>
600 <S11:Body wsu:Id="req">
601     <wst:RequestSecurityToken>
602         <wst:RequestType>
603             http://docs.oasis-open.org/ws-sx/ws-trust/200512/Issue
604         </wst:RequestType>
605     </wst:RequestSecurityToken>
606 </S11:Body>
607 </S11:Envelope>

```

```

608
609 <S11:Envelope xmlns:S11="..." xmlns:wst="..." xmlns:wsc="...">
610     <S11:Header>
611         ...
612         <wsa:Action xmlns:wsa="...">
613             http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Amend
614         </wsa:Action>
615         ...
616     </S11:Header>
617     <S11:Body>
618         <wst:RequestSecurityTokenResponseCollection>
619             <wst:RequestSecurityTokenResponse>
620                 <wst:RequestedSecurityToken>
621                     <wsc:SecurityContextToken>
622                         <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
623                     </wsc:SecurityContextToken>
624                 </wst:RequestedSecurityToken>
625             </wst:RequestSecurityTokenResponse>
626         </wst:RequestSecurityTokenResponseCollection>
627     </S11:Body>
628 </S11:Envelope>

```

5 Renewing Contexts

When a security context is created it typically has an associated expiration. If a requestor desires to extend the duration of the token it uses a custom binding of the renewal mechanism defined in WS-Trust. The following Action URIs are used with this binding:

```
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Renew
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Renew
```

This binding allows optional extensions but DOES NOT allow key semantics to be altered.

A renewal MUST include re-authentication of the original claims because the original claims might have an expiration time that conflicts with the requested expiration time in the renewal request. Because the security context token issuer is not required to cache such information from the original issuance request, the requestor is required to re-authenticate the original claims in every renewal request. It is RECOMMENDED that the original claims re-authentication is done in the same way as in the original token issuance request.

Proof of possession of the key associated with the security context MUST be proven in order for security context to be renewed. It is RECOMMENDED that this is done by creating the original claims signature over the signature that signs message body and key headers.

During renewal, new key material MAY be exchanged. Such key material MUST NOT be protected using the existing session key.

This binding uses the request type from the renewal binding.

The following example illustrates a renewal which re-proves the original claims.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wst="..." xmlns:wsc="...">
  <S11:Header>
    ...
    <wsa:Action xmlns:wsa="...">
      http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Renew
    </wsa:Action>
    ...
    <wsse:Security>
      <xx:CustomToken wsu:Id="cust" xmlns:xx="...">
        ...
      </xx:CustomToken>
      <ds:Signature xmlns:ds="..." Id="sig1">
        ... signature over body and key headers using #cust...
      </ds:Signature>
      <wsc:SecurityContextToken wsu:Id="sct">
        <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
      </wsc:SecurityContextToken>
      <ds:Signature xmlns:ds="..." Id="sig2">
        ... signature over #sig1 using #sct ...
      </ds:Signature>
    </wsse:Security>
    ...
  </S11:Header>
  <S11:Body wsu:Id="req">
    <wst:RequestSecurityToken>
      <wst:RequestType>
```

```

677         http://docs.oasis-open.org/ws-sx/ws-trust/200512/Renew
678     </wst:RequestType>
679     <wst:RenewTarget>
680         <wsse:SecurityTokenReference>
681             <wsse:Reference URI="#sct"/>
682         </wsse:SecurityTokenReference>
683     </wst:RenewTarget>
684     <wst:Lifetime>...</wst:Lifetime>
685 </wst:RequestSecurityToken>
686 </S11:Body>
687 </S11:Envelope>

```

```

688
689 <S11:Envelope xmlns:S11="..." xmlns:wst="..." xmlns:wsc="...">
690     <S11:Header>
691         ...
692         <wsa:Action xmlns:wsa="...">
693             http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Renew
694         </wsa:Action>
695         ...
696     </S11:Header>
697     <S11:Body>
698         <wst:RequestSecurityTokenResponseCollection>
699             <wst:RequestSecurityTokenResponse>
700                 <wst:RequestedSecurityToken>
701                     <wsc:SecurityContextToken>
702                         <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
703                         <wsc:Instance>UUID2</wsc:Instance>
704                     </wsc:SecurityContextToken>
705                 </wst:RequestedSecurityToken>
706                 <wst:Lifetime>...</wst:Lifetime>
707             </wst:RequestSecurityTokenResponse>
708         </wst:RequestSecurityTokenResponseCollection>
709     </S11:Body>
710 </S11:Envelope>

```

6 Canceling Contexts

It is not uncommon for a requestor to be done with a security context token before it expires. In such cases the requestor can explicitly cancel the security context using this specialized binding based on the WS-Trust Cancel binding.

The following Action URIs are used with this binding:

```
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Cancel
http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Cancel
```

Once a security context has been cancelled it MUST NOT be allowed for authentication or authorization or allow renewal.

Proof of possession of the key associated with the security context MUST be proven in order for security context to be cancelled. It is RECOMMENDED that this is done by creating a signature over the message body and key headers using the key associated with the security context.

This binding uses the Cancel request type from WS-Trust.

As described in WS-Trust the RSTR cancel message is informational and the context is cancelled once the cancel RST is processed even in the cancel RSTR is never received by the requestor.

The following example illustrates canceling a context.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wst="..." xmlns:wsc="...">
  <S11:Header>
    ...
    <wsa:Action xmlns:wsa="...">
      http://docs.oasis-open.org/ws-sx/ws-trust/200512/RST/SCT/Cancel
    </wsa:Action>
    ...
    <wsse:Security>
      <wsc:SecurityContextToken wsu:Id="sct">
        <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
      </wsc:SecurityContextToken>
      <ds:Signature xmlns:ds="..." Id="sig1">
        ...signature over body and key headers using #sct...
      </ds:Signature>
    </wsse:Security>
    ...
  </S11:Header>
  <S11:Body wsu:Id="req">
    <wst:RequestSecurityToken>
      <wst:RequestType>
        http://docs.oasis-open.org/ws-sx/ws-trust/200512/Cancel
      </wst:RequestType>
      <wst:CancelTarget>
        <wsse:SecurityTokenReference>
          <wsse:Reference URI="#sct"/>
        </wsse:SecurityTokenReference>
      </wst:CancelTarget>
    </wst:RequestSecurityToken>
  </S11:Body>
</S11:Envelope>
```

```

760         </wsse:SecurityTokenReference>
761         </wst:CancelTarget>
762     </wst:RequestSecurityToken>
763 </S11:Body>
764 </S11:Envelope>

```

```

765
766 <S11:Envelope xmlns:S11="..." xmlns:wst="..." >
767   <S11:Header>
768     ...
769     <wsa:Action xmlns:wsa="...">
770       http://docs.oasis-open.org/ws-sx/ws-trust/200512/RSTR/SCT/Cancel
771     </wsa:Action>
772     ...
773   </S11:Header>
774   <S11:Body>
775     <wst:RequestSecurityTokenResponseCollection>
776       <wst:RequestSecurityTokenResponse>
777         <wst:RequestedTokenCancelled/>
778       </wst:RequestSecurityTokenResponse>
779     </wst:RequestSecurityTokenResponseCollection>
780   </S11:Body>
781 </S11:Envelope>

```

7 Deriving Keys

A security context token implies or contains a shared secret. This secret MAY be used for signing and/or encrypting messages, but it is RECOMMENDED that derived keys be used for signing and encrypting messages associated only with the security context.

Using a common secret, parties may define different key derivations to use. For example, four keys may be derived so that two parties can sign and encrypt using separate keys. In order to keep the keys fresh (prevent providing too much data for analysis), subsequent derivations may be used. We introduce the `<wsc:DerivedKeyToken>` token as a mechanism for indicating which derivation is being used within a given message.

The derived key mechanism can use different algorithms for deriving keys. The algorithm is expressed using a URI. This specification defines one such algorithm.

As well, while presented here using security context tokens, the `<wsc:DerivedKeyToken>` token can be used to derive keys from any security token that has a shared secret, key, or key material.

We use a subset of the mechanism defined for TLS in RFC 2246. Specifically, we use the P_SHA-1 function to generate a sequence of bytes that can be used to generate security keys. We refer to this algorithm as:

```
http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512/dk/p_shal
```

This function is used with three values – *secret*, *label*, and *seed*. The secret is the shared secret that is exchanged (note that if two secrets were securely exchanged, possible as part of an initial exchange, they are concatenated in the order they were sent/received). Secrets are processed as octets representing their binary value (value prior to encoding). The label is the concatenation of the client's label and the service's label. These labels can be discovered in each party's policy (or specifically within a `<wsc:DerivedKeyToken>` token). Labels are processed as UTF-8 encoded octets. If either isn't specified in the policy, then a default value of "WS-SecureConversation" (represented as UTF-8 octets) is used. The seed is the concatenation of nonce values (if multiple were exchanged) that were exchanged (initiator + receiver). The nonce is processed as a binary octet sequence (the value prior to base64 encoding). The nonce seed is required, and MUST be generated by one or more of the communicating parties. The P_SHA-1 function has two parameters – *secret* and *value*. We concatenate the *label* and the *seed* to create the *value*. That is:

```
P_SHA1 (secret, label + seed)
```

At this point, both parties can use the P_SHA-1 function to generate shared keys as needed. For this protocol, we don't define explicit derivation uses.

The `<wsc:DerivedKeyToken>` element is used to indicate that the key for a specific reference is generated from the function. This is so that explicit security tokens, secrets, or key material need not be exchanged as often thereby increasing efficiency and overall scalability. However, parties MUST mutually agree on specific derivations (e.g. the first 128 bits is the client's signature key, the next 128 bits in the client's encryption key, and so on). The policy presents a method for specifying this information. The RECOMMENDED approach is to use separate nonces and have independently generated keys for signing and encrypting in each direction. Furthermore, it is RECOMMENDED that new keys be derived for each message (i.e., previous nonces are not re-used).

Once the parties determine a shared secret to use as the basis of a key generation sequence, an initial key is generated using this sequence. When a new key is required, a new `<wsc:DerivedKeyToken>` may be passed referencing the previously generated key. The recipient then knows to use the sequence to generate a new key, which will match that specified in the security token. If both parties pre-agree on key sequencing, then additional token exchanges are not required.

For keys derived using a shared secret from a security context, the `<wsse:SecurityTokenReference>` element SHOULD be used to reference the `<wsc:SecurityContextToken>`. Basically, a signature or encryption references a `<wsc:DerivedKeyToken>` in the `<wsse:Security>` header that, in turn, references the `<wsc:SecurityContextToken>`.

Derived keys are expressed as security tokens. The following URI is used to represent the token type:

```
http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512/dk
```

The derived key token does not support references using key identifiers or key names. All references MUST use an ID (to a `wsu:Id` attribute) or a URI reference to the `<wsc:Identifier>` element in the SCT.

7.1 Syntax

The following illustrates the syntax for `<wsc:DerivedKeyToken>` is as follows:

```
<wsc:DerivedKeyToken wsu:Id="..." Algorithm="..." xmlns:wsc="..."
xmlns:wsse="..." xmlns:wsu="...">
  <wsse:SecurityTokenReference>...</wsse:SecurityTokenReference>
  <wsc:Properties>...</wsc:Properties>
  <wsc:Generation>...</wsc:Generation>
  <wsc:Offset>...</wsc:Offset>
  <wsc:Length>...</wsc:Length>
  <wsc:Label>...</wsc:Label>
  <wsc:Nonce>...</wsc:Nonce>
</wsc:DerivedKeyToken>
```

The following describes the attributes and tags listed in the schema overview above:

`/wsc:DerivedKeyToken`

This specifies a key that is derived from a shared secret.

870 /wsc:DerivedKeyToken/@wsu:Id
 871 This optional attribute specifies an XML ID that can be used locally to reference this element.

872 /wsc:DerivedKeyToken/@Algorithm
 873 This optional URI attribute specifies key derivation algorithm to use. This specification predefines
 874 the P_SHA1 algorithm described above. If this attribute isn't specified, this algorithm is assumed.

875 /wsc:DerivedKeyToken/wsse:SecurityTokenReference
 876 This optional element is used to specify security context token, security token, or shared
 877 key/secret used for the derivation. If not specified, it is assumed that the recipient can determine
 878 the shared key from the message context. If the context cannot be determined, then a fault such
 879 as wsc:UnknownDerivationSource should be raised.

880 /wsc:DerivedKeyToken/wsc:Properties
 881 This optional element allows metadata to be associated with this derived key. For example, if the
 882 <wsc:Name> property is defined, this derived key is given a URI name that can then be used as
 883 the source for other derived keys. The <wsc:Nonce> and <wsc:Label> elements can be
 884 specified as properties and indicate the nonce and label to use (defaults) for all keys derived from
 885 this key.

886 /wsc:DerivedKeyToken/wsc:Properties/wsc:Name
 887 This optional element is used to give this derived key a URI name that can then be used as the
 888 source for other derived keys.

889 /wsc:DerivedKeyToken/wsc:Properties/wsc:Label
 890 This optional element defines a label to use for all keys derived from this key. See
 891 /wsc:DerivedKeyToken/wsc:Label defined below.

892 /wsc:DerivedKeyToken/wsc:Properties/wsc:Nonce
 893 This optional element defines a label to use for all keys derived from this key. See
 894 /wsc:DerivedKeyToken/wsc:Nonce defined below.

895 /wsc:DerivedKeyToken/wsc:Properties/{any}
 896 This is an extensibility mechanism to allow additional elements (arbitrary content) to be used.

897 /wsc:DerivedKeyToken/wsc:Generation
 898 If fixed-size keys (generations) are being generated, then this optional element can be used to
 899 specify which generation of the key to use. The value of this element is an unsigned long value
 900 indicating the generation number to use (beginning with zero). This element MUST NOT be used
 901 if the <wsc:Offset> element is specified. Specifying this element is equivalent to specifying the
 902 <wsc:Offset> and <wsc:Length> elements having multiplied out the values. That is, offset =
 903 (generation) * fixed_size and length = fixed_size.

904 /wsc:DerivedKeyToken/wsc:Offset
 905 If fixed-size keys are not being generated, then the <wsc:Offset> and <wsc:Length>
 906 elements indicate where in the byte stream to find the generated key. This specifies the ordering
 907 (in bytes) of the generated output. The value of this optional element is an unsigned long value
 908 indicating the byte position (starting at 0). For example, 0 indicates the first byte of output and 16
 909 indicates the 17th byte of generated output. This element MUST NOT be used if the
 910 <wsc:Generation> element is specified. It should be noted that not all algorithms will support
 911 the <wsc:Offset> and <wsc:Length> elements.

912 /wsc:DerivedKeyToken/wsc:Length
 913 This element specifies the length (in bytes) of the derived key. This optional element can be
 914 specified in conjunction with <wsc:Offset> or <wsc:Generation>. If this isn't specified, it is

915 assumed that the recipient knows the key size to use. The value of this element is an unsigned
916 long value indicating the size of the key in bytes (e.g., 16).

917 /wsc:DerivedKeyToken/wsc:Label

918 The label can be specified within a <wsc:DerivedKeyToken> using the wsc:Label
919 element. If the label isn't specified then a default value of "WS-
920 SecureConversationWS-SecureConversation" (represented as UTF-8 octets) is used.
921 Labels are processed as UTF-8 encoded octets..

922 /wsc:DerivedKeyToken/wsc:Nonce

923 If specified, this optional element specifies a base64 encoded nonce that is used in the key
924 derivation function for this derived key. If this isn't specified, it is assumed that the recipient
925 knows the nonce to use. Note that once a nonce is used for a derivation sequence, the same
926 nonce SHOULD be used for all subsequent derivations.

927

928 If additional information is not specified (such as explicit elements or policy), then the
929 following defaults apply:

930 The offset is 0

931 The length is 32 bytes (256 bits)

932

933 It is RECOMMENDED that separate derived keys be used to strengthen the cryptography. If
934 multiple keys are used, then care should be taken not to derive too many times and risk key
935 attacks.

936 7.2 Examples

937 The following example illustrates a message sent using two derived keys, one for signing
938 and one for encrypting:

```
939 <S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."  
940   xmlns:xenc="..." xmlns:wsc="..." xmlns:ds="...">  
941   <S11:Header>  
942     <wsse:Security>  
943       <wsc:SecurityContextToken wsu:Id="ctx2">  
944         <wsc:Identifier>uuid:...UUID2...</wsc:Identifier>  
945       </wsc:SecurityContextToken>  
946       <wsc:DerivedKeyToken wsu:Id="dk2">  
947         <wsse:SecurityTokenReference>  
948           <wsse:Reference URI="#ctx2"/>  
949         </wsse:SecurityTokenReference>  
950         <wsc:Nonce>KJHFRE...</wsc:Nonce>  
951       </wsc:DerivedKeyToken>  
952     <xenc:ReferenceList>  
953       ...  
954       <ds:KeyInfo>  
955         <wsse:SecurityTokenReference>  
956           <wsse:Reference URI="#dk2"/>  
957         </wsse:SecurityTokenReference>  
958       </ds:KeyInfo>  
959       ...  
960     </xenc:ReferenceList>  
961     <wsc:SecurityContextToken wsu:Id="ctx1">  
962       <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>  
963     </wsc:SecurityContextToken>  
964     <wsc:DerivedKeyToken wsu:Id="dk1">  
965       <wsse:SecurityTokenReference>  
966         <wsse:Reference URI="#ctx1"/>
```

```

967         </wsse:SecurityTokenReference>
968         <wsc:Nonce>KJHFRE...</wsc:Nonce>
969     </wsc:DerivedKeyToken>
970     <xenc:ReferenceList>
971         ...
972     <ds:KeyInfo>
973         <wsse:SecurityTokenReference>
974             <wsse:Reference URI="#dk1"/>
975         </wsse:SecurityTokenReference>
976     </ds:KeyInfo>
977     ...
978 </xenc:ReferenceList>
979 </wsse:Security>
980 ...
981 </S11:Header>
982 <S11:Body>
983     ...
984 </S11:Body>
985 </S11:Envelope>

```

The following illustrates the syntax for a derived key based on the 3rd generation of the shared key identified in the specified security context:

```

989 <wsc:DerivedKeyToken xmlns:wsc="..." xmlns:wsse="...">
990     <wsse:SecurityTokenReference>
991         <wsse:Reference URI="#ctx1"/>
992     </wsse:SecurityTokenReference>
993     <wsc:Generation>2</wsc:Generation>
994 </wsc:DerivedKeyToken>

```

The following illustrates the syntax for a derived key based on the 1st generation of a key derived from an existing derived key (4th generation):

```

998 <wsc:DerivedKeyToken xmlns:wsc="...">
999     <wsc:Properties>
1000         <wsc:Name>.../derivedKeySource</wsc:Name>
1001         <wsc:Label>NewLabel</wsc:Label>
1002         <wsc:Nonce>FHFE...</wsc:Nonce>
1003     </wsc:Properties>
1004     <wsc:Generation>3</wsc:Generation>
1005 </wsc:DerivedKeyToken>

```

```

1007 <wsc:DerivedKeyToken wsu:Id="newKey" xmlns:wsc="..." xmlns:wsse="..." >
1008     <wsse:SecurityTokenReference>
1009         <wsse:Reference URI=".../derivedKeySource"/>
1010     </wsse:SecurityTokenReference>
1011     <wsc:Generation>0</wsc:Generation>
1012 </wsc:DerivedKeyToken>

```

In the example above we have named a derived key so that other keys can be derived from it. To do this we use the `<wsc:Properties>` element name tag to assign a global name attribute. Note that in this example, the ID attribute could have been used to name the base derived key if we didn't want it to be a globally named resource. We have also included the `<wsc:Label>` and `<wsc:Nonce>` elements as metadata properties indicating how to derive sequences of this derivation.

7.3 Implied Derived Keys

This specification also defines a shortcut mechanism for referencing certain types of derived keys. Specifically, a `@wsc:Nonce` attribute can also be added to the security token reference (STR) defined in the [WS-Security] specification. When present, it indicates that the key is not in the referenced token, but is a key derived from the referenced token's key/secret. The `@wsc:Length` attribute can be used in conjunction with `@wsc:Nonce` in the security token reference (STR) to indicate the length of the derived key. The value of this attribute is an unsigned long value indicating the size of the key in bytes. If this attribute isn't specified, the default derived key length value is 32.

Consequently, the following two illustrations are functionally equivalent:

```
<wsse:Security xmlns:wsc="..." xmlns:wsse="..." xmlns:xx="..."
xmlns:ds="..." xmlns:wsu="...">
  <xx:MyToken wsu:Id="base">...</xx:MyToken>
  <wsc:DerivedKeyToken wsu:Id="newKey">
    <wsse:SecurityTokenReference>
      <wsse:Reference URI="#base"/>
    </wsse:SecurityTokenReference>
    <wsc:Nonce>...</wsc:Nonce>
  </wsc:DerivedKeyToken>
  <ds:Signature>
    ...
    <ds:KeyInfo>
      <wsse:SecurityTokenReference>
        <wsse:Reference URI="#newKey"/>
      </wsse:SecurityTokenReference>
    </ds:KeyInfo>
  </ds:Signature>
</wsse:Security>
```

This is functionally equivalent to the following:

```
<wsse:Security xmlns:wsc="..." xmlns:wsse="..." xmlns:xx="..."
xmlns:ds="..." xmlns:wsu="...">
  <xx:MyToken wsu:Id="base">...</xx:MyToken>
  <ds:Signature>
    ...
    <ds:KeyInfo>
      <wsse:SecurityTokenReference wsc:Nonce="...">
        <wsse:Reference URI="#base"/>
      </wsse:SecurityTokenReference>
    </ds:KeyInfo>
  </ds:Signature>
</wsse:Security>
```

8 Associating a Security Context

For a variety of reasons it may be necessary to reference a Security Context Token. These references can be broken into two general categories: references from within the `<wsse:Security>` element to a token also within the `<wsse:Security>` element, generally used to indicate the key used in a signature or encryption operation and references from other parts of the SOAP envelope, for example to specify a token to be used in some particular way. References within the `<wsse:Security>` element can further be divided into reference to an SCT found within the message and references to a SCT not present in the message.

The Security Context Token does not support references to it using key identifiers or key names. All references **MUST** either use an ID (to a `wsu:Id` attribute) or a `<wsse:Reference>` to the `<wsc:Identifier>` element.

References using an ID are message-specific. References using the `<wsc:Identifier>` element value are message independent.

If the SCT is referenced from within the `<wsse:Security>` element or from an RST or RSTR, it is **RECOMMENDED** that these references be message independent, but these references **MAY** be message-specific.

When an SCT located in the `wsse:Security` element is referenced from outside the `<wsse:Security>` element, a message independent referencing mechanisms **MUST** be used, to enable a cleanly layered processing model unless there is a prior agreement between the involved parties to use message-specific referencing mechanism.

When an SCT is referenced from within the `<wsse:Security>` element, but the SCT is not present in the message, (presumably because it was transmitted in a previous message) a message independent referencing mechanism **MUST** be used.

The following example illustrates associating a specific security context with an action.

```
<S11:Envelope xmlns:S11="..." xmlns:wsse="..." xmlns:wsu="..."
  xmlns:wsc="...">
  <S11:Header>
    ...
    <wsse:Security>
      <wsc:SecurityContextToken wsu:Id="sct1">
        <wsc:Identifier>uuid:...UUID1...</wsc:Identifier>
      </wsc:SecurityContextToken>
      <ds:Signature xmlns:ds="...">
        ...signature over body and key headers using #sct1...
      </ds:Signature>
      <wsc:SecurityContextToken wsu:Id="sct2">
        <wsc:Identifier>uuid:...UUID2...</wsc:Identifier>
      </wsc:SecurityContextToken>
      <ds:Signature xmlns:ds="...">
        ...signature over body and key headers using #sct2...
      </ds:Signature>
    </wsse:Security>
  </S11:Header>
</S11:Envelope>
```



```
1112     ...
1113 </S11:Header>
1114 <S11:Body wsu:Id="req">
1115     <xx:Custom xmlns:xx="http://example.com/custom" xmlns:wsse="...">
1116         ...
1117         <wsse:SecurityTokenReference>
1118             <wsse:Reference URI="#sct2"/>
1119         </wsse:SecurityTokenReference>
1120     </xx:Custom>
1121 </S11:Body>
1122 </S11:Envelope>
```

9 Error Handling

There are many circumstances where an *error* can occur while processing security information. Errors use the SOAP Fault mechanism. Note that the reason text provided below is RECOMMENDED, but alternative text MAY be provided if more descriptive or preferred by the implementation. The tables below are defined in terms of SOAP 1.1. For SOAP 1.2, the Fault/Code/Value is env:Sender (as defined in SOAP 1.2) and the Fault/Code/Subcode/Value is the *faultcode* below and the Fault/Reason/Text is the *faultstring* below. It should be noted that profiles MAY provide second-level details fields, but they should be careful not to introduce security vulnerabilities when doing so (e.g. by providing too detailed information).

Error that occurred (faultstring)	Fault code (faultcode)
The requested context elements are insufficient or unsupported.	wsc:BadContextToken
Not all of the values associated with the SCT are supported.	wsc:UnsupportedContextToken
The specified source for the derivation is unknown.	wsc:UnknownDerivationSource
The provided context token has expired	wsc:RenewNeeded
The specified context token could not be renewed.	wsc:UnableToRenew

10 Security Considerations

As stated in the Goals section of this document, this specification is meant to provide extensible framework and flexible syntax, with which one could implement various security mechanisms. This framework and syntax by itself *does not provide any guarantee of security*. When implementing and using this framework and syntax, one must make every effort to ensure that the result is not vulnerable to any one of a wide range of attacks.

It is not feasible to provide a comprehensive list of security considerations for such an extensible set of mechanisms. A complete security analysis must be conducted on specific solutions based on this specification. Below we illustrate some of the security concerns that often come up with protocols of this type, but we stress that this *is not an exhaustive list of concerns*.

It is critical that all relevant elements of a message be included in signatures. As well, the signatures for security context establishment must include a timestamp, nonce, or sequence number depending on the degree of replay prevention required. Security context establishment should include full policies to prevent possible attacks (e.g. downgrading attacks).

Authenticating services are susceptible to denial of service attacks. Care should be taken to mitigate such attacks as is warranted by the service.

There are many other security concerns that one may need to consider in security protocols. The list above should not be used as a "check list" instead of a comprehensive security analysis.

In addition to the consideration identified here, readers should also review the security considerations in [[WS-Security](#)] and [[WS-Trust](#)].

A. Sample Usages

This non-normative appendix illustrates several sample usage patterns of [WS-Trust] and this document. Specifically, it illustrates different patterns that could be used to parallel, at an end-to-end message level, the selected TLS/SSL scenarios. This is not intended to be the definitive method for the scenarios, nor is it fully inclusive. Its purpose is simply to illustrate, in a context familiar to readers, how this specification might be used.

The following sections are based on a scenario where the client wishes to authenticate the server prior to sharing any of its own credentials.

It should be noted that the following sample usages are illustrative; any implementation of the examples illustrated below should be carefully reviewed for potential security attacks. For example, multi-leg exchanges such as those below should be careful to prevent man-in-the-middle attacks or downgrade attacks. It may be desirable to use running hashes as challenges that are signed or a similar mechanism to ensure continuity of the exchange.

The examples below assume that both parties understand the appropriate security policies in use and can correctly construct signatures and encryption that the other party can process.

A.1 Anonymous SCT

In this scenario the requestor wishes to remain anonymous while authenticating the recipient and establishing an SCT for secure communication.

This scenario assumes that the requestor has a key for the recipient. If this isn't the case, they can use [WS-MEX] or the mechanisms described in a later section or obtain one from another security token service.

There are two basic patterns that can apply, which only vary slightly. The first is as follows:

1. The requestor sends an RST to the recipient requesting an SCT. The request contains key material encrypted for the recipient. The request is not authenticated.
2. The recipient, if it accepts such requests, returns an RSTRC with one or more RSTRs with the SCT as the requested token and does not return any proof information indicating that the requestor's key is the proof.

A slight variation on this is as follows:

1. The requestor sends an RST to the recipient requesting an SCT. The request contains key material encrypted for the recipient. The request is not authenticated.
2. The recipient, if it accepts such requests, returns an RSTRC with one or more RSTR and with the SCT as the requested token and returns its own key material encrypted using the requestor's key.

Another slight variation is to return a new key encrypted using the requestor's provided key.

It should be noted that the variations that involve encrypting data using the requestor's key material might be subject to certain types of key attacks.

1203 Yet another approach is to establish a secure channel (e.g. TLS/SSL IP/Sec) between the
1204 requestor and the recipient. Key material can then safely flow in either direction. In some
1205 circumstances, this provides greater protection than the approach above when returning
1206 key information to the requestor.

1207 **A.2 Mutual Authentication SCT**

1208 In this scenario the requestor is willing to authenticate, but wants the recipient to
1209 authenticate first. The following steps outline the message flow:

- 1210 1. The requestor sends an RST requesting an SCT. The request contains key material
1211 encrypted for the recipient. The request is not authenticated.
- 1212 2. The recipient returns an RSTRC with one or more RSTRs including a challenge for the
1213 requestor. The RSTRC is secured by the recipient so that the requestor can
1214 authenticate it.
- 1215 3. The requestor, after authenticating the recipient's RSTRC, sends an RSTRC
1216 responding to the challenge.
- 1217 4. The recipient, after authenticating the requestor's RSTRC, sends a secured RSTRC
1218 containing the token and either proof information or partial key material (depending
1219 on whether or not the requestor provided key material).

1220

1221 Another variation exists where step 1 includes a specific challenge for the service.
1222 Depending on the type of challenge used this may not be necessary because the message
1223 may contain enough entropy to ensure a fresh response from the recipient.

1224

1225 In other variations the requestor doesn't include key information until step 3 so that it can
1226 first verify the signature of the recipient in step 2.

B. Token Discovery Using RST/RSTR

If the recipient's security token is not known, the RST/RSTR mechanism can still be used. The following example illustrates one possible sequence of messages:

1. The requestor sends an RST requesting an SCT. This request does not contain any key material, nor is the request authenticated.
2. The recipient sends an RSTRC with one or more RSTRs to the requestor with an embedded challenge. The RSTRC is secured by the recipient so that the requestor can authenticate it.
3. The requestor sends an RSTRC to the recipient and includes key information protected for the recipient. This request may or may not be secured depending on whether or not the request is anonymous.
4. The final issuance step depends on the exact scenario. Any of the final legs from above might be used.

Note that step 1 might include a challenge for the recipient. Please refer to the comment in the previous section on this scenario.

Also note that in response to step 1 the recipient might issue a fault secured with [[WS-Security](#)] providing the requestor with information about the recipient's security token.

C. Acknowledgements

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

Original Authors of the initial contribution:

Steve Anderson, OpenNetwork
Jeff Bohren, OpenNetwork
Toufic Boubez, Layer 7
Marc Chanliau, Computer Associates
Giovanni Della-Libera, Microsoft
Brendan Dixon, Microsoft
Praerit Garg, Microsoft
Martin Gudgin (Editor), Microsoft
Satoshi Hada, IBM
Phillip Hallam-Baker, VeriSign
Maryann Hondo, IBM
Chris Kaler, Microsoft
Hal Lockhart, BEA
Robin Martherus, Oblix
Hiroshi Maruyama, IBM
Anthony Nadalin (Editor), IBM
Nataraj Nagaratnam, IBM
Andrew Nash, Reactivity
Rob Philpott, RSA Security
Darren Platt, Ping Identity
Hemma Prafullchandra, VeriSign
Maneesh Sahu, Actional
John Shewchuk, Microsoft
Dan Simon, Microsoft
Davanum Srinivas, Computer Associates
Elliot Waingold, Microsoft
David Waite, Ping Identity
Doug Walter, Microsoft
Riaz Zolfonoon, RSA Security

Original Acknowledgements of the initial contribution:

Paula Austel, IBM
Keith Ballinger, Microsoft
John Brezak, Microsoft
Tony Cowan, IBM
HongMei Ge, Microsoft
Slava Kavsan, RSA Security
Scott Konersmann, Microsoft
Leo Laferriere, Computer Associates
Paul Leach, Microsoft
Richard Levinson, Computer Associates
John Linn, RSA Security
Michael McIntosh, IBM
Steve Millet, Microsoft

1293 Birgit Pfitzmann, IBM
1294 Fumiko Satoh, IBM
1295 Keith Stobie, Microsoft
1296 T.R. Vishwanath, Microsoft
1297 Richard Ward, Microsoft
1298 Hervey Wilson, Microsoft
1299 **TC Members during the development of this specification:**
1300 Don Adams, Tibco Software Inc.
1301 Jan Alexander, Microsoft Corporation
1302 Steve Anderson, BMC Software
1303 Donal Arundel, IONA Technologies
1304 Howard Bae, Oracle Corporation
1305 Abbie Barbir, Nortel Networks Limited
1306 Charlton Barreto, Adobe Systems
1307 Mighael Botha, Software AG, Inc.
1308 Toufic Boubez, Layer 7 Technologies Inc.
1309 Norman Brickman, Mitre Corporation
1310 Melissa Brumfield, Booz Allen Hamilton
1311 Lloyd Burch, Novell
1312 Scott Cantor, Internet2
1313 Greg Carpenter, Microsoft Corporation
1314 Steve Carter, Novell
1315 Ching-Yun (C.Y.) Chao, IBM
1316 Martin Chapman, Oracle Corporation
1317 Kate Cherry, Lockheed Martin
1318 Henry (Hyenvui) Chung, IBM
1319 Luc Clement, Systinet Corp.
1320 Paul Cotton, Microsoft Corporation
1321 Glen Daniels, Sonic Software Corp.
1322 Peter Davis, Neustar, Inc.
1323 Martijn de Boer, SAP AG
1324 Werner Dittmann, Siemens AG
1325 Abdeslem DJAOUI, CCLRC-Rutherford Appleton Laboratory
1326 Fred Dushin, IONA Technologies
1327 Petr Dvorak, Systinet Corp.
1328 Colleen Evans, Microsoft Corporation
1329 Ruchith Fernando, WSO2
1330 Mark Fussell, Microsoft Corporation
1331 Vijay Gajjala, Microsoft Corporation
1332 Marc Goodner, Microsoft Corporation
1333 Hans Granqvist, VeriSign
1334 Martin Gudgin, Microsoft Corporation
1335 Tony Gullotta, SOA Software Inc.
1336 Jiandong Guo, Sun Microsystems

1337 Phillip Hallam-Baker, VeriSign
1338 Patrick Harding, Ping Identity Corporation
1339 Heather Hinton, IBM
1340 Frederick Hirsch, Nokia Corporation
1341 Jeff Hodges, Neustar, Inc.
1342 Will Hopkins, BEA Systems, Inc.
1343 Alex Hristov, Otecia Incorporated
1344 John Hughes, PA Consulting
1345 Diane Jordan, IBM
1346 Venugopal K, Sun Microsystems
1347 Chris Kaler, Microsoft Corporation
1348 Dana Kaufman, Forum Systems, Inc.
1349 Paul Knight, Nortel Networks Limited
1350 Ramanathan Krishnamurthy, IONA Technologies
1351 Christopher Kurt, Microsoft Corporation
1352 Kelvin Lawrence, IBM
1353 Hubert Le Van Gong, Sun Microsystems
1354 Jong Lee, BEA Systems, Inc.
1355 Rich Levinson, Oracle Corporation
1356 Tommy Lindberg, Dajeil Ltd.
1357 Mark Little, JBoss Inc.
1358 Hal Lockhart, BEA Systems, Inc.
1359 Mike Lyons, Layer 7 Technologies Inc.
1360 Eve Maler, Sun Microsystems
1361 Ashok Malhotra, Oracle Corporation
1362 Anand Mani, CrimsonLogic Pte Ltd
1363 Jonathan Marsh, Microsoft Corporation
1364 Robin Martherus, Oracle Corporation
1365 Miko Matsumura, Infravio, Inc.
1366 Gary McAfee, IBM
1367 Michael McIntosh, IBM
1368 John Merrells, Sxip Networks SRL
1369 Jeff Mischkinsky, Oracle Corporation
1370 Prateek Mishra, Oracle Corporation
1371 Bob Morgan, Internet2
1372 Vamsi Motukuru, Oracle Corporation
1373 Raajmohan Na, EDS
1374 Anthony Nadalin, IBM
1375 Andrew Nash, Reactivity, Inc.
1376 Eric Newcomer, IONA Technologies
1377 Duane Nickull, Adobe Systems
1378 Toshihiro Nishimura, Fujitsu Limited

1379 Rob Philpott, RSA Security
1380 Denis Pilipchuk, BEA Systems, Inc.
1381 Darren Platt, Ping Identity Corporation
1382 Martin Raepple, SAP AG
1383 Nick Ragouzis, Enosis Group LLC
1384 Prakash Reddy, CA
1385 Alain Regnier, Ricoh Company, Ltd.
1386 Irving Reid, Hewlett-Packard
1387 Bruce Rich, IBM
1388 Tom Rutt, Fujitsu Limited
1389 Maneesh Sahu, Actional Corporation
1390 Frank Siebenlist, Argonne National Laboratory
1391 Joe Smith, Apani Networks
1392 Davanum Srinivas, WSO2
1393 Yakov Sverdlov, CA
1394 Gene Thurston, AmberPoint
1395 Victor Valle, IBM
1396 Asir Vedamuthu, Microsoft Corporation
1397 Greg Whitehead, Hewlett-Packard
1398 Ron Williams, IBM
1399 Corinna Witt, BEA Systems, Inc.
1400 Kyle Young, Microsoft Corporation
1401
1402