



# SCA JMS Binding v1.1 TestCases Version 1.0

**Committee Specification Draft 01 /  
Public Review Draft 01 plus issue 147 proposed  
resolution**

**188 November 2010**

## **Specification URIs:**

### **This Version:**

<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0-csprd01.html>  
<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0-csprd01.odt>  
<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0-csprd01.pdf>  
(Authoritative)

### **Previous Version:**

N/A

### **Latest Version:**

<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0.html>  
<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0.odt>  
<http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0.pdf>  
(Authoritative)

## **Technical Committee:**

OASIS Service Component Architecture / Bindings (SCA-Bindings) TC

## **Chair(s):**

Simon Holdsworth, IBM <[simon\\_holdsworth@uk.ibm.com](mailto:simon_holdsworth@uk.ibm.com)>

## **Editor(s):**

Anthony Elder, IBM <[ant.elder@uk.ibm.com](mailto:ant.elder@uk.ibm.com)>  
Simon Holdsworth, IBM <[simon\\_holdsworth@uk.ibm.com](mailto:simon_holdsworth@uk.ibm.com)>  
Anish Karmarkar, Oracle <[Anish.Karmarkar@oracle.com](mailto:Anish.Karmarkar@oracle.com)>

## **Related Work:**

This specification is related to:

- [Service Component Architecture JMS Binding Specification Version 1.1](#)

**Declared XML Namespace(s):**

<http://docs.oasis-open.org/ns/opencsa/scatests/200903>  
<http://test.sca.oasisopen.org/>

**Abstract:**

This document defines the TestCases for the SCA JMS Binding specification.

The TestCases represent a series of tests that an SCA runtime must pass in order to claim conformance to the requirements of the SCA JMS Binding specification.

**Status:**

This document was last revised or approved by the OASIS Service Component Architecture / Binding (SCA-Bindings) TC on the above date. The level of approval is also listed above. Check the "Latest Version" or "Latest Approved Version" location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/sca-bindings/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/sca-bindings/ipr.php>).

**Citation Format:**

When referencing this specification the following citation format should be used:

**SCA-JMSBINDING-TESTCASES-1.0** OASIS Committee Specification Draft 01, SCA JMS Binding v1.1 TestCases Version 1.0, November 2010, <http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-testcases-1.0-csd01.pdf>

---

# Notices

Copyright © OASIS® 2010. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The names "OASIS", "SCA" and "Service Component Architecture" are trademarks of OASIS, the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <http://www.oasis-open.org/who/trademark.php> for above guidance.

# Table of Contents

1 Introduction.....	5
1.1 TestCase Structure.....	5
1.2 Namespaces and Java Package Names.....	6
1.3 Terminology.....	7
1.4 Normative References.....	7
1.5 Non-normative References.....	7
2 TestCases.....	8
2.1 Section 3.....	8
3 Cross Mapping of Test Assertions to TestCases.....	37
4 Catalog of Test Artifacts.....	40
4.1 Composite Files - lower level.....	40
4.2 Java Interfaces.....	40
4.3 Java Implementation Classes.....	41
4.4 WSDL Interface Files.....	41
5 Conformance.....	43
Appendix A.Test Assertions for the JMS Binding.....	44
A.1.Example Test Assertion.....	44
A.2.Test Assertions for JMS Bindings Specification Section 3.....	44
A.3.Test Assertions for JMS Bindings Specification Section 4.....	55
A.4.Test Assertions for JMS Bindings Specification Section 5.....	59
A.5.Test Assertions for JMS Bindings Specification Section 6.....	59
A.6.Cross Mapping of Conformance Statements to Test Assertions.....	66
Appendix B.Acknowledgments.....	68
Appendix C.Revision History.....	69

---

# 1 Introduction

This document defines the TestCases for the SCA JMS Binding specification [\[SCA-JMS\]](#).

The tests described in this document are ~~related~~[derived from the normative statements in SCA JMS Binding specification via -to the](#) Test Assertions [which are described in the SCA JMS Binding Test assertions document \[JMS-TA\] Appendix A, "JMS Binding Test Assertions"](#).

## 1.1 TestCase Structure

The SCA JMS Binding test cases follow a standard structure. They are divided into two main parts:

1. JMS Test Client, which drives the test and checks that the results are as expected
2. SCA Test Application which consists of SCA Composites, WSDL files, XSDs and code artifacts such as Java classes, organized into a series of SCA contributions

The basic idea is that the SCA Test Application runs on the SCA runtime that is under test, while the JMS Test Client runs as a standalone application, invoking and being invoked by the Test Application through one or more service interfaces.

### JMS Test Client

The JMS Test Client is designed as a standalone Java application. The version built here is a Java application which uses the JUnit test framework.

The JMS Test Client is structured to contain configuration information about the testcase, which consists of:

1. metadata identifying the SCA Test Application in terms of the SCA Contributions that are used and the Composites that must be deployed and run
2. data indicating which service operation(s) must be invoked with input data and expected output data (including exceptions for expected failure cases)

The JMS Test Client consists of a base runtime class, BaseJMSTestCase.java. Each actual testcase is implemented by a small class which extends the base runtime class. The bulk of the code required to run a test is held in the base runtime class. The small testcase class contains the configuration for the specific test, which it provides to the code in the base runtime class through a standard interface.

The JMS Test Client base runtime class is structured so that there is a replaceable class called the RuntimeBridge, which is used to communicate with the SCA runtime under test, for the purposes of deploying and running the test application. Each SCA runtime provider can produce a version of this class. The code within the runtime bridge is likely to be highly proprietary and specific to the SCA runtime for which it is written. Which runtime bridge class is used at runtime is controlled by an environment variable or system variable with the name "OASIS\_TESTENV\_RUNTIME\_BRIDGE\_CLASS", which is read by the code in BaseJMSTestCase.

The JMS Test Client uses JMS to communicate with the SCA Test Application. Tests involve SCA services and references with JMS bindings, and possibly with bidirectional interfaces. Each SCA Test Application consists of one top level SCA Composite file and its associated artifacts (implementations, interface files), plus the JMS Test Client described above.

A typical test application has a design where the top level composite offers a single service to the JMS Test Client application over a JMS binding. The top level composite contains one component which offers the service that is used by the client application, and may have a single reference which invokes the JMS Test Client.

## Test Artifacts Organization

Note that the design of these testcases promotes reuse of artifacts between testcases, so that many testcases share components. For example, components implementing simple invocable services are all implemented using a single parameterized implementation artifact.

All the test artifacts are contained in a number of Contributions, which are simply filesystem directories which are all peers in the filesystem hierarchy. The names of the directories are the names of the Contributions and the names are significant. The names of Contributions containing implementation type specific artifacts (such as Java classes) are also specially structured to allow for replacement of one type of implementation artifact with another.

Broadly, Contribution names are as follows:

- BJM\_nnnnn - a contribution that is specific for a particular testcase, where "nnnnn" is the number of the testcase. Often this is required because a particular testcase involves artifacts that contain errors that are statically checkable - an SCA runtime is permitted to reject such artifacts when they are contributed and deployed and it is important to ensure that contributions containing deliberate errors for one testcase do not interfere with the operation of other testcases.
- BJM\_nnnnn\_Java - a contribution for a specific testcase where there is a need for language specific artifacts that relate to that testcase alone
- General - a shared contribution containing implementation type independent artifacts that can be used by many testcases.
- General\_Java - a shared contribution containing implementation type dependent artifacts for Java POJOs. These artifacts can include both Java classes and also SCA composites that directly use Java classes..
- Contribution1, Contribution2, etc - contributions that are used by various testcases that are testing the handling of SCA contributions

## 1.2 Namespaces and Java Package Names

The SCA JMS Binding testcase suite makes use of some XML namespaces and Java package names, as follows:

### SCA Artifact Namespaces

These apply to artifacts such as Composites

<http://docs.oasis-open.org/ns/opencsa/scatests/200903>

### WSDL Namespace

<http://test.sca.oasisopen.org/>

### Java Package name

For Java interface classes and for Java implementation classes

`org.oasisopen.sca.test`

## 1.3 Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this specification are to be interpreted as described in IETF RFC 2119 [RFC 2119].

## 1.4 Normative References

- |            |  |
|------------|--|
| [RFC 2119] | S. Bradner. <i>Key words for use in RFCs to Indicate Requirement Levels</i> . IETF RFC 2119, March 1997.<br><a href="http://www.ietf.org/rfc/rfc2119.txt">http://www.ietf.org/rfc/rfc2119.txt</a>  |
| [SCA-JMS]  | <u>OASIS Committee Specification Draft 05, SCA JMS Binding Specification Version 1.1, November 2010 <a href="http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-spec-csd05.pdf">http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-spec-csd05.pdf</a></u>                            |
| [TA-GUIDE] | <u>OASIS Committee Draft 05, Test Assertions Guidelines Version 1.0, August 2010 <a href="http://docs.oasis-open.org/tag/guidelines/v1.0/cd05/testassertionsguidelines-cd-05.pdf">http://docs.oasis-open.org/tag/guidelines/v1.0/cd05/testassertionsguidelines-cd-05.pdf</a></u>                                     |
| [IETFJMS]  | <u>M. Phillips, P. Adams, D. Rokicki, E. Johnson, <i>URI Scheme for Java™ Message Service 1.0</i> <a href="http://tools.ietf.org/id/draft-merrick-jms-uri-12.txt">http://tools.ietf.org/id/draft-merrick-jms-uri-12.txt</a>, IETF Internet-Draft January 20, 2011, pending publication of final approved version</u> |
| [JCA15]    | <u>J2EE Connector Architecture Specification Version 1.5 <a href="http://java.sun.com/j2ee/connector/">http://java.sun.com/j2ee/connector/</a></u>   |
| [JMS-TA]   | <u>OASIS Committee Specification Draft 01, SCA JMS Binding Test Assertions, November 2010 <a href="http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-test-assertions-1.0-csd01.pdf">http://docs.oasis-open.org/opencsa/sca-bindings/sca-jmsbinding-1.1-test-assertions-1.0-csd01.pdf</a></u>        |

## 1.5 Non-normative References

N/A

## 2 TestCases

### 2.1 Section 3

#### BJM\_30001\_TestCase

Testcase ID	BJM_30001_TestCase
Test Assertion	BJM-TA-30001
Description	Tests that the @uri attribute of a <binding.jms> element matches the syntax defined by the IETF URI Scheme for Java™ Message Service 1.0 <a href="#">[IETFJMS]</a>
Artifacts	BJM_30001_TestCase.java Test_BJM_30001.composite TestInvocation.wsdl Service1.wsdl
Expected output	Negative test: “exception”

#### BJM\_30002\_1\_TestCase

Testcase ID	BJM_30002_1_TestCase
Test Assertion	BJM-TA-30002
Description	Tests that when the @uri attribute is specified, the SCA runtime MUST raise an error if the referenced resources do not already exist  This is the test for the destination does not exist
Artifacts	BJM_30002_1_TestCase.java Test_BJM_30002_1.composite TestInvocation.wsdl Service1.wsdl
Expected output	Negative test: “exception”

#### BJM\_30002\_2\_TestCase

Testcase ID	BJM_30002_2_TestCase
Test Assertion	BJM-TA-30002
Description	Tests that when the @uri attribute is specified, the SCA runtime MUST raise an error if the referenced resources do not already exist  This is the test for the connection factory does not exist
Artifacts	BJM_30002_2_TestCase.java Test_BJM_30002_2.composite



	TestInvocation.wsdl Service1.wsdl
Expected output	Negative test: "exception"

### BJM\_30003\_TestCase

Testcase ID	BJM_30003_TestCase
Test Assertion	BJM-TA-30003
Description	Tests that when the @correlationScheme attribute is "sca:messageID" the SCA runtime MUST set the correlation ID of replies to the message ID of the corresponding request
Artifacts	BJM_3003_TestCase.java Test_BJM_3003.composite Service1.wsdl
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_3003 request message</return>"

### BJM\_30004\_TestCase

Testcase ID	BJM_30004_TestCase
Test Assertion	BJM-TA-30004
Description	Tests that the correlation ID of a reply message is set to the value of the correlation ID of the corresponding request message when a request/reply operation is invoked.
Artifacts	BJM_3004_TestCase.java Test_BJM_3004.composite Service1.wsdl
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_3004 request message</return>"

### BJM\_30005\_TestCase

Testcase ID	BJM_30005_TestCase
Test Assertion	BJM-TA-30005
Description	Tests that if the value of the @correlationScheme attribute is "sca:none" the SCA runtime MUST NOT set the correlation ID
Artifacts	BJM_3005_TestCase.java Test_BJM_3005.composite Service1.wsdl
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked

	with BJM_3005 request message</return>”
--	---

## BJM\_30007\_TestCase

Testcase ID	BJM_30007_TestCase
Test Assertion	BJM-TA-30007
Description	Tests that the correlation ID of request messages are set to a non-null value when using the sca:correlationID correlation scheme on a reference.
Artifacts	BJM_3007_TestCase.java Test_BJM_3007.composite
Expected output	Positive test:  “<?xml version=“1.0” encoding=“UTF-8”?><return>service1 operation1 invoked with BJM_3007 request message</return>”

## BJM\_30011A\_TestCase

Testcase ID	BJM_30011A_TestCase
Test Assertion	BJM-TA-30011
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "always" and the @jndiName attribute is present and the resource cannot be created at the location specified by the @jndiName attribute then the SCA runtime MUST raise an error  This test is for the activationSpec
Artifacts	BJM_3011A_TestCase.java Test_BJM_3011A.composite Service1.wsdl
Expected output	Negative test:  “exception”

## BJM\_30011C\_TestCase

Testcase ID	BJM_30011C_TestCase
Test Assertion	BJM-TA-30011
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "always" and the @jndiName attribute is present and the resource cannot be created at the location specified by the @jndiName attribute then the SCA runtime MUST raise an error  This test is for the connectionFactory
Artifacts	BJM_3011C_TestCase.java Test_BJM_3011C.composite Service1.wsdl
Expected output	Negative test:  “exception”

## BJM\_30011D\_TestCase

Testcase ID	BJM_30011D_TestCase
Test Assertion	BJM-TA-30011
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "always" and the @jndiName attribute is present and the resource cannot be created at the location specified by the @jndiName attribute then the SCA runtime MUST raise an error  This test is for the destination
Artifacts	BJM_3011D_TestCase.java  Test_BJM_3011D.composite  Service1.wsdl
Expected output	Negative test:  "exception"

## BJM\_30012A\_TestCase

Testcase ID	BJM_30012A_TestCase
Test Assertion	BJM-TA-30012
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" then the @jndiName attribute MUST specify the location of the possibly existing resource  This test is for the activationSpec
Artifacts	BJM_3012A_TestCase.java  Test_BJM_3012A.composite  Service1.wsdl
Expected output	Negative test:  "exception"

## BJM\_30012C\_TestCase

Testcase ID	BJM_30012C_TestCase
Test Assertion	BJM-TA-30012
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" then the @jndiName attribute MUST specify the location of the possibly existing resource  This test is for the connectionFactory
Artifacts	BJM_3012C_TestCase.java  Test_BJM_3012C.composite  Service1.wsdl
Expected output	Negative test:  "exception"

## BJM\_30012D\_TestCase

Testcase ID	BJM_30012D_TestCase
Test Assertion	BJM-TA-30012
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" then the @jndiName attribute MUST specify the location of the possibly existing resource  This test is for the destination
Artifacts	BJM_3012D_TestCase.java  Test_BJM_3012D.composite  Service1.wsdl
Expected output	Negative test:  "exception"

## BJM\_30014A\_TestCase

Testcase ID	BJM_30014A_TestCase
Test Assertion	BJM-TA-30014
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" and the @jndiName attribute refers to an existing resource that is not a JMS Destination of the appropriate type, a JMS connection factory or a JMS activation spec respectively then the SCA runtime MUST raise an error  This test is for the activationSpec
Artifacts	BJM_3014A_TestCase.java  Test_BJM_3014A.composite  Service1.wsdl
Expected output	Negative test:  "exception"

## BJM\_30014C\_TestCase

Testcase ID	BJM_30014C_TestCase
Test Assertion	BJM-TA-30014
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" and the @jndiName attribute refers to an existing resource that is not a JMS Destination of the appropriate type, a JMS connection factory or a JMS activation spec respectively then the SCA runtime MUST raise an error  This test is for the connectionFactory
Artifacts	BJM_3014C_TestCase.java  Test_BJM_3014C.composite  Service1.wsdl
Expected output	Negative test:

	"exception"
--	-------------

### BJM\_30014D\_TestCase

Testcase ID	BJM_30014D_TestCase
Test Assertion	BJM-TA-30014
Description	<p>Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" and the @jndiName attribute refers to an existing resource that is not a JMS Destination of the appropriate type, a JMS connection factory or a JMS activation spec respectively then the SCA runtime MUST raise an error</p> <p>This test is for the destination</p>
Artifacts	<p>BJM_3014D_TestCase.java</p> <p>Test_BJM_3014D.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

### BJM\_30015Aa\_TestCase

Testcase ID	BJM_30015Aa_TestCase
Test Assertion	BJM-TA-30015
Description	<p>Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error</p> <p>This test is for activationspec and no @jndiName</p>
Artifacts	<p>BJM_3015Aa_TestCase.java</p> <p>Test_BJM_30145Aa.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

### BJM\_30015Ab\_TestCase

Testcase ID	BJM_30015Ab_TestCase
Test Assertion	BJM-TA-30015
Description	<p>Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error</p> <p>This test is for activationspec and resource not present</p>
Artifacts	BJM_3015Ab_TestCase.java

	Test_BJM_30145Ab.composite Service1.wsdl
Expected output	Negative test: "exception"

### BJM\_30015Ac\_TestCase

Testcase ID	BJM_30015Ac_TestCase
Test Assertion	BJM-TA-30015
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error  This test is for activationspec and resource wrong type
Artifacts	BJM_3015Ac_TestCase.java Test_BJM_30145Ac.composite Service1.wsdl
Expected output	Negative test: "exception"

### BJM\_30015Ca\_TestCase

Testcase ID	BJM_30015Ca_TestCase
Test Assertion	BJM-TA-30015
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error  This test is for connectionFactory and no @jndiName
Artifacts	BJM_3015Ca_TestCase.java Test_BJM_30145Ca.composite Service1.wsdl
Expected output	Negative test: "exception"

### BJM\_30015Cb\_TestCase

Testcase ID	BJM_30015Cb_TestCase
Test Assertion	BJM-TA-30015
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST

	raise an error This test is for connectionFactory and resource not present
Artifacts	BJM_3015Cb_TestCase.java Test_BJM_30145Cb.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30015Cc\_TestCase

Testcase ID	BJM_30015Cc_TestCase
Test Assertion	BJM-TA-30015
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error  This test is for connectionFactory and resource wrong type
Artifacts	BJM_3015Cc_TestCase.java Test_BJM_30145Cc.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30015Da\_TestCase

Testcase ID	BJM_30015Da_TestCase
Test Assertion	BJM-TA-30015
Description	Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error  This test is for destination and no @jndiName
Artifacts	BJM_3015Da_TestCase.java Test_BJM_30145Da.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30015Db\_TestCase

Testcase ID	BJM_30015Db_TestCase
-------------	----------------------

Test Assertion	BJM-TA-30015
Description	<p>Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error</p> <p>This test is for destination and resource not present</p>
Artifacts	<p>BJM_3015Db_TestCase.java</p> <p>Test_BJM_30145Db.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

### BJM\_30015Dc\_TestCase

Testcase ID	BJM_30015Dc_TestCase
Test Assertion	BJM-TA-30015
Description	<p>Tests when the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error</p> <p>This test is for destination and resource wrong type</p>
Artifacts	<p>BJM_3015Dc_TestCase.java</p> <p>Test_BJM_3015Dc.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

### BJM\_30017\_TestCase

Testcase ID	BJM_30017_TestCase
Test Assertion	BJM-TA-30017
Description	Tests that a binding.jms element MUST NOT include both a connectionFactory element and an activationSpec element
Artifacts	<p>BJM_3017_TestCase.java</p> <p>Test_BJM_3017.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

### BJM\_30018\_TestCase

Testcase ID	BJM_30018_TestCase
-------------	--------------------



Test Assertion	BJM-TA-30018
Description	Tests when the connectionFactory element is present, then the destination MUST be defined either by the destination element or the @uri attribute
Artifacts	BJM_3018_TestCase.java Test_BJM_3018.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30020\_TestCase

Testcase ID	BJM_30020_TestCase
Test Assertion	BJM-TA-30020
Description	Tests that the activationSpec element MUST NOT be present when the binding is being used for an SCA reference
Artifacts	BJM_3020_TestCase.java Test_BJM_3020.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30021\_TestCase

Testcase ID	BJM_30021_TestCase
Test Assertion	BJM-TA-30021
Description	Tests that a response element MUST NOT include both a connectionFactory element and an activationSpec element
Artifacts	BJM_3021_TestCase.java Test_BJM_3021.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30023\_TestCase

Testcase ID	BJM_30023_TestCase
Test Assertion	BJM-TA-30023
Description	Tests that the response/activationSpec element MUST NOT be present when the binding is being used for an SCA service
Artifacts	BJM_3023_TestCase.java Test_BJM_3023.composite Service1.wsdl

Expected output	Negative test: "exception"
-----------------	-------------------------------

## BJM\_30024\_1\_TestCase

Testcase ID	BJM_30024_1_TestCase
Test Assertion	BJM-TA-30024
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each of the JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers to values specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the value for the header specified in the @uri attribute (highest priority);</li> <li>2) the value for the header specified in the operationProperties/headers element matching the operation being invoked;</li> <li>3) the value for the header specified in the headers element;</li> <li>4) the default value for the header as specified by the definition of the binding.jms/headers element (lowest priority)</li> </ol> <p>This is the URI case</p>
Artifacts	BJM_3024_1_TestCase.java Test_BJM_3024_1.composite Service1.wsdl
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;arg0&gt;service1 operation1 invoked with BJM_3024 request message&lt;/arg0&gt;</pre>

## BJM\_30024\_2\_TestCase

Testcase ID	BJM_30024_2_TestCase
Test Assertion	BJM-TA-30024
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each of the JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers to values specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the value for the header specified in the @uri attribute (highest priority);</li> <li>2) the value for the header specified in the operationProperties/headers element matching the operation being invoked;</li> <li>3) the value for the header specified in the headers element;</li> <li>4) the default value for the header as specified by the definition of the binding.jms/headers element (lowest priority)</li> </ol> <p>This is the operationProperties case</p>
Artifacts	BJM_3024_2_TestCase.java Test_BJM_3024_2.composite Service1.wsdl
Expected output	Positive test:

	"<?xml version="1.0" encoding="UTF-8"?><arg0>service1 operation1 invoked with BJM_3024 request message</arg0>"
--	--

### BJM\_30024\_3\_TestCase

Testcase ID	BJM_30024_3_TestCase
Test Assertion	BJM-TA-30024
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each of the JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers to values specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the value for the header specified in the @uri attribute (highest priority);</li> <li>2) the value for the header specified in the operationProperties/headers element matching the operation being invoked;</li> <li>3) the value for the header specified in the headers element;</li> <li>4) the default value for the header as specified by the definition of the binding.jms/headers element (lowest priority)</li> </ol> <p>This is the header case</p>
Artifacts	BJM_3024_3_TestCase.java Test_BJM_3024_3.composite Service1.wsdl
Expected output	Positive test: "<?xml version="1.0" encoding="UTF-8"?><arg0>service1 operation1 invoked with BJM_3024 request message</arg0>"

### BJM\_30024\_4\_TestCase

Testcase ID	BJM_30024_4_TestCase
Test Assertion	BJM-TA-30024
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each of the JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers to values specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the value for the header specified in the @uri attribute (highest priority);</li> <li>2) the value for the header specified in the operationProperties/headers element matching the operation being invoked;</li> <li>3) the value for the header specified in the headers element;</li> <li>4) the default value for the header as specified by the definition of the binding.jms/headers element (lowest priority)</li> </ol> <p>This is the default case</p>
Artifacts	BJM_3024_4_TestCase.java Test_BJM_3024_4.composite Service1.wsdl
Expected output	Positive test:

	"<?xml version="1.0" encoding="UTF-8"?><arg0>service1 operation1 invoked with BJM_3024 request message</arg0>"
--	--

## BJM\_30025\_1\_TestCase

Testcase ID	BJM_30025_1_TestCase
Test Assertion	BJM-TA-30025
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each named user property with type and value specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the type and value for the named user property specified in an operationProperties/headers/property element matching the name of the operation being invoked (highest priority);</li> <li>2) the type and value for the named user property specified in a headers/property element (lowest priority)</li> </ol> <p>This is the operationProperties case</p>
Artifacts	BJM_3025_1_TestCase.java Test_BJM_3025_1.composite Service1.wsdl
Expected output	Positive test: "<?xml version="1.0" encoding="UTF-8"?><arg0>service1 operation1 invoked with BJM_3025 request message</arg0>"

## BJM\_30025\_2\_TestCase

Testcase ID	BJM_30025_2_TestCase
Test Assertion	BJM-TA-30025
Description	<p>Tests when sending messages for a JMS binding, the SCA runtime MUST set each named user property with type and value specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the type and value for the named user property specified in an operationProperties/headers/property element matching the name of the operation being invoked (highest priority);</li> <li>2) the type and value for the named user property specified in a headers/property element (lowest priority)</li> </ol> <p>This is the headers case</p>
Artifacts	BJM_3025_2_TestCase.java Test_BJM_3025_2.composite Service1.wsdl
Expected output	Positive test: "<?xml version="1.0" encoding="UTF-8"?><arg0>service1 operation1 invoked with BJM_3025 request message</arg0>"

## BJM\_30026\_1\_TestCase

Testcase ID	BJM_30026_1_TestCase
Test Assertion	BJM-TA-30026
Description	<p>Tests when receiving messages for a JMS binding, the SCA runtime MUST use a message selector if specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"><li>1) the value for the message selector specified in the @uri attribute value's "selector" parameter (highest priority);</li><li>2) the value for the message selector specified in the messageSelection/@selector attribute;</li><li>3) otherwise no message selector is used (lowest priority)</li></ol> <p>This is the @uri case</p>
Artifacts	<p>BJM_3026_1_TestCase.java</p> <p>Test_BJM_3026_1.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Positive test:</p> <p>"&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service1 operation1 invoked with BJM_3026 type1 message&lt;/return&gt;"</p>

## BJM\_30026\_2\_TestCase

Testcase ID	BJM_30026_2_TestCase
Test Assertion	BJM-TA-30026
Description	<p>Tests when receiving messages for a JMS binding, the SCA runtime MUST use a message selector if specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"><li>1) the value for the message selector specified in the @uri attribute value's "selector" parameter (highest priority);</li><li>2) the value for the message selector specified in the messageSelection/@selector attribute;</li><li>3) otherwise no message selector is used (lowest priority)</li></ol> <p>This is the messageSelection case</p>
Artifacts	<p>BJM_3026_2_TestCase.java</p> <p>Test_BJM_3026_2.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Positive test:</p> <p>"&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service1 operation1 invoked with BJM_3026 type1 message&lt;/return&gt;"</p>

## BJM\_30026\_3\_TestCase

Testcase ID	BJM_30026_3_TestCase
Test Assertion	BJM-TA-30026

Description	<p>Tests when receiving messages for a JMS binding, the SCA runtime MUST use a message selector if specified in the binding definition in the following priority order:</p> <ol style="list-style-type: none"> <li>1) the value for the message selector specified in the @uri attribute value's "selector" parameter (highest priority);</li> <li>2) the value for the message selector specified in the messageSelection/@selector attribute;</li> <li>3) otherwise no message selector is used (lowest priority)</li> </ol> <p>This is the default case</p>
Artifacts	<p>BJM_3026_3_TestCase.java</p> <p>Test_BJM_3026_3.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Positive test:</p> <p>"&lt;?xml version='1.0' encoding='UTF-8'?'&gt;&lt;return&gt;service1 operation1 invoked with BJM_3026 request message&lt;/return&gt;"</p>

## BJM\_30029\_TestCase

Testcase ID	BJM_30029_TestCase
Test Assertion	BJM-TA-30029
Description	Tests that the value of the operationProperties/@selectedOperation attribute MUST be unique across the containing binding.jms element
Artifacts	<p>BJM_3029_TestCase.java</p> <p>Test_BJM_3029.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Negative test:</p> <p>"exception"</p>

## BJM\_30031\_TestCase

Testcase ID	BJM_30031_TestCase
Test Assertion	BJM-TA-30031
Description	Tests that the resourceAdapter element MUST be present when JMS resources are to be created for a JMS provider that implements the JCA 1.5 Specification <b>JCA15</b> <b>JCA15</b> specification, and is ignored otherwise
Artifacts	<p>BJM_3031_TestCase.java</p> <p>Test_BJM_3031.composite</p> <p>Service1.wsdl</p>
Expected output	<p>Positive test:</p> <p>"&lt;?xml version='1.0' encoding='UTF-8'?'&gt;&lt;return&gt;service1 operation1 invoked with BJM_3031 request message&lt;/return&gt;"</p>

## BJM\_30034\_TestCase

Testcase ID	BJM_30034_TestCase
Test Assertion	BJM-TA-30034
Description	Tests when the @uri attribute is specified, the destination element MUST NOT be present
Artifacts	BJM_3034_TestCase.java Test_BJM_3034.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_30036\_TestCase

Testcase ID	BJM_30036_TestCase
Test Assertion	BJM-TA-30036
Description	Tests that the binding.jms element MUST conform to the XML schema defined in sca-bindingjms-1.1.xsd
Artifacts	BJM_3036_TestCase.java Test_BJM_3036.composite Service1.wsdl
Expected output	Negative test: "exception"

## BJM\_40001\_TestCase

Testcase ID	BJM_40001D_TestCase
Test Assertion	BJM-TA-40001
Description	Tests The SCA runtime MUST support the default JMS wire format and operation selector behavior, and MAY provide additional means to override it
Artifacts	BJM_4001_TestCase.java Test_BJM_4001.composite Service1.wsdl
Expected output	Positive test: "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_4001 request message</return>"

## BJM\_40002\_1\_TestCase

Testcase ID	BJM_40002_1_TestCase
Test Assertion	BJM-TA-40002
Description	Tests if operationSelector.jmsDefault is used if no operationSelector element is specified

	This tests if there is only one operation on the service's interface, then that operation is the selected operation name
Artifacts	BJM_4002_TestCase.java Test_BJM_4002.composite TestComposite21.composite Service1.wsdl
Expected output	Positive test: “<?xml version="1.0" encoding="UTF-8"?><return>service1 operation1 invoked with BJM_4002_1 request message</return>”

## BJM\_4002\_2\_TestCase

Testcase ID	BJM_4002_2_TestCase
Test Assertion	BJM-TA-40002
Description	Tests if operationSelector.jmsDefault is used if no operationSelector element is specified  This tests when more than one operation in the interface; the JMS user property "scaOperationName" is present and the value of that user property is used as the selected operation name
Artifacts	BJM_4002__2_TestCase.java Test_BJM_4002.composite TestComposite21.composite Service2.wsdl
Expected output	Positive test: “<?xml version="1.0" encoding="UTF-8"?><return>service2 operation2 invoked with BJM_4002_2 request message</return>”

## BJM\_4002\_3\_TestCase

Testcase ID	BJM_4002_3_TestCase
Test Assertion	BJM-TA-40002
Description	Tests if operationSelector.jmsDefault is used if no operationSelector element is specified  This tests when more than one operation in the interface; no scaOperationName user property; the message is a JMS text or bytes message containing XML, and the selected operation name is the local name of the root element of the XML payload.
Artifacts	BJM_4002_3_TestCase.java Test_BJM_4002.composite TestComposite21.composite Service2.wsdl
Expected output	Positive test: “<?xml version="1.0" encoding="UTF-8"?><return>service2 operation2 invoked



	with BJM_4002 request message</return>”
--	---

## BJM\_40002\_4\_TestCase

Testcase ID	BJM_40002_4_TestCase
Test Assertion	BJM-TA-40002
Description	<p>Tests if operationSelector.jmsDefault is used if no operationSelector element is specified</p> <p>This tests when more than one operation in the interface; no scaOperationName user property; no top-level XML element in the message body matching an operation name; the selected operation name is "onMessage"</p>
Artifacts	<p>BJM_4002_4_TestCase.java</p> <p>Test_BJM_4002.composite</p> <p>TestComposite21.composite</p> <p>Service5.wsdl</p>
Expected output	<p>Positive test:</p> <p>“&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service5 onMessage invoked with BJM_4002_4 request message&lt;/return&gt;”</p>

## BJM\_40003\_TestCase

Testcase ID	BJM_40003_TestCase
Test Assertion	BJM-TA-40003
Description	<p>Tests when using the default wire format to send request messages, if there is a single parameter and the interface includes more than one operation, the SCA runtime MUST set the JMS user property "scaOperationName" to the name of the operation being invoked</p>
Artifacts	<p>BJM_4003_TestCase.java</p> <p>Test_BJM_4003.composite</p>
Expected output	<p>Positive test:</p> <p>“&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;Service2Impl2.operation1 service1 operation1 invoked with BJM_4003 request message&lt;/return&gt;”</p>

## BJM\_40004\_TestCase

Testcase ID	BJM_40004_TestCase
Test Assertion	BJM-TA-40004
Description	<p>Tests if no wireFormat element is specified in a JMS binding then SCA runtimes MUST use wireFormat.jmsDefault as the default</p>
Artifacts	<p>BJM_4004_TestCase.java</p> <p>Test_BJM_4004.composite</p> <p>TestComposite1.composite</p> <p>Service1.wsdl</p>
Expected output	Negative test:

	"exception"
--	-------------

## BJM\_40004\_2\_TestCase

Testcase ID	BJM_40004_2_TestCase
Test Assertion	BJM-TA-40004
Description	Tests if no wireFormat element is specified in a JMS binding then SCA runtimes MUST use wireFormat.jmsDefault as the default
Artifacts	BJM_4004_2_TestCase.java Test_BJM_4004.composite TestComposite1.composite Service1.wsdl
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_4004 request message</return>"

## BJM\_40005T\_TestCase

Testcase ID	BJM_40005T_TestCase
Test Assertion	BJM-TA-40005
Description	Tests When using the default wire format an SCA runtime MUST be able to receive both JMS text and bytes messages  This is the Text message test
Artifacts	BJM_4005T_TestCase.java Test_BJM_4005.composite TestComposite1.composite Service1.wsdl
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_4005 request message</return>"

## BJM\_40005B\_TestCase

Testcase ID	BJM_40005B_TestCase
Test Assertion	BJM-TA-40005
Description	Tests When using the default wire format an SCA runtime MUST be able to receive both JMS text and bytes messages  This is the Bytes message test
Artifacts	BJM_4005B_TestCase.java Test_BJM_4005.composite TestComposite1.composite Service1.wsdl

Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service1 operation1 invoked with BJM_4005 request message&lt;/return&gt;</pre>
-----------------	---

## BJM\_4006\_TestCase

Testcase ID	BJM_4006_TestCase
Test Assertion	BJM-TA-40006
Description	Tests when using the default wire format an SCA runtime MUST send either a JMS text or a JMS bytes message
Artifacts	BJM_4006_TestCase.java Test_BJM_4006.composite TestComposite34.composite Service3.wsdl
Expected output	Positive test: “Reply message is BytesMessage or TextMessage”

## BJM\_4008\_TestCase

Testcase ID	BJM_4008_TestCase
Test Assertion	BJM-TA-40008
Description	Tests when a binding.jms element specifies the operationSelector.jmsDefault element, the SCA runtime MUST use the default operation selection algorithm to determine the selected operation
Artifacts	BJM_4008_TestCase.java Test_BJM_4008.composite TestComposite21.composite Service2.wsdl
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service2 operation2 invoked with BJM_4008 request message&lt;/return&gt;</pre>

## BJM\_4009\_TestCase

Testcase ID	BJM_4009_TestCase
Test Assertion	BJM-TA-40009
Description	Tests when a binding.jms element specifies the wireFormat.jmsDefault element, the SCA runtime MUST use the default wire format
Artifacts	BJM_4009_TestCase.java Test_BJM_4009.composite TestComposite1.composite Service1.wsdl
Expected output	Positive test:

	“<?xml version="1.0" encoding="UTF-8"?><return>service1 operation1 invoked with BJM_4009 request message</return>”
--	--

## BJM\_40010\_TestCase

Testcase ID	BJM_40010_TestCase
Test Assertion	BJM-TA-40010
Description	Tests when a message is received at an SCA service with JMS binding and the resolved operation name is in the target component's interface, the SCA runtime MUST invoke the target component using the resolved operation name
Artifacts	BJM_4010_TestCase.java Test_BJM_4010.composite TestComposite21.composite Service2.wsdl
Expected output	Positive test:  “<?xml version="1.0" encoding="UTF-8"?><return>service2 operation2 invoked with BJM_4010 request message</return>”

## BJM\_40011\_TestCase

Testcase ID	BJM_40011_TestCase
Test Assertion	BJM-TA-40011
Description	Tests when a message is received at an SCA service with JMS binding and the resolved operation name is not in the target component's interface the SCA runtime MUST raise an error
Artifacts	BJM_4011_TestCase.java Test_BJM_4011.composite TestComposite21.composite Service2.wsdl
Expected output	Negative test:  “exception”

## BJM\_50001\_TestCase

Testcase ID	BJM_50001_TestCase
Test Assertion	BJM-TA-50001
Description	Tests that the JMS binding implementations MUST support the JMS intent
Artifacts	BJM_5001_TestCase.java Test_BJM_5001.composite TestComposite1.composite Service1.wsdl
Expected output	Positive test:  “<?xml version="1.0" encoding="UTF-8"?><return>service1 operation1 invoked

	with BJM_5001 request message</return>”
--	---

## BJM\_60002\_TestCase

Testcase ID	BJM_60002_TestCase
Test Assertion	BJM-TA-60002
Description	Tests that for an SCA service with a JMS binding and unidirectional interface, when a request message is received as part of a one-way MEP, the SCA runtime MUST ignore the JMSReplyTo destination header in the JMS message, and not raise an error
Artifacts	BJM_6002_TestCase.java Test_BJM_6002.composite TestComposite34.composite Service3.wsdl
Expected output	Positive test:  “<?xml version=“1.0” encoding=“UTF-8”?><arg0>service3 operation1 invoked with BJM_6002 request message</arg0>”

## BJM\_60003\_1\_TestCase

Testcase ID	BJM_60003_1_TestCase
Test Assertion	BJM-TA-60003
Description	Tests that for an SCA reference with a JMS binding that has a destination specified via the response element, the SCA runtime MUST receive response messages as defined by the binding's @correlationScheme attribute.  This is the test for the messageID correlation scheme
Artifacts	BJM_6003_1_TestCase.java Test_BJM_6003.composite Service1.wsdl TestComposite1.composite TestInvocation.wsdl
Expected output	Positive test:  “<?xml version=“1.0” encoding=“UTF-8”?><return>service1 operation1 invoked service1 operation1 invoked with BJM_6003_1 request message</return>”

## BJM\_60003\_2\_TestCase

Testcase ID	BJM_60003_2_TestCase
Test Assertion	BJM-TA-60003
Description	Tests that for an SCA reference with a JMS binding that has a destination specified via the response element, the SCA runtime MUST receive response messages as defined by the binding's @correlationScheme attribute.  This is the test for the correlationID correlation scheme
Artifacts	BJM_6003_2_TestCase.java

	Test_BJM_6003.composite Service1.wsdl TestComposite1.composite TestInvocation.wsdl
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service1 operation1 invoked service1 operation1 invoked with BJM_6003_2 request message&lt;/return&gt;</pre>

### BJM\_60003\_3\_TestCase

Testcase ID	BJM_60003_3_TestCase
Test Assertion	BJM-TA-60003
Description	<p>Tests that for an SCA reference with a JMS binding that has a destination specified via the response element, the SCA runtime MUST receive response messages as defined by the binding's @correlationScheme attribute.</p> <p>This is the test for the none correlation scheme</p>
Artifacts	BJM_6003_3_TestCase.java Test_BJM_6003.composite Service1.wsdl TestComposite1.composite TestInvocation.wsdl
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;return&gt;service1 operation1 invoked service1 operation1 invoked with BJM_6003_3 request message&lt;/return&gt;</pre>

### BJM\_60004\_TestCase

Testcase ID	BJM_60004_TestCase
Test Assertion	BJM-TA-60004
Description	<p>Tests that for an SCA reference with a JMS binding, when a request message is sent as part of a request/response MEP, and the JMS binding has a response element with a destination defined, then the SCA runtime MUST use that destination for the JMSReplyTo header in the JMS message it creates for the request</p>
Artifacts	BJM_6004_TestCase.java Test_BJM_6004.composite
Expected output	Positive test: <p>"JMSReplyTo is as expected"</p>

### BJM\_60005\_TestCase

Testcase ID	BJM_60005_TestCase
Test Assertion	BJM-TA-60005
Description	Tests that for an SCA reference with a JMS binding, when a request message is

	sent as part of a request/response MEP, and the JMS binding does not have a response element with a destination defined, the SCA runtime MUST provide an appropriate destination on which to receive response messages and use that destination for the JMSReplyTo header in the JMS message it creates for the request
Artifacts	BJM_6005_TestCase.java Test_BJM_6005.composite
Expected output	Positive test: "JMSReplyTo is set"

## BJM\_60007\_TestCase

Testcase ID	BJM_60007_TestCase
Test Assertion	BJM-TA-60007
Description	Tests that for an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a non-null JMSReplyTo destination, the SCA runtime MUST send the response message to that destination
Artifacts	BJM_6007_TestCase.java Test_BJM_6007.composite Service1.wsdl TestComposite1.composite
Expected output	Positive test: "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_6007 request message</return>"

## BJM\_60007\_2\_TestCase

Testcase ID	BJM_60007_2_TestCase
Test Assertion	BJM-TA-60007
Description	Tests that for an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a non-null JMSReplyTo destination, the SCA runtime MUST send the response message to that destination  This is the case where the service binding includes a response destination, which should be ignored as the JMSReplyTo should be used.
Artifacts	BJM_6007_2_TestCase.java Test_BJM_6007.composite Service1.wsdl TestComposite1.composite
Expected output	Positive test: "<?xml version='1.0' encoding='UTF-8'?'><return>service1 operation1 invoked with BJM_6007 request message</return>"

## BJM\_60008\_TestCase

Testcase ID	BJM_60008_TestCase
Test Assertion	BJM-TA-60008
Description	Tests that for an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a null JMSReplyTo destination and the JMS binding includes a response/destination element the SCA runtime MUST send the response message to that destination
Artifacts	BJM_6008_TestCase.java Test_BJM_6008.composite TestComposite1.composite Service1.wsdl
Expected output	Positive test: “<?xml version="1.0" encoding="UTF-8"?><return>service1 operation1 invoked with BJM_6008 request message</return>”

## BJM\_60011\_TestCase

Testcase ID	BJM_60011_TestCase
Test Assertion	BJM-TA-60011
Description	Tests that for an SCA reference with a JMS binding and a bidirectional interface, when a request message is sent as part of a request/response MEP the SCA runtime MUST set the scaCallbackDestination user property in the message it creates to a JMS URI string, in the format defined by the IETF URI Scheme for Java Message Service 1.0 <del>[IETFJMS]</del> <del>[IETFJMS]</del> , that identifies the destination to which callback messages are to be sent
Artifacts	BJM_6011_TestCase.java Test_BJM_6011.composite Service3Impl3.java
Expected output	Positive test: “scaCallbackDestination property is a jms URI”

## BJM\_60012\_TestCase

Testcase ID	BJM_60012_TestCase
Test Assertion	BJM-TA-60012
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, when a request message is sent as part of a one-way MEP the SCA runtime MUST set the destination to which callback messages are to be sent as the JMSReplyTo destination in the message it creates
Artifacts	BJM_6012_TestCase.java Test_BJM_6012.composite Service3Impl4.java
Expected output	Positive test: “JMSReplyTo is set”



## BJM\_60013\_TestCase

Testcase ID	BJM_60013_TestCase
Test Assertion	BJM-TA-60013
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, when a request message is sent as part of a request/response MEP, the SCA runtime MUST set the JMSReplyTo header in the message it creates as described in section 6.2
Artifacts	BJM_6013_TestCase.java Test_BJM_6013.composite Service3Impl3.java
Expected output	Positive test: “JMSReplyTo header is set”

## BJM\_60013\_2\_TestCase

Testcase ID	BJM_60013_2_TestCase
Test Assertion	BJM-TA-60013
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, when a request message is sent as part of a request/response MEP, the SCA runtime MUST set the JMSReplyTo header in the message it creates as described in section 6.2
Artifacts	BJM_6013_2_TestCase.java Test_BJM_6013_2.composite Service3Impl3.java
Expected output	Positive test: “JMSReplyTo header is set as expected”

## BJM\_60014\_1\_1\_TestCase

Testcase ID	BJM_60014_1_1_TestCase
Test Assertion	BJM-TA-60014
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, the SCA runtime MUST identify the callback destination from the reference's callback service binding if present, or supply a suitable callback destination if not present  This is the test for the destination defined on the callback binding using a uri attribute
Artifacts	BJM_6014_1_1_TestCase.java Test_BJM_6014_1_1.composite Service3Impl3.java
Expected output	Positive test: “scaCallbackDestination property is a jms URI”

## BJM\_60014\_1\_2\_TestCase

Testcase ID	BJM_60014_1_2_TestCase
Test Assertion	BJM-TA-60014
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, the SCA runtime MUST identify the callback destination from the reference's callback service binding if present, or supply a suitable callback destination if not present  This is the case where the callback destination is specified on the binding by a destination element
Artifacts	BJM_6014_1_2_TestCase.java  Test_BJM_6014_1_2.composite  Service3Impl3.java
Expected output	Positive test:  "scaCallbackDestination property is a jms URI"

## BJM\_60014\_2\_TestCase

Testcase ID	BJM_60014_2_TestCase
Test Assertion	BJM-TA-60014
Description	Tests that for an SCA reference with a JMS binding and bidirectional interface, the SCA runtime MUST identify the callback destination from the reference's callback service binding if present, or supply a suitable callback destination if not present  This is the test for the destination defined on the callback binding using a <destination> element
Artifacts	BJM_6014_2_TestCase.java  Test_BJM_6014_2.composite  Service3Impl3.java
Expected output	Positive test:  "scaCallbackDestination property is a jms URI"

## BJM\_60015\_1\_TestCase

Testcase ID	BJM_60015_1_TestCase
Test Assertion	BJM-TA-60015
Description	For an SCA service with a JMS binding, when a callback request message is sent for either a one-way or request/response MEP, the SCA runtime MUST send the callback request message to the callback destination.  This is test for the service callback binding identifying the callback destination
Artifacts	BJM_6015_1_TestCase.java  Test_BJM_6015.composite  Service4Impl1.java
Expected output	Positive test:  "<?xml version='1.0' encoding='UTF-8'?'><arg0>onewayOperation1 callback

	request</arg0>”
--	-----------------

## BJM\_60015\_2\_TestCase

Testcase ID	BJM_60015_2_TestCase
Test Assertion	BJM-TA-60015
Description	<p>For an SCA service with a JMS binding, when a callback request message is sent for either a one-way or request/response MEP, the SCA runtime MUST send the callback request message to the callback destination.</p> <p>This is test for the scaCallbackDestination property identifying the callback destination</p>
Artifacts	<p>BJM_6015_2_TestCase.java</p> <p>Test_BJM_6015.composite</p> <p>Service4Impl1.java</p>
Expected output	<p>Positive test:</p> <p>“&lt;?xml version=“1.0” encoding=“UTF-8”?&gt;&lt;arg0&gt;onewayOperation1 callback request&lt;/arg0&gt;”</p>

## BJM\_60015\_3\_TestCase

Testcase ID	BJM_60015_3_TestCase
Test Assertion	BJM-TA-60015
Description	<p>For an SCA service with a JMS binding, when a callback request message is sent for either a one-way or request/response MEP, the SCA runtime MUST send the callback request message to the callback destination.</p> <p>This is test for the JMS replyTo property identifying the callback destination</p>
Artifacts	<p>BJM_6015_3_TestCase.java</p> <p>Test_BJM_6015.composite</p> <p>Service4Impl1.java</p>
Expected output	<p>Positive test:</p> <p>“&lt;?xml version=“1.0” encoding=“UTF-8”?&gt;&lt;arg0&gt;onewayOperation1 callback request&lt;/arg0&gt;”</p>

## BJM\_60016\_TestCase

Testcase ID	BJM_60016_TestCase
Test Assertion	BJM-TA-60016
Description	<p>Tests that for an SCA service with a JMS binding, when a callback request message is sent and no callback destination can be identified then the SCA runtime SHOULD raise an error, and MUST throw an exception to the caller of the callback operation.</p>
Artifacts	<p>BJM_6016_TestCase.java</p> <p>Test_BJM_6016.composite</p> <p>Service4Impl1.java</p>
Expected output	Negative test:

	"excpetion"
--	-------------

## BJM\_60017\_1\_TestCase

Testcase ID	BJM_60017_1_TestCase
Test Assertion	BJM-TA-60017
Description	<p>Tests that for an SCA service with a JMS binding, when a callback request message is sent the SCA runtime MUST set the JMSReplyTo destination in the callback request message as defined in sections 6.1 or 6.2 as appropriate for the type of the callback operation invoked.</p> <p>This is the section 6.2 request-response callback case so a replyTo should be set.</p>
Artifacts	BJM_6017_1_TestCase.java Test_BJM_6017.composite Service4Impl2.java
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;arg0&gt;onewayOperation1 callback request&lt;/arg0&gt;</pre>

## BJM\_60017\_2\_TestCase

Testcase ID	BJM_60017_2_TestCase
Test Assertion	BJM-TA-60017
Description	<p>Tests that for an SCA service with a JMS binding, when a callback request message is sent the SCA runtime MUST set the JMSReplyTo destination in the callback request message as defined in sections 6.1 or 6.2 as appropriate for the type of the callback operation invoked.</p> <p>This is the section 6.1 oneway callback case so no replyTo should be set.</p>
Artifacts	BJM_6017_2_TestCase.java Test_BJM_6017.composite Service4Impl2.java
Expected output	Positive test: <pre>&lt;?xml version="1.0" encoding="UTF-8"?&gt;&lt;arg0&gt;operation1 callback request&lt;/arg0&gt;</pre>

### 3 Cross Mapping of Test Assertions to TestCases

Test Assertion	Test Cases
BJM-TA-30001	BJM_3001_TestCase
BJM-TA-30002	BJM_3002_1_TestCase,BJM_3002_2_TestCase
BJM-TA-30003	BJM_3003_TestCase
BJM-TA-30004	BJM_3004_TestCase
BJM-TA-30005	BJM_3005_TestCase
BJM-TA-30006	Not required (SCA runtimes MAY allow...)
BJM-TA-30007	BJM_3007_TestCase
BJM-TA-30010	Not required (TA SHOULD not MUST)
BJM-TA-30011	BJM_3011A_TestCase,BJM_3011C_TestCase BJM_3011D_TestCase
BJM-TA-30012	BJM_3012A_TestCase,BJM_3012C_TestCase BJM_3012D_TestCase
BJM-TA-30013	Not tested
BJM-TA-30014	BJM_3014A_TestCase,BJM_3014C_TestCase BJM_3014D_TestCase
BJM-TA-30015	BJM_3015Aa_TestCase,BJM_3015Ab_TestCase, BJM_3015Ac_TestCase,BJM_3015Ca_TestCase, BJM_3015Cb_TestCase,BJM_3015Cc_TestCase, BJM_3015Da_TestCase,BJM_3015Db_TestCase, BJM_3015Dc_TestCase
BJM-TA-30017	BJM_3017_TestCase
BJM-TA-30018	BJM_3018_TestCase
BJM-TA-30019	Not tested
BJM-TA-30020	BJM_3020_TestCase
BJM-TA-30021	BJM_3021_TestCase
BJM-TA-30022	Not tested
BJM-TA-30023	BJM_3023_TestCase
BJM-TA-30024-1	BJM_3024_1_TestCase
BJM-TA-30024-2	BJM_3024_2_TestCase
BJM-TA-30024-3	BJM_3024_3_TestCase
BJM-TA-30024-4	BJM_3024_4_TestCase
BJM-TA-30025-1	BJM_3025_1_TestCase
BJM-TA-30025-2	BJM_3025_2_TestCase
BJM-TA-30026-1	BJM_3026_1_TestCase
BJM-TA-30026-2	BJM_3026_2_TestCase
BJM-TA-30026-3	BJM_3026_3_TestCase
BJM-TA-30028	Not required (SCA runtimes MAY allow...)
BJM-TA-30029	BJM_3029_TestCase

BJM-TA-30030	Not required (SCA runtimes MAY allow...)
BJM-TA-30031	BJM_3031_TestCase
BJM-TA-30034	BJM_3034_TestCase
BJM-TA-30036	BJM_3036_TestCase
BJM-TA-30037	Not tested

Test Assertion	Test Cases
BJM-TA-40001	BJM_4001_TestCase
BJM-TA-40002	BJM_4002_1_TestCase, BJM_4002_2_TestCase, BJM_4002_3_TestCase, BJM_4002_4_TestCase
BJM-TA-40003	BJM_4003_TestCase
BJM-TA-40004	BJM_4004_TestCase, BJM_4004_2_TestCase
BJM-TA-40005	BJM_4005B_TestCase, BJM_4005T_TestCase
BJM-TA-40006	BJM_4006_TestCase
BJM-TA-40007	Not required (SCA runtimes MAY allow...)
BJM-TA-40008	BJM_4008_TestCase
BJM-TA-40009	BJM_4009_TestCase
BJM-TA-40010	BJM_4010_TestCase
BJM-TA-40011	BJM_4011_TestCase

Test Assertion	Test Cases
BJM-TA-50001	BJM_5001_TestCase
BJM-TA-50002	Not tested

Test Assertion	Test Cases
BJM-TA-60001	Not tested
BJM-TA-60002	BJM_6002_TestCase
BJM-TA-60003	BJM_6003_1_TestCase, BJM_6003_2_TestCase, BJM_6003_3_TestCase
BJM-TA-60004	BJM_6004_TestCase
BJM-TA-60005	BJM_6005_TestCase
BJM-TA-60006	Not tested
BJM-TA-60007	BJM_6007_TestCase, BJM_6007_2_TestCase
BJM-TA-60008	BJM_6008_TestCase
BJM-TA-60009	Not required (SHOULD not MUST)
BJM-TA-60010	Not tested
BJM-TA-60011	BJM_6011_TestCase
BJM-TA-60012	BJM_6012_TestCase
BJM-TA-60013	BJM_6013_TestCase, BJM_6013_2_TestCase
BJM-TA-60014-1	BJM_6014_1_1_TestCase, BJM_6014_1_2_TestCase

	ase
BJM-TA-60014-2	BJM 6014 2 TestCase
BJM-TA-60015	BJM_6015_1_TestCase, BJM_6015_2_TestCase, BJM 6015 3 TestCase
BJM-TA-60016	BJM 6016 TestCase
BJM-TA-60017	BJM 6017 1 TestCase, BJM 6017 2 TestCase
BJM-TA-60018	Not tested

## 4 Catalog of Test Artifacts

### 4.1 Composite Files - lower level

Name	Valid	Description
TestClient_0001.composite	Y	<i>Test client invocation composite</i>  1 service TestInvocation interface TestInvocation  1 reference reference1 (1..1) interface Service1
TestComposite1.composite	Y	1 service Service1 interface Service1  0 references Service1Impl
TestComposite21.composite	Y	1 service Service2 interface Service2  0 references Service2Impl
TestComposite34.composite	Y	1 service Service3 interface Service3  1 reference Reference3 interface Service3 Service3Impl
TestComposite4.composite	Y	1 service Service1 interface Service1  0 references Service1Impl2

### 4.2 Java Interfaces

Name	Description
Service1.java	Remotable interface with 1 operation "operation1", string input and output
Service2.java	Remotable interface with 2 operations "operation1", string input and output "operation2", string input and output
Service3.java	Remotable interface with 1 oneway operation "operation1", string input
Service4.java	Remotable interface with call back Service4Callback, with 2 operations "operation1", string input and output



	"onewayOperation1", string input
Service5.java	Remotable interface with 2 operations "onMessage", string input and output "dummy", string input and output
Service4Callback.java	Remotable interface with 2 operations "callbackMessage", string input "callbackWithReply", string input and output
TestInvocation.java	Remotable interface with 1 operation "invokeTest", string input,string output

### 4.3 Java Implementation Classes

Name	Description
Service1Impl.java	1 service "Service1", 1 property "serviceName"
Service1Impl2.java	1 service "Service1", 1 property "serviceName", 1 reference "reference1"
Service2Impl.java	1 service "Service2", 1 property "serviceName"
Service2Impl2.java	1 service "Service2", 1 references "reference1"
Service3Impl2.java	1 service "Service3", 1 property "serviceName", 1 reference "reference3"
Service3Impl3.java	1 service "Service3", 1 property "serviceName", 1 reference "reference4"
Service3Impl4.java	1 service "Service3", 1 property "serviceName", 1 reference "reference4"
Service4Impl1.java	1 service "Service4"
Service4Impl2.java	1 service "Service4"
Service5Impl.java	1 service "Service5", 1 property "serviceName"
BJM_0001_Client.java	1 service "TestInvocation", 1 property "testName", 1 reference "reference1"

### 4.4 WSDL Interface Files

Name	Description
Service1.wsdl	Service1 interface 1 operation "operation1", string input and output
Service2.wsdl	Service2 interface

	2 operations “operation1”, string input and output “operation2”, string input and output
Service3.wsdl	Service3 interface 1 operation “operation1”, string input and no output
Service5.wsdl	Service5 interface 2 operations “onMessage”, string input and output “dummy”, string input and output
TestInvocation.wsdl	TestInvocation interface supplied by SCA component to allow client application to invoke test artifacts 1 operation: - "invokeTest" string input, string output

---

## 5 Conformance

There are no conformance statements relating to the TestCases.

## Appendix A. Test Assertions for the JMS Binding

This section defines the Test Assertions for the SCA JMS Binding specification, following the format defined in the OASIS Test Assertion Guidelines specification [TA-GUIDE].

### A.1. Example Test Assertion

Test assertions are presented in a tabular format with rows corresponding to the entry types defined in the OASIS Test Assertions Guidelines

Assertion ID	BJM-TA-nnnnn
	[BJMnnnnn]
Target	<xyuvbghs/> element of composite file
Prerequisites	The [<xyuvbghs/> element] has a @foobar attribute
Predicate	The @foobar attribute of [the <xyuvbghs/> element] is a URI that references a foobar element in the SCA Domain-
Prescription Level	Mandatory
Tags	foobar references

**Assertion ID:** Is a unique ID for the test assertion. Its format starts with a 3 letter string that identifies the specification to which it relates - "BJM" for the SCA JMS Binding specification. This is followed by "-TA-" to indicate that this identifier is for a test assertion. This is then followed by a unique 5 digit number

**Source:** Is the identifier(s) of the normative statement(s) in the specification to which this assertion relates.

**Target:** Identifies the target which is addressed by this assertion. This is typically some SCA document element, but possibly could identify an SCA runtime and its behaviour.

**Prerequisites:** Defines any prerequisites for this test assertion. The prerequisites may be defined in terms of one or more other test assertions that must be true.

**Predicate:** The meat of the assertion - something that should evaluate to true or false for the given target.

**Prescription Level:** Mandatory (for MUST requirements) or Preferred (for SHOULD requirements) or Permitted (for MAY requirements).

**Tags:** Zero or more labels that may be attached to this test assertion - these tags can be used to group sets of assertions.

### A.2. Test Assertions for JMS Bindings Specification Section 3

Assertion ID	BJM-TA-30001
Source	[BJM30001]
Target	The @uri attribute of a <binding.jms> element
Prerequisites	
Predicate	The @uri attribute matches the syntax defined in [IETFJMS]
Prescription Level	Mandatory
Tags	uri
Comment	The value of the @uri attribute MUST have the format defined by the IETF URI

	<b>Scheme for Java™ Message Service 1.0 [IETFJMS]</b>
--	---

<b>Assertion ID</b>	BJM-TA-30002
<b>Source</b>	[BJM30002]
<b>Target</b>	The @uri attribute of a <binding.jms> element
<b>Prerequisites</b>	One or more of the JNDI resources identified by the destination and jndiConnectionFactoryName in the @uri attribute does not exist
<b>Predicate</b>	SCA runtime raises an error
<b>Prescription Level</b>	Mandatory
<b>Tags</b>	uri, jndi
<b>Comment</b>	When the @uri attribute is specified, the SCA runtime MUST raise an error if the referenced resources do not already exist

<b>Assertion ID</b>	BJM-TA-30003
<b>Source</b>	[BJM30003]
<b>Target</b>	The @correlationScheme attribute of a <binding.jms> element
<b>Prerequisites</b>	1) <binding.jms> element child of a <service> element has the @correlationScheme attribute set to "sca:messageID" 2) the <service> element has an interface that includes at least one request/reply operation
<b>Predicate</b>	The correlation ID of a reply message is set to the value of the message ID of the corresponding request message when a request/reply operation is invoked
<b>Prescription Level</b>	Mandatory
<b>Tags</b>	request/reply, correlation, service
<b>Comment</b>	If the value of the @correlationScheme attribute is "sca:messageID" the SCA runtime MUST set the correlation ID of replies to the message ID of the corresponding request

<b>Assertion ID</b>	BJM-TA-30004
<b>Source</b>	[BJM30004]
<b>Target</b>	The @correlationScheme attribute of a <binding.jms> element
<b>Prerequisites</b>	1) <binding.jms> element child of a <service> element has the @correlationScheme attribute set to "sca:correlationID" 2) the <service> element has an interface that includes at least one request/reply operation
<b>Predicate</b>	The correlation ID of a reply message is set to the value of the correlation ID of the corresponding request message when a request/reply operation is invoked
<b>Prescription Level</b>	Mandatory
<b>Tags</b>	request/reply, correlation, service
<b>Comment</b>	If the value of the @correlationScheme attribute is "sca:correlationID" the SCA runtime MUST set the correlation ID of replies to the correlation ID of the corresponding request

<b>Assertion ID</b>	BJM-TA-30005
---------------------	--------------

<u>Source</u>	<u>[BJM30005]</u>
<u>Target</u>	<u>The @correlationScheme attribute of a &lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>1) &lt;binding.jms&gt; element child of a &lt;service&gt; element has the @correlationScheme attribute set to "sca:none"</u> <u>2) the &lt;service&gt; element has an interface that includes at least one request/reply operation</u>
<u>Predicate</u>	<u>The correlation ID of a reply message is unset when a request/reply operation is invoked</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>request/reply, correlation, service</u>
<u>Comment</u>	<u>If the value of the @correlationScheme attribute is "sca:none" the SCA runtime MUST NOT set the correlation ID in responses that it sends</u>

<u>Assertion ID</u>	<u>BJM-TA-30006</u>
<u>Source</u>	<u>[BJM30006]</u>
<u>Target</u>	<u>The @correlationScheme attribute of a &lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element child of a &lt;service&gt; element has the @correlationScheme attribute set to some value other than "sca:messageID", "sca:correlationID", "sca:none".</u> <u>The value selected has a specific meaning for the target SCA runtime</u>
<u>Predicate</u>	<u>SCA runtime does not raise an error</u>
<u>Prescription Level</u>	<u>Optional</u>
<u>Tags</u>	<u>request/reply, correlation, service</u>
<u>Comment</u>	<u>SCA runtimes MAY allow other values of the @correlationScheme attribute to indicate other correlation schemes</u> <u>This is untestable. Each SCA runtime may accept additional values, however it will still reject values that it does not understand.</u>

<u>Assertion ID</u>	<u>BJM-TA-30007</u>
<u>Source</u>	<u>[BJM30007]</u>
<u>Target</u>	<u>The @correlationScheme attribute of a &lt;binding.jms&gt; element child of a &lt;reference&gt; element</u>
<u>Prerequisites</u>	<u>1) &lt;binding.jms&gt; element child of a &lt;reference&gt; element has the @correlationScheme attribute set to "sca:correlationID"</u>
<u>Predicate</u>	<u>The correlation ID of request messages is set to a non-null value.</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>correlation, reference</u>
<u>Comment</u>	<u>If the value of the @correlationScheme attribute is "sca:correlationID" the SCA runtime MUST set a non-null correlation ID value in requests that it sends</u>

<u>Assertion ID</u>	<u>BJM-TA-30010</u>
<u>Source</u>	<u>[BJM30010]</u>
<u>Target</u>	<u>SCA Runtime</u>

<u>Prerequisites</u>	1) <u>interface with at least one request/reply operation</u> 2) <u>&lt;service&gt; with a child &lt;binding.jms&gt; element</u> <u>JMS client application invokes request/reply operation</u>
<u>Predicate</u>	<u>One and only one response is received by the JMS client application</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>request/reply, service</u>
<u>Comment</u>	<u>Whatever the value of the destination/@type attribute, the SCA runtime MUST ensure a single response is delivered for request/response operations</u> <u>This is untestable as there is no defined timescale over which the second response could appear</u>

<u>Assertion ID</u>	<u>BJM-TA-30011</u>
<u>Source</u>	<u>[BJM30011]</u>
<u>Target</u>	<u>@create attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	1) <u>@create attribute value is "always"</u> 2) <u>@jndiName attribute specified</u> 3) <u>Resource of the required type cannot be created at the JNDI location</u>
<u>Predicate</u>	<u>SCA runtime raises an error</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	<u>If the @create attribute value for a destination, connectionFactory or activationSpec element is "always" and the @jndiName attribute is present and the resource cannot be created at the location specified by the @jndiName attribute then the SCA runtime MUST raise an error</u>

<u>Assertion ID</u>	<u>BJM-TA-30012</u>
<u>Source</u>	<u>[BJM30012]</u>
<u>Target</u>	<u>@create attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	<u>@create attribute value is "ifNotExist"</u>
<u>Predicate</u>	<u>The @jndiName attribute specifies the location of the resource</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	<u>If the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" then the @jndiName attribute MUST specify the location of the possibly existing resource</u>

<u>Assertion ID</u>	<u>BJM-TA-30013</u>
<u>Source</u>	<u>[BJM30013]</u>
<u>Target</u>	<u>@create attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	1) <u>@create attribute value is "ifNotExist"</u> 2) <u>@jndiName attribute specified</u>

	3) resource does not exist at given JNDI location, and cannot be created there
<u>Predicate</u>	SCA runtime raises an error
<u>Prescription Level</u>	Mandatory
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	If the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" and the resource does not exist at the location identified by the @jndiName attribute and cannot be created there then the SCA runtime MUST raise an error

<u>Assertion ID</u>	<u>BJM-TA-30014</u>
<u>Source</u>	<u>[BJM30014]</u>
<u>Target</u>	<u>@jndiName attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	1) @create attribute value is "ifNotExist" 2) The @jndiName attribute refers to an existing resource 3) The existing resource is not of the correct type
<u>Predicate</u>	SCA runtime raises an error
<u>Prescription Level</u>	Mandatory
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	If the @create attribute value for a destination, connectionFactory or activationSpec element is "ifNotExist" and the @jndiName attribute refers to an existing resource that is not a JMS Destination of the appropriate type, a JMS connection factory or a JMS activation spec respectively then the SCA runtime MUST raise an error

<u>Assertion ID</u>	<u>BJM-TA-30015</u>
<u>Source</u>	<u>[BJM30015]</u>
<u>Target</u>	<u>@create attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	1) @create attribute value is "never" 2a) @jndiName not specified, or 2b) @jndiName specified but refers to a non-existent resource, or 2c) @jndiName specified but refers to a resource of an incorrect type
<u>Predicate</u>	SCA runtime raises an error
<u>Prescription Level</u>	Mandatory
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	If the @create attribute value for a destination, connectionFactory or activationSpec element is "never" and the @jndiName attribute is not specified, or the resource is not present at the location identified by the @jndiName attribute, or the location refers to a resource of an incorrect type then the SCA runtime MUST raise an error

<u>Assertion ID</u>	<u>BJM-TA-30017</u>
<u>Source</u>	<u>[BJM30017]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>



<u>Prerequisites</u>	
<u>Predicate</u>	<u>The &lt;binding.jms&gt; element does not have both a &lt;connectionFactory&gt; and &lt;activationSpec&gt; child element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>connectionFactory, activationSpec</u>
<u>Comment</u>	<u>A binding.jms element MUST NOT include both a connectionFactory element and an activationSpec element</u>

<u>Assertion ID</u>	<u>BJM-TA-30018</u>
<u>Source</u>	<u>[BJM30018]</u>
<u>Target</u>	<u>&lt;connectionFactory&gt; element child of &lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with a &lt;connectionFactory&gt; child</u>
<u>Predicate</u>	<u>The destination is defined either by the &lt;destination&gt; element child of the &lt;binding.jms&gt; element or by the @uri attribute of the &lt;binding.jms&gt; element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>connectionFactory, destination</u>
<u>Comment</u>	<u>When the connectionFactory element is present as a child of the binding.jms element, then the destination MUST be defined either by the destination element child of the binding.jms element or the @uri attribute of the binding.jms element</u>

<u>Assertion ID</u>	<u>BJM-TA-30019</u>
<u>Source</u>	<u>[BJM30019]</u>
<u>Target</u>	<u>&lt;activationSpec&gt; element child of &lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>1) &lt;binding.jms&gt; element with an &lt;activationSpec&gt; child 2) destination is defined either by the &lt;destination&gt; element or by the @uri attribute of the &lt;binding.jms&gt; element</u>
<u>Predicate</u>	<u>The destination defined by the &lt;destination&gt; element or @uri attribute refers to the same JMS destination as the &lt;activationSpec&gt;</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>activationSpec, destination</u>
<u>Comment</u>	<u>If the activationSpec element is present as a child of the binding.jms element and the destination is also specified via a destination element child of the binding.jms element or the @uri attribute of the binding.jms element then it MUST refer to the same JMS destination as the activationSpec</u>

<u>Assertion ID</u>	<u>BJM-TA-30020</u>
<u>Source</u>	<u>[BJM30020]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element child of a &lt;reference&gt; element</u>
<u>Predicate</u>	<u>The &lt;binding.jms&gt; element does not have an &lt;activationSpec&gt; child</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>reference, activationSpec</u>
<u>Comment</u>	<u>The activationSpec element MUST NOT be present when the binding is being used for an SCA reference</u>

<u>Assertion ID</u>	<u>BJM-TA-30021</u>
<u>Source</u>	<u>[BJM30021]</u>
<u>Target</u>	<u>&lt;response&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with &lt;response&gt; child element</u>
<u>Predicate</u>	<u>The &lt;response&gt; element does not include both a &lt;connectionFactory&gt; and &lt;activationSpec&gt; child</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>response, connectionFactory, activationSpec</u>
<u>Comment</u>	<u>A response element MUST NOT include both a connectionFactory element and an activationSpec element</u>

<u>Assertion ID</u>	<u>BJM-TA-30022</u>
<u>Source</u>	<u>[BJM30022]</u>
<u>Target</u>	<u>&lt;response&gt; element</u>
<u>Prerequisites</u>	<u>&lt;response&gt; element with both &lt;destination&gt; and &lt;activationSpec&gt; child elements</u>
<u>Predicate</u>	<u>The &lt;destination&gt; and &lt;activationSpec&gt; elements refer to the same destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>response, activationSpec, destination</u>
<u>Comment</u>	<u>If a response/destination and response/activationSpec element are both specified they MUST refer to the same JMS destination</u>

<u>Assertion ID</u>	<u>BJM-TA-30023</u>
<u>Source</u>	<u>[BJM30023]</u>
<u>Target</u>	<u>&lt;response&gt; element</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; element child with &lt;response&gt; element child</u>
<u>Predicate</u>	<u>The &lt;response&gt; element does not have an &lt;activationSpec&gt; child element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>response, activationSpec, service</u>
<u>Comment</u>	<u>The response/activationSpec element MUST NOT be present when the binding is being used for an SCA service</u>

<u>Assertion ID</u>	<u>BJM-TA-30024-1</u>
<u>Source</u>	<u>[BJM30024]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>@uri attribute including parameters specifying values for type, deliveryMode, timeToLive and priority</u>
<u>Predicate</u>	<u>JMS messages sent have JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers set as specified by the @uri element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, headers</u>
<u>Comment</u>	<u>When sending messages for a JMS binding, the SCA runtime MUST set each of the JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers to values</u>

	<p>specified in the binding definition in the following priority order:</p> <ul style="list-style-type: none"> <li>1) the value for the header specified in the @uri attribute (highest priority);</li> <li>2) the value for the header specified in the operationProperties/headers element matching the operation being invoked;</li> <li>3) the value for the header specified in the headers element;</li> <li>4) the default value for the header as specified by the definition of the binding.jms/headers element (lowest priority)</li> </ul>
--	---

Assertion ID	BJM-TA-30024-2
Source	[BJM30024]
Target	SCA runtime
Prerequisites	<p>1) operationProperties/headers element corresponding to the operation being invoked with values specified for one or more of @type, @deliveryMode, @timeToLive and @priority</p> <p>2) @uri attribute not present or not including parameters specifying values for those headers</p>
Predicate	JMS messages sent have JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers set as specified by the operationProperties/headers element for the operation being invoked
Prescription Level	Mandatory
Tags	uri, headers, operationProperties
Comment	Priority 2 case for BJM30024

Assertion ID	BJM-TA-30024-3
Source	[BJM30024]
Target	SCA runtime
Prerequisites	<p>1) headers element with values specified for one or more of @type, @deliveryMode, @timeToLive and @priority</p> <p>2) No operationProperties/headers element corresponding to the operation being invoked, or the operationProperties/headers element that does correspond to the operation being invoked does not have values specified those headers</p> <p>3) @uri attribute not present, or not including parameters specifying values for those headers</p>
Predicate	JMS messages sent have JMSType, JMSDeliveryMode, JMSTimeToLive and JMSPriority headers set as specified by the headers element
Prescription Level	Mandatory
Tags	uri, headers, operationProperties
Comment	Priority 3 case for BJM30024

Assertion ID	BJM-TA-30024-4
Source	[BJM30024]
Target	SCA runtime

<u>Prerequisites</u>	<p>1) <u>no headers element, or headers element no values specified for one or more of @type, @deliveryMode, @timeToLive and @priority</u></p> <p>2) <u>No operationProperties/headers element corresponding to the operation being invoked, or the operationProperties/headers element that does correspond to the operation being invoked does not have values specified those headers</u></p> <p>3) <u>@uri attribute not present, or not including parameters specifying values for those headers</u></p>
<u>Predicate</u>	<u>JMS messages sent have JMSDeliveryMode, JMSTimeToLive and JMSPriority headers set to default values of “persistent”, 0, and 4 respectively</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, headers, operationProperties</u>
<u>Comment</u>	<u>Priority 4 case for BJM30024; note that there is no defined default for the type parameter.</u>

<u>Assertion ID</u>	<u>BJM-TA-30025-1</u>
<u>Source</u>	<u>[BJM30025]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>operationProperties element corresponding to the operation being invoked with one or more headers/property children</u>
<u>Predicate</u>	<u>JMS messages sent include a user property for each operationProperties/headers/property element, with the given name, type and value</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>headers, operationProperties</u>
<u>Comment</u>	<p><u>When sending messages for a JMS binding, the SCA runtime MUST set each named user property with type and value specified in the binding definition in the following priority order:</u></p> <p><u>1) the type and value for the named user property specified in an operationProperties/headers/property element matching the name of the operation being invoked (highest priority);</u></p> <p><u>2) the type and value for the named user property specified in a headers/property element (lowest priority)</u></p>

<u>Assertion ID</u>	<u>BJM-TA-30025-2</u>
<u>Source</u>	<u>[BJM30025]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<p><u>headers element with one or more headers/property children</u></p> <p><u>No operationProperties element corresponding to the operation being invoked, or an operationProperties element corresponding to the operation being invoked with no headers/property children with the same names as those in the headers element</u></p>
<u>Predicate</u>	<u>JMS messages sent include a user property for each headers/property element, with the given name, type and value</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>headers, operationProperties</u>
<u>Comment</u>	<u>Priority 2 case for BJM30025</u>

<u>Assertion ID</u>	<u>BJM-TA-30026-1</u>
<u>Source</u>	<u>[BJM30026]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>@uri attribute including selector parameter</u>
<u>Predicate</u>	<u>Only messages received by the binding matching the selector specified in the @uri attribute are delivered to the component</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, selector</u>
<u>Comment</u>	<u>When receiving messages for a JMS binding, the SCA runtime MUST use a message selector if specified in the binding definition in the following priority order:</u> <u>1) the value for the message selector specified in the @uri attribute value's "selector" parameter (highest priority);</u> <u>2) the value for the message selector specified in the messageSelection/@selector attribute;</u> <u>3) otherwise no message selector is used (lowest priority)</u>

<u>Assertion ID</u>	<u>BJM-TA-30026-2</u>
<u>Source</u>	<u>[BJM30026]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>1) messageSelection/@selector attribute present</u> <u>2) @uri attribute not present, or not including selector parameter</u>
<u>Predicate</u>	<u>Only messages received by the binding matching the selector specified in the messageSelection/@selector attribute are delivered to the component</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, selector</u>
<u>Comment</u>	<u>Priority 2 case for BJM30026</u>

<u>Assertion ID</u>	<u>BJM-TA-30026-3</u>
<u>Source</u>	<u>[BJM30026]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>1) messageSelection/@selector attribute not present</u> <u>2) @uri attribute not present, or not including selector parameter</u>
<u>Predicate</u>	<u>All messages received by the binding are delivered to the component</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, selector</u>
<u>Comment</u>	<u>Priority 3 case for BJM30026</u>

<u>Assertion ID</u>	<u>BJM-TA-30028</u>
<u>Source</u>	<u>[BJM30028]</u>
<u>Target</u>	<u>&lt;resourceAdapter&gt; element</u>

<u>Prerequisites</u>	
<u>Predicate</u>	
<u>Prescription Level</u>	<u>Optional</u>
<u>Tags</u>	
<u>Comment</u>	<u>SCA runtimes MAY place restrictions on the properties of the resource adapter Java bean that can be set using the resourceAdapter element</u> <u>Nothing to test</u>

<u>Assertion ID</u>	<u>BJM-TA-30029</u>
<u>Source</u>	<u>[BJM30029]</u>
<u>Target</u>	<u>@selectedOperation attribute</u>
<u>Prerequisites</u>	<u>Multiple operationProperties/@selectedOperation attributes in the same binding.jms element</u>
<u>Predicate</u>	<u>All @selectedOperation attributes of operationProperties elements have different values</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>selectedOperation, operationProperties</u>
<u>Comment</u>	<u>The value of the operationProperties/@selectedOperation attribute MUST be unique across the containing binding.jms element</u>

<u>Assertion ID</u>	<u>BJM-TA-30030</u>
<u>Source</u>	<u>[BJM30030]</u>
<u>Target</u>	<u>&lt;operationProperties&gt; element</u>
<u>Prerequisites</u>	
<u>Predicate</u>	
<u>Prescription Level</u>	<u>Preferred</u>
<u>Tags</u>	<u>selectedOperation, operationProperties</u>
<u>Comment</u>	<u>The SCA runtime SHOULD make the operationProperties element corresponding to the selectedOperation available to the wireFormat implementation</u> <u>Nothing to test</u>

<u>Assertion ID</u>	<u>BJM-TA-30031</u>
<u>Source</u>	<u>[BJM30031]</u>
<u>Target</u>	<u>&lt;resourceAdapter&gt; element</u>
<u>Prerequisites</u>	<u>JMS provider for the resources referenced by the JMS binding is implemented using JCA 1.5 [JCA15]</u> <u>Destination, connectionFactory or activationSpec element with @create attribute value of "always" or "ifNotExist".</u>
<u>Predicate</u>	<u>The &lt;resourceAdapter&gt; element is present</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>resource adapter, destination, connectionFactory, activationSpec</u>
<u>Comment</u>	<u>The resourceAdapter element MUST be present when JMS resources are to be created for a JMS provider that implements the JCA 1.5 Specification [JCA15] specification, and is ignored otherwise</u>

<u>Assertion ID</u>	<u>BJM-TA-30034</u>
<u>Source</u>	<u>[BJM30034]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with @uri attribute</u>
<u>Predicate</u>	<u>The &lt;binding.jms&gt; element has no &lt;destination&gt; child element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>uri, destination</u>
<u>Comment</u>	<u>When the @uri attribute is specified, the destination element MUST NOT be present</u>

<u>Assertion ID</u>	<u>BJM-TA-30036</u>
<u>Source</u>	<u>[BJM30036]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	
<u>Predicate</u>	<u>The &lt;binding.jms&gt; element conforms to the XML schema</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	
<u>Comment</u>	<u>The binding.jms element MUST conform to the XML schema defined in sca-binding-jms-1.1.xsd</u>

<u>Assertion ID</u>	<u>BJM-TA-30037</u>
<u>Source</u>	<u>[BJM30037]</u>
<u>Target</u>	<u>@create attribute of a &lt;destination&gt;, &lt;connectionFactory&gt; or &lt;activationSpec&gt; element</u>
<u>Prerequisites</u>	<u>1) @create attribute value is "always"</u> <u>2) @jndiName attribute not specified</u> <u>3) Resource of the required type cannot be created</u>
<u>Predicate</u>	<u>SCA runtime raises an error</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>jndi, connectionFactory, activationSpec, destination</u>
<u>Comment</u>	<u>If the @create attribute value for a destination, connectionFactory or activationSpec element is "always" and the @jndiName attribute is not present and the resource cannot be created, then the SCA runtime MUST raise an error</u>

### **A.3. Test Assertions for JMS Bindings Specification Section 4**

<u>Assertion ID</u>	<u>BJM-TA-40001</u>
<u>Source</u>	<u>[BJM40001]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with either no &lt;wireFormat&gt; child or a &lt;wireFormat.jmsDefault&gt; child, and either no &lt;operationSelector&gt; child or a &lt;operationSelector.jmsDefault&gt; child.</u>
<u>Predicate</u>	<u>Messages sent by the service or reference adhere to the default wire format and operation selector behaviour, and messages received by the service or reference that</u>

	<u>follow this behaviour are correctly processed.</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, operationSelector, default</u>
<u>Comment</u>	<u>The SCA runtime MUST support the default JMS wire format and operation selector behavior, and MAY provide additional means to override it</u>

<u>Assertion ID</u>	<u>BJM-TA-40002</u>
<u>Source</u>	<u>[BJM40002]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with no &lt;operationSelector&gt; child</u>
<u>Predicate</u>	<u>The SCA runtime behaves as if &lt;operationSelector.jmsDefault&gt; was specified on the binding</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>operationSelector default</u>
<u>Comment</u>	<u>If no operationSelector element is specified then SCA runtimes MUST use operationSelector.jmsDefault as the default</u>

<u>Assertion ID</u>	<u>BJM-TA-40003</u>
<u>Source</u>	<u>[BJM40003]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with:</u> <u>&lt;binding.jms&gt; element with either no &lt;wireFormat&gt; child or &lt;wireFormat.jmsDefault&gt;</u> <u>&lt;interface&gt; element that identifies an interface with more than one operation, and at least one operation with a single parameter</u> <u>An invocation from a component connected to the service of one of the operations with a single parameter</u>
<u>Predicate</u>	<u>The JMS message sent from the service has the JMS user property "scaOperationName" set to the name of the operation being invoked</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, operation name</u>
<u>Comment</u>	<u>When using the default wire format to send request messages, if there is a single parameter and the interface includes more than one operation, the SCA runtime MUST set the JMS user property "scaOperationName" to the name of the operation being invoked</u>

<u>Assertion ID</u>	<u>BJM-TA-40004</u>
<u>Source</u>	<u>[BJM40004]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with no &lt;wireFormat&gt; child</u>
<u>Predicate</u>	<u>The SCA runtime behaves as if &lt;operationSelector.jmsDefault&gt; was specified on the binding</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, default</u>



<u>Comment</u>	<u>If no wireFormat element is specified in a JMS binding then SCA runtimes MUST use wireFormat.jmsDefault as the default</u>
----------------	---

<u>Assertion ID</u>	<u>BJM-TA-40005</u>
<u>Source</u>	<u>[BJM40005]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>A &lt;service&gt; or &lt;reference&gt; element with a &lt;binding.jms&gt; element with either no &lt;wireFormat&gt; child or a &lt;wireFormat.jmsDefault&gt; child</u>
<u>Predicate</u>	<u>Response messages sent to the reference and request messages sent to the service are accepted using either JMS text or JMS bytes format</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, default</u>
<u>Comment</u>	<u>When using the default wire format an SCA runtime MUST be able to receive both JMS text and bytes messages</u>

<u>Assertion ID</u>	<u>BJM-TA-40006</u>
<u>Source</u>	<u>[BJM40006]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>A &lt;service&gt; or &lt;reference&gt; element with a &lt;binding.jms&gt; element with either no &lt;wireFormat&gt; child or a &lt;wireFormat.jmsDefault&gt; child</u>
<u>Predicate</u>	<u>Response messages sent by the service and request messages sent by the reference are either JMS text or JMS bytes</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, default</u>
<u>Comment</u>	<u>When using the default wire format an SCA runtime MUST send either a JMS text or a JMS bytes message</u>

<u>Assertion ID</u>	<u>BJM-TA-40007</u>
<u>Source</u>	<u>[BJM40007]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;binding.jms&gt; element with either no &lt;wireFormat&gt; child element or the &lt;wireFormat.jmsDefault&gt; child element.</u>
<u>Predicate</u>	
<u>Prescription Level</u>	<u>Optional</u>
<u>Tags</u>	<u>wireFormat, default</u>
<u>Comment</u>	<u>When using the default wire format an SCA runtime MAY provide additional configuration to allow selection between JMS text or bytes messages to be sent</u>  <u>Nothing to test here</u>

<u>Assertion ID</u>	<u>BJM-TA-40008</u>
<u>Source</u>	<u>[BJM40008]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child with either no &lt;operationSelector&gt; child or</u>

	<u>a &lt;operationSelector.jmsDefault&gt; child</u>
<u>Predicate</u>	<u>The resolved operation name is identified using the JMS default operation selector algorithm</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>operationSelector, default</u>
<u>Comment</u>	<u>When a binding.jms element specifies the operationSelector.jmsDefault element, the SCA runtime MUST use the default operation selection algorithm to determine the selected operation</u>

<u>Assertion ID</u>	<u>BJM-TA-40009</u>
<u>Source</u>	<u>[BJM40009]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; or &lt;reference&gt; with &lt;binding.jms&gt; child with &lt;wireFormat.jmsDefault&gt; child</u>
<u>Predicate</u>	<u>Messages sent by the service or reference adhere to the default wire format behaviour, and messages received by the service or reference that follow this behaviour are correctly processed.</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>wireFormat, default</u>
<u>Comment</u>	<u>When a binding.jms element specifies the wireFormat.jmsDefault element, the SCA runtime MUST use the default wire format</u>

<u>Assertion ID</u>	<u>BJM-TA-40010</u>
<u>Source</u>	<u>[BJM40010]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>Resolved operation name in the target component's interface</u>
<u>Predicate</u>	<u>The target component's operation corresponding to the resolved operation name is invoked</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>resolved operation, operationSelector</u>
<u>Comment</u>	<u>When a message is received at an SCA service with JMS binding and the resolved operation name is in the target component's interface, the SCA runtime MUST invoke the target component using the resolved operation name</u>

<u>Assertion ID</u>	<u>BJM-TA-40011</u>
<u>Source</u>	<u>[BJM40011]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>Resolved operation name not in the target component's interface</u>
<u>Predicate</u>	<u>An error is raised by the SCA runtime</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>resolved operation, operationSelector</u>
<u>Comment</u>	<u>When a message is received at an SCA service with JMS binding and the resolved</u>

	<u>operation name is not in the target component's interface the SCA runtime MUST raise an error</u>
--	--

#### A.4. Test Assertions for JMS Bindings Specification Section 5

<u>Assertion ID</u>	<u>BJM-TA-50001</u>
<u>Source</u>	<u>[BJM50001]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>SCA service or reference element with requires="JMS" and binding.jms child.</u>
<u>Predicate</u>	<u>The SCA runtime does not report this as an error</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMS intent</u>
<u>Comment</u>	<u>JMS binding implementations MUST support the JMS intent</u>

<u>Assertion ID</u>	<u>BJM-TA-50002</u>
<u>Source</u>	<u>[BJM50002]</u>
<u>Target</u>	<u>JMS &lt;bindingType&gt; element</u>
<u>Prerequisites</u>	<u>&lt;bindingType&gt; element for the JMS binding</u>
<u>Predicate</u>	<u>The &lt;bindingType&gt; element includes the JMS intent in the @alwaysProvides attribute</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMS intent</u>
<u>Comment</u>	<u>The JMS intent MUST always be included in the @alwaysProvides attribute of the JMS bindingType</u>

#### A.5. Test Assertions for JMS Bindings Specification Section 6

<u>Assertion ID</u>	<u>BJM-TA-60001</u>
<u>Source</u>	<u>[BJM60001]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with:</u> <ul style="list-style-type: none"><li><u>No callback interface</u></li></ul> <u>&lt;binding.jms&gt; child</u>
<u>Predicate</u>	<u>JMS messages sent by the reference's JMS binding have a null JMSReplyTo destination</u>
<u>Prescription Level</u>	<u>Preferred</u>
<u>Tags</u>	<u>JMSReplyTo unidirectional reference one-way</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding and unidirectional interface, when a request message is sent as part of a one-way MEP, the SCA runtime SHOULD NOT set the JMSReplyTo destination header in the JMS message that it creates, regardless of whether the JMS binding has a response element with a destination defined</u>

<u>Assertion ID</u>	<u>BJM-TA-60002</u>
<u>Source</u>	<u>[BJM60002]</u>
<u>Target</u>	<u>SCA runtime</u>

<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>Request message corresponding to a one-way operation in the service's interface sent to the service's JMS binding with a non-null JMSReplyTo</u>
<u>Predicate</u>	<u>No error is raised</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo unidirectional service one-way</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding and unidirectional interface, when a request message is received as part of a one-way MEP, the SCA runtime MUST ignore the JMSReplyTo destination header in the JMS message, and not raise an error</u>

<u>Assertion ID</u>	<u>BJM-TA-60003</u>
<u>Source</u>	<u>[BJM60003]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child with &lt;response&gt; child with &lt;destination&gt; child element.</u>
<u>Predicate</u>	<u>Responses are received according to the value of the @correlationScheme attribute</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>reference request/response correlation</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding that has a destination specified via the response element, the SCA runtime MUST receive response messages as defined by the binding's @correlationScheme attribute</u>

<u>Assertion ID</u>	<u>BJM-TA-60004</u>
<u>Source</u>	<u>[BJM60004]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child with &lt;response&gt; child with &lt;destination&gt; child</u> <u>Request/response operation invoked using the JMS reference binding</u>
<u>Predicate</u>	<u>Request messages sent by the JMS reference binding have the JMSReplyTo set to the destination specified in the &lt;destination&gt; element</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo reference destination request/response</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding, when a request message is sent as part of a request/response MEP, and the JMS binding has a response element with a destination defined, then the SCA runtime MUST use that destination for the JMSReplyTo header in the JMS message it creates for the request</u>

<u>Assertion ID</u>	<u>BJM-TA-60005</u>
<u>Source</u>	<u>[BJM60005]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child with either no &lt;response&gt; child, or a &lt;response&gt; child with no &lt;destination&gt; child.</u> <u>Request/response operation invoked using the JMS reference binding</u>

<u>Predicate</u>	<u>Request messages sent by the JMS reference binding have the JMSReplyTo set to a non-null destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo reference destination request/response</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding, when a request message is sent as part of a request/response MEP, and the JMS binding does not have a response element with a destination defined, the SCA runtime MUST provide an appropriate destination on which to receive response messages and use that destination for the JMSReplyTo header in the JMS message it creates for the request</u>

<u>Assertion ID</u>	<u>BJM-TA-60006</u>
<u>Source</u>	<u>[BJM60006]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child, with either no &lt;response&gt; child, or a &lt;response&gt; child with no &lt;destination&gt; child element.</u>
<u>Predicate</u>	<u>Responses are received either on unique destinations, or according to the value of the @correlationScheme attribute</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Reference request/response destination correlation</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding that does not have a destination specified via the response element, the SCA runtime MUST either receive response messages as defined by the binding's @correlationScheme attribute, or use a unique destination for each request/response interaction</u>

<u>Assertion ID</u>	<u>BJM-TA-60007</u>
<u>Source</u>	<u>[BJM60007]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>Request message received as part of a request/response MEP with non-null JMSReplyTo destination</u>
<u>Predicate</u>	<u>Response message is sent by the service JMS binding to the JMSReplyTo destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo service response destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a non-null JMSReplyTo destination, the SCA runtime MUST send the response message to that destination</u>

<u>Assertion ID</u>	<u>BJM-TA-60008</u>
<u>Source</u>	<u>[BJM60008]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child with &lt;response&gt; child with &lt;destination&gt; child</u> <u>Request message received as part of a request/response MEP with null JMSReplyTo destination</u>

<u>Predicate</u>	<u>Response message is sent by the service JMS binding to the binding's response destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo service response destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a null JMSReplyTo destination and the JMS binding includes a response/destination element the SCA runtime MUST send the response message to that destination</u>

<u>Assertion ID</u>	<u>BJM-TA-60009</u>
<u>Source</u>	<u>[BJM60009]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child with either no &lt;response&gt; child, or a &lt;response&gt; child with no &lt;destination&gt; child</u>  <u>Request message received as part of a request/response MEP with null JMSReplyTo destination</u>
<u>Predicate</u>	<u>An error is raised by the SCA runtime</u>
<u>Prescription Level</u>	<u>Preferred</u>
<u>Tags</u>	<u>JMSReplyTo service response destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP where the request message included a null JMSReplyTo destination and the JMS binding does not include a response/destination then an error SHOULD be raised by the SCA runtime</u>

<u>Assertion ID</u>	<u>BJM-TA-60010</u>
<u>Source</u>	<u>[BJM60010]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u>  <u>Request message is received by the service JMS binding as part of a request/response MEP</u>
<u>Predicate</u>	<u>Response message sent by the service JMS binding with the correlation identifier set as defined by the @correlationScheme attribute</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Service response correlation</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a response message is sent as part of a request/response MEP the SCA runtime MUST set the correlation identifier in the JMS message that it creates for the response as defined by the JMS binding's @correlationScheme attribute</u>

<u>Assertion ID</u>	<u>BJM-TA-60011</u>
<u>Source</u>	<u>[BJM60011]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; with &lt;binding.jms&gt; child and bidirectional interface</u>
<u>Predicate</u>	<u>Request messages sent by the reference JMS binding for request/response</u>

	<u>interactions include the <code>scaCallbackDestination</code> user property whose value is a JMS URI string, in the format defined by the IETF URI Scheme for Java™ Message Service 1.0 [IETFJMS], that identifies the destination to which callback messages are to be sent</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Reference bidirectional callback destination</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding and a bidirectional interface, when a request message is sent as part of a request/response MEP the SCA runtime MUST set the <code>scaCallbackDestination</code> user property in the message it creates to a JMS URI string, in the format defined by the IETF URI Scheme for Java™ Message Service 1.0 [IETFJMS], that identifies the destination to which callback messages are to be sent</u>

<u>Assertion ID</u>	<u>BJM-TA-60012</u>
<u>Source</u>	<u>[BJM60012]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child and bidirectional interface, one-way operation invoked</u>
<u>Predicate</u>	<u>JMSReplyTo set to the destination for callback messages</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	
<u>Comment</u>	<u>For an SCA reference with a JMS binding and bidirectional interface, when a request message is sent as part of a one-way MEP the SCA runtime MUST set the destination to which callback messages are to be sent as the <code>JMSReplyTo</code> destination in the message it creates</u>

<u>Assertion ID</u>	<u>BJM-TA-60013</u>
<u>Source</u>	<u>[BJM60013]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; element with &lt;binding.jms&gt; child and bidirectional interface</u> <u>Request message sent as part of a request/response MEP</u>
<u>Predicate</u>	<u>Request messages sent by the reference JMS binding have the <code>JMSReplyTo</code> header set as in section 6.2</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Reference bidirectional JMSReplyTo</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding and bidirectional interface, when a request message is sent as part of a request/response MEP, the SCA runtime MUST set the <code>JMSReplyTo</code> header in the message it creates as described in section 6.2</u> <u>Already tested by BJM60004 and BJM60005</u>

<u>Assertion ID</u>	<u>BJM-TA-60014-1</u>
<u>Source</u>	<u>[BJM60014]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; with:</u> <ul style="list-style-type: none"><li>• <u>&lt;binding.jms&gt; child</u></li></ul>

	<ul style="list-style-type: none"> <li>• <u>bidirectional interface</u></li> </ul> <u>callback destination identified via callback service JMS binding</u>
<u>Predicate</u>	<u>Request messages sent by the reference JMS binding include the scaCallbackDestination user property set to the specified callback destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Reference bidirectional callback destination</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding and bidirectional interface, the SCA runtime MUST identify the callback destination from the reference's callback service binding if present, or supply a suitable callback destination if not present</u>

<u>Assertion ID</u>	<u>BJM-TA-60014-2</u>
<u>Source</u>	<u>[BJM60014]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;reference&gt; with:</u> <ul style="list-style-type: none"> <li>• <u>&lt;binding.jms&gt; child</u></li> <li>• <u>bidirectional interface</u></li> </ul> <u>no callback destination specified via callback service JMS binding</u>
<u>Predicate</u>	<u>Request messages sent by the reference JMS binding include the scaCallbackDestination user property set to a specified callback destination provided by the SCA runtime</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Reference bidirectional callback destination</u>
<u>Comment</u>	<u>For an SCA reference with a JMS binding and bidirectional interface, the SCA runtime MUST identify the callback destination from the reference's callback service binding if present, or supply a suitable callback destination if not present</u>

<u>Assertion ID</u>	<u>BJM-TA-60015</u>
<u>Source</u>	<u>[BJM60015]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>Callback destination identified as follows, in order of priority:</u> <ul style="list-style-type: none"> <li>• <u>The scaCallbackDestination identified by an earlier request, if not null;</u></li> <li>• <u>the JMSReplyTo destination identified by an earlier one-way request, if not null;</u></li> </ul> <u>the request destination of the service's callback reference JMS binding, if specified</u>
<u>Predicate</u>	<u>Request messages sent by the service's callback JMS reference are sent to the callback destination</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>Service callback destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a callback request message is sent for either a one-way or request/response MEP, the SCA runtime MUST send the callback</u>



	<u>request message to the callback destination.</u>
--	---

<u>Assertion ID</u>	<u>BJM-TA-60016</u>
<u>Source</u>	<u>[BJM60016]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u> <u>No <i>scaCallbackDestination</i> identified by an earlier request</u> <u>No <i>JMSReplyTo</i> destination identified by an earlier one-way request</u> <u>No request destination specified by the service's callback reference JMS binding</u>
<u>Predicate</u>	<u>When a callback request is made an exception is thrown</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo service callback destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a callback request message is sent and no callback destination can be identified then the SCA runtime SHOULD raise an error, and MUST throw an exception to the caller of the callback operation</u>

<u>Assertion ID</u>	<u>BJM-TA-60017</u>
<u>Source</u>	<u>[BJM60017]</u>
<u>Target</u>	<u>SCA runtime</u>
<u>Prerequisites</u>	<u>&lt;service&gt; element with &lt;binding.jms&gt; child</u>
<u>Predicate</u>	<u>Callback request messages have the <i>JMSReplyTo</i> set as defined in section 6.1 or 6.2 as appropriate</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	<u>JMSReplyTo service callback destination</u>
<u>Comment</u>	<u>For an SCA service with a JMS binding, when a callback request message is sent the SCA runtime MUST set the <i>JMSReplyTo</i> destination in the callback request message as defined in sections 6.1 or 6.2 as appropriate for the type of the callback operation invoked</u>

<u>Assertion ID</u>	<u>BJM-TA-60018</u>
<u>Source</u>	<u>[BJM60018]</u>
<u>Target</u>	<u>&lt;binding.jms&gt; element</u>
<u>Prerequisites</u>	<u>&lt;service&gt; or &lt;reference&gt; with &lt;binding.jms&gt; child, bidirectional interface and callback &lt;binding.jms&gt;</u>
<u>Predicate</u>	<u>Behaviour as defined in section 6.4 and its subsections is observed</u>
<u>Prescription Level</u>	<u>Mandatory</u>
<u>Tags</u>	
<u>Comment</u>	<u>SCA runtimes MUST follow the behavior described in section 6.4 and its subsections when <i>binding.jms</i> is used in both the forward and callback directions</u>

## A.6. Cross Mapping of Conformance Statements to Test Assertions

This section contains a list of conformance items for the SCA JMS Binding specification and the corresponding Test Assertions.

Conformance ID	Test Assertion
<a href="#">BJM30001</a>	<a href="#">BJM-TA-30001</a>
<a href="#">BJM30002</a>	<a href="#">BJM-TA-30002</a>
<a href="#">BJM30003</a>	<a href="#">BJM-TA-30003</a>
<a href="#">BJM30004</a>	<a href="#">BJM-TA-30004</a>
<a href="#">BJM30005</a>	<a href="#">BJM-TA-30005</a>
<a href="#">BJM30006</a>	<a href="#">BJM-TA-30006</a>
<a href="#">BJM30007</a>	<a href="#">BJM-TA-30007</a>
<a href="#">BJM30010</a>	<a href="#">BJM-TA-30010</a>
<a href="#">BJM30011</a>	<a href="#">BJM-TA-30011</a>
<a href="#">BJM30012</a>	<a href="#">BJM-TA-30012</a>
<a href="#">BJM30013</a>	<a href="#">BJM-TA-30013</a>
<a href="#">BJM30014</a>	<a href="#">BJM-TA-30014</a>
<a href="#">BJM30015</a>	<a href="#">BJM-TA-30015</a>
<a href="#">BJM30017</a>	<a href="#">BJM-TA-30017</a>
<a href="#">BJM30018</a>	<a href="#">BJM-TA-30018</a>
<a href="#">BJM30019</a>	<a href="#">BJM-TA-30019</a>
<a href="#">BJM30020</a>	<a href="#">BJM-TA-30020</a>
<a href="#">BJM30021</a>	<a href="#">BJM-TA-30021</a>
<a href="#">BJM30022</a>	<a href="#">BJM-TA-30022</a>
<a href="#">BJM30023</a>	<a href="#">BJM-TA-30023</a>
<a href="#">BJM30024</a>	<a href="#">BJM-TA-30024-1, BJM-TA-30024-2, BJM-TA-30024-3, BJM-TA-30024-4</a>
<a href="#">BJM30025</a>	<a href="#">BJM-TA-30025-1, BJM-TA-30025-2</a>
<a href="#">BJM30026</a>	<a href="#">BJM-TA-30026-1, BJM-TA-30026-2, BJM-TA-30026-3</a>
<a href="#">BJM30028</a>	<a href="#">BJM-TA-30028</a>
<a href="#">BJM30029</a>	<a href="#">BJM-TA-30029</a>
<a href="#">BJM30030</a>	<a href="#">BJM-TA-30030</a>
<a href="#">BJM30031</a>	<a href="#">BJM-TA-30031</a>
<a href="#">BJM30034</a>	<a href="#">BJM-TA-30034</a>
<a href="#">BJM30036</a>	<a href="#">BJM-TA-30036</a>
<a href="#">BJM30037</a>	<a href="#">BJM-TA-30037</a>
<a href="#">BJM40001</a>	<a href="#">BJM-TA-40001</a>
<a href="#">BJM40002</a>	<a href="#">BJM-TA-40002</a>
<a href="#">BJM40003</a>	<a href="#">BJM-TA-40003</a>
<a href="#">BJM40004</a>	<a href="#">BJM-TA-40004</a>
<a href="#">BJM40005</a>	<a href="#">BJM-TA-40005</a>
<a href="#">BJM40006</a>	<a href="#">BJM-TA-40006</a>
<a href="#">BJM40007</a>	<a href="#">BJM-TA-40007</a>

<a href="#">BJM40008</a>	<a href="#">BJM-TA-40008</a>
<a href="#">BJM40009</a>	<a href="#">BJM-TA-40009</a>
<a href="#">BJM40010</a>	<a href="#">BJM-TA-40010</a>
<a href="#">BJM40011</a>	<a href="#">BJM-TA-40011</a>
<a href="#">BJM50001</a>	<a href="#">BJM-TA-50001</a>
<a href="#">BJM50002</a>	<a href="#">BJM-TA-50002</a>
<a href="#">BJM60001</a>	<a href="#">BJM-TA-60001</a>
<a href="#">BJM60002</a>	<a href="#">BJM-TA-60002</a>
<a href="#">BJM60003</a>	<a href="#">BJM-TA-60003</a>
<a href="#">BJM60004</a>	<a href="#">BJM-TA-60004</a>
<a href="#">BJM60005</a>	<a href="#">BJM-TA-60005</a>
<a href="#">BJM60006</a>	<a href="#">BJM-TA-60006</a>
<a href="#">BJM60007</a>	<a href="#">BJM-TA-60007</a>
<a href="#">BJM60008</a>	<a href="#">BJM-TA-60008</a>
<a href="#">BJM60009</a>	<a href="#">BJM-TA-60009</a>
<a href="#">BJM60010</a>	<a href="#">BJM-TA-60010</a>
<a href="#">BJM60011</a>	<a href="#">BJM-TA-60011</a>
<a href="#">BJM60012</a>	<a href="#">BJM-TA-60012</a>
<a href="#">BJM60013</a>	<a href="#">BJM-TA-60013</a>
<a href="#">BJM60014</a>	<a href="#">BJM-TA-60014-1, BJM-TA-60014-2</a>
<a href="#">BJM60015</a>	<a href="#">BJM-TA-60015</a>
<a href="#">BJM60016</a>	<a href="#">BJM-TA-60016</a>
<a href="#">BJM60017</a>	<a href="#">BJM-TA-60017</a>
<a href="#">BJM60018</a>	<a href="#">BJM-TA-60018</a>

---

## Appendix B. Acknowledgments

The following individuals have participated in the creation of this specification and are gratefully acknowledged

### Participants:

Participant Name	Affiliation
Bryan Aupperle	IBM
Ron Barack	SAP AG
Michael Beisiegel	IBM
Henning Blohm	SAP AG
David Booz	IBM
Martin Chapman	Oracle Corporation
Jean-Sebastien Delfino	IBM
Laurent Domenech	TIBCO Software Inc.
Jacques Durand	Fujitsu Limited
Mike Edwards	IBM
Ant Elder	IBM
Billy Feng	Primeton Technologies, Inc.
Nimish Hathalia	TIBCO Software Inc.
Simon Holdsworth	IBM
Eric Johnson	TIBCO Software Inc.
Uday Joshi	Oracle Corporation
Khanderao Kand	Oracle Corporation
Anish Karmarkar	Oracle Corporation
Nickolaos Kavantzaz	Oracle Corporation
Mark Little	Red Hat
Ashok Malhotra	Oracle Corporation
Jim Marino	Individual
Jeff Mischkinsky	Oracle Corporation
Dale Moberg	Axway Software
Simon Nash	Individual
Sanjay Patil	SAP AG
Plamen Pavlov	SAP AG
Peter Peshev	SAP AG
Piotr Przybylski	IBM
Luciano Resende	IBM
Tom Rutt	Fujitsu Limited
Vladimir Savchenko	SAP AG
Scott Vorthmann	TIBCO Software Inc.
Tim Watson	Oracle Corporation
Owen Williams	Avaya, Inc.
Prasad Yendluri	Software AG, Inc.

---

## Appendix C. Revision History

Revision	Date	Editor	Changes Made
wd01	2010-04-15	Simon Holdsworth	Initial draft
wd02	2010-09-16	Ant Elder	Initial tests for wd06 test assertions doc
wd03	2010-10-07	Ant Elder	Review updates and wd07 test assertions doc
wd04	2010-10-21	Ant Elder	More review updates
wd05	2010-10-27	Ant Elder	Added BJM_3007 and further review updates
wd06	2010-10-29	Simon Holdsworth	Updated references, other editorial updates
wd07	2010-11-11	Ant Elder	Updated some expect messages texts