



Web Services ReliableMessaging Policy Assertion (WS-RM Policy) 1.1

Committee Draft 05

1 February 2007

Specification URIs:

This Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.html>

Previous Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200608/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200608/wsrmp-1.1-spec-cd-05.html>

Latest Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.html>

Latest Approved Version:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.pdf>

<http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-spec-cd-05.html>

Technical Committee:

OASIS Web Services Reliable Exchange (WS-RX) TC

Chairs:

Paul Fremantle <paul@wso2.com>

Sanjay Patil <sanjay.patil@sap.com>

Editors:

Doug Davis, IBM <dug@us.ibm.com>

Anish Karmarkar, Oracle <Anish.Karmarkar@oracle.com>

Gilbert Pilz, BEA <gpilz@bea.com>

Ümit Yalçınalp, SAP <umit.yalcinalp@sap.com>

Abstract:

This specification describes a domain-specific policy assertion for WS-ReliableMessaging [WS-RM] that can be specified within a policy alternative as defined in WS-Policy Framework [WS-Policy].

By using the XML [XML], SOAP [SOAP 1.1], [SOAP 1.2] and WSDL [WSDL 1.1] extensibility models, the WS* specifications are designed to be composed with each other to provide a rich Web services environment. This by itself does not provide a negotiation solution for Web services. This is a building block that is used in conjunction with other Web service and application-specific protocols to accommodate a wide variety of policy exchange models.

Status:

This document was last revised or approved by the WS-RX on the above date. The level of approval is also listed above. Check the "Latest Version" or "Latest Approved Version" location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <http://www.oasis-open.org/committees/ws-rx>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/ws-rx/ipr.php>).

The non-normative errata page for this specification is located at <http://www.oasis-open.org/committees/ws-rx>.

Notices

Copyright © OASIS® 1993–2007. All Rights Reserved. OASIS trademark, IPR and other policies apply.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The names "OASIS", [insert specific trademarked names, abbreviations, etc. here] are trademarks of OASIS, the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications,

94 while reserving the right to enforce its marks against misleading uses. Please see <http://www.oasis->
95 [open.org/who/trademark.php](http://www.oasis-open.org/who/trademark.php) for above guidance.

Table of Contents

96		
97	1	Introduction..... 6
98	1.1	Goals and Requirements..... 6
99	1.1	Terminology..... 6
100	1.2	Namespace..... 7
101	1.3	Compliance..... 7
102	2	RM Policy Assertions..... 8
103	2.1	Assertion Model 8
104	2.2	Normative Outline..... 8
105	2.3	Assertion Attachment..... 9
106	2.4	Assertion Example..... 11
107	2.5	Sequence Security Policy..... 11
108	3	Security Considerations..... 13
109	4	References..... 14
110	4.1	Normative..... 14
111	4.2	Non Normative..... 15
112		Appendix A. Acknowledgments..... 16
113		Appendix B. XML Schema..... 17
114		Appendix C. Revision History..... 19

1 Introduction

This specification defines a domain-specific policy assertion for reliable messaging for use with WS-Policy and WS-ReliableMessaging.

1.1 Goals and Requirements

1.1.1 Requirements

1.1 Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [KEYWORDS].

This specification uses the following syntax to define normative outlines for messages:

- The syntax appears as an XML instance, but values in italics indicate data types instead of values.
- Characters are appended to elements and attributes to indicate cardinality:
 - "?" (0 or 1)
 - "*" (0 or more)
 - "+" (1 or more)
- The character "|" is used to indicate a choice between alternatives.
- The characters "[" and "]" are used to indicate that contained items are to be treated as a group with respect to cardinality or choice.
- An ellipsis (i.e. "...") indicates a point of extensibility that allows other child, or attribute, content. Additional children and/or attributes MAY be added at the indicated extension points but MUST NOT contradict the semantics of the parent and/or owner, respectively. If an extension is not recognized it SHOULD be ignored.
- XML namespace prefixes (See Section 1.3) are used to indicate the namespace of the element being defined.

Elements and Attributes defined by this specification are referred to in the text of this document using XPath 1.0 [XPATH 1.0] expressions. Extensibility points are referred to using an extended version of this syntax:

- An element extensibility point is referred to using {any} in place of the element name. This indicates that any element name can be used, from any namespace other than the wsrmp namespace.
- An attribute extensibility point is referred to using @{any} in place of the attribute name. This indicates that any attribute name can be used, from any namespace other than the wsrmp namespace.

1.2 Namespace

The XML namespace [XML-ns] URI that MUST be used by implementations of this specification is:

<http://docs.oasis-open.org/ws-rx/wsrmp/200702>

Dereferencing the above URI will produce the Resource Directory Description Language [RDDL 2.0] document that describes this namespace.

Table 1 lists the XML namespaces that are used in this specification. The choice of any namespace prefix is arbitrary and not semantically significant.

Table 1

Prefix	Namespace	Specification
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL 1.1]
wsp	http://schemas.xmlsoap.org/ws/2004/09/policy	[WS-Policy]
wsrmp	http://docs.oasis-open.org/ws-rx/wsrmp/200702	This specification.
wsu	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd	WS-Security-Utility Schema

1.3 Compliance

An implementation is not compliant with this specification if it fails to satisfy one or more of the MUST or REQUIRED level requirements defined herein. A SOAP Node MUST NOT use the XML namespace identifier for this specification (listed in Section 1.3) within SOAP Envelopes unless it is compliant with this specification.

Normative text within this specification takes precedence over normative outlines, which in turn take precedence over the XML Schema [XML-Schema Part1, XML-Schema Part2] descriptions.

2 RM Policy Assertions

WS-Policy Framework and WS-Policy Attachment [WS-PolicyAttachment] collectively define a framework, model and grammar for expressing the requirements, and general characteristics of entities in an XML Web services-based system. To enable an RM Destination and an RM Source to describe their requirements for a given Sequence, this specification defines a single RM policy assertion that leverages the WS-Policy framework.

2.1 Assertion Model

The RM policy assertion indicates that the RM Source and RM Destination MUST use WS-ReliableMessaging to ensure reliable delivery of messages. Specifically, the WS-ReliableMessaging protocol determines invariants maintained by the reliable messaging endpoints and the directives used to track and manage the delivery of a Sequence of messages.

2.2 Normative Outline

The normative outline for the RM assertion is:

```
<wsrmp:RMAssertion [wsp:Optional="true"]? ... >
  <wsp:Policy>
    [ <wsrmp:SequenceSTR/> |
      <wsrmp:SequenceTransportSecurity/> ] ?
    <wsrmp:DeliveryAssurance>
      <wsp:Policy>
        [ <wsrmp:ExactlyOnce/> |
          <wsrmp:AtLeastOnce/> |
          <wsrmp:AtMostOnce/> ]
        <wsrmp:InOrder/> ?
      </wsp:Policy>
    </wsrmp:DeliveryAssurance> ?
  </wsp:Policy>
  ...
</wsrmp:RMAssertion>
```

The following describes the content model of the RMAssertion element.

/wsrmp:RMAssertion

A policy assertion that specifies that WS-ReliableMessaging protocol MUST be used when sending messages.

/wsrmp:RMAssertion/@wsp:Optional="true"

Per WS-Policy, this is compact notation for two policy alternatives, one with and one without the assertion. The intuition is that the behavior indicated by the assertion is optional, or in this case, that WS-ReliableMessaging MAY be used.

/wsrmp:RMAssertion/wsp:Policy

This required element allows for the inclusion of nested policy assertions.

/wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceSTR

When present, this assertion defines the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a wsse:SecurityTokenReference in the CreateSequence message. See section 2.5.1.

205 /wsrmp:RMAssertion/wsp:Policy/wsrmp:SequenceTransportSecurity

206 When present, this assertion defines the requirement that an RM Sequence MUST be bound to

207 the session(s) of the underlying transport-level protocol used to carry the `CreateSequence` and

208 `CreateSequenceResponse` message. When present, this assertion MUST be used in

209 conjunction with the `sp:TransportBinding` assertion, see section 2.5.2.

210 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance

211 This expression, which may be omitted, describes the message delivery quality of service

212 between the RM and application layer. When used by an RM Destination it expresses the delivery

213 assurance in effect between the RM Destination and its corresponding application destination,

214 and it also indicates requirements on any RM Source that transmits messages to this RM

215 destination. Conversely when used by an RM Source it expresses the delivery assurance in effect

216 between the RM Source and its corresponding application source, as well as indicating

217 requirements on any RM Destination that receives messages from this RM Source. In either case

218 the delivery assurance does not affect the messages transmitted on the wire. Absence of this

219 expression from a `wsrmp:RMAssertion` policy assertion simply means that the endpoint has

220 chosen not to advertise its delivery assurance characteristics.

221 Note that when there are multiple policy alternatives of the RM Assertion, the Delivery Assurance

222 on each MUST NOT conflict.

223 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy

224 This required element identifies additional requirements for the use of the

225 `wsrmp:DeliveryAssurance`.

226 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:ExactlyOnce

227 This expresses the ExactlyOnce Delivery Assurance defined in [].

228 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtLeastOnce

229 This expresses the AtLeastOnce Delivery Assurance defined in [].

230 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:AtMostOnce

231 This expresses the AtMostOnce Delivery Assurance defined in [].

232 /wsrmp:RMAssertion/wsp:Policy/wsrmp:DeliveryAssurance/wsp:Policy/wsrmp:InOrder

233 This expresses the InOrder Delivery Assurance defined in [].

234 /wsrmp:RMAssertion/{any}

235 This is an extensibility mechanism to allow different (extensible) types of information, based on a

236 schema, to be passed.

237 /wsrmp:RMAssertion/@{any}

238 This is an extensibility mechanism to allow different (extensible) types of information, based on a

239 schema, to be passed.

240 2.3 Assertion Attachment

241 The RM policy assertion is allowed to have the following Policy Subjects [[WS-PolicyAttachment](#)]:

- 242 ● Endpoint Policy Subject
- 243 ● Message Policy Subject

244 WS-PolicyAttachment defines a set of WSDL/1.1 policy attachment points for each of the above Policy
245 Subjects. Since an RM policy assertion specifies a concrete behavior, it MUST NOT be attached to the
246 abstract WSDL policy attachment points.

247 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an
248 RM policy assertion but which MUST NOT have RM policy assertions attached:

- 249 • wsdl:message
- 250 • wsdl:portType/wsdl:operation/wsdl:input
- 251 • wsdl:portType/wsdl:operation/wsdl:output
- 252 • wsdl:portType/wsdl:operation/wsdl:fault
- 253 • wsdl:portType

254 The following is the list of WSDL/1.1 elements whose scope contains the Policy Subjects allowed for an
255 RM policy assertion and which MAY have RM policy assertions attached:

- 256 • wsdl:port
- 257 • wsdl:binding
- 258 • wsdl:binding/wsdl:operation/wsdl:input
- 259 • wsdl:binding/wsdl:operation/wsdl:output
- 260 • wsdl:binding/wsdl:operation/wsdl:fault

261 If an RM policy assertion is attached to any of:

- 262 • wsdl:binding/wsdl:operation/wsdl:input
- 263 • wsdl:binding/wsdl:operation/wsdl:output
- 264 • wsdl:binding/wsdl:operation/wsdl:fault

265 then an RM policy assertion, specifying wsp:Optional=true MUST be attached to the corresponding
266 wsdl:binding or wsdl:port, indicating that the endpoint supports WS-RM. Any messages, regardless of
267 whether they have an attached Message Policy Subject RM policy assertion, MAY be sent to that endpoint
268 using WS-RM. Additionally, the receiving endpoint MUST NOT reject any message belonging to a
269 Sequence, simply because there was no Message Policy Subject RM policy assertion attached to that
270 message. There might be certain RM implementations that are incapable of applying RM Quality of
271 Service (QoS) semantics on a per-message basis. In order to ensure the broadest interoperability, when
272 an endpoint decorates its WSDL with RM policy assertions using Message Policy Subject, it MUST also
273 be prepared to accept that all messages sent to that endpoint might be sent within the context of an RM
274 Sequence, regardless of whether the corresponding wsdl:input, wsdl:output or wsdl:fault had an attached
275 RM policy assertion.

276 Rather than turn away messages that were unnecessarily sent with RM semantics, the receiving endpoint
277 described by the WSDL MUST accept these messages.

278 By attaching an RM policy assertion that specifies wsp:Optional="true" to the corresponding endpoint that
279 has attached RM policy assertions at the Message Policy Subject level, the endpoint is describing the
280 above constraint in policy.

281 In the case where an optional RM Assertion applies to an output message, there is no requirement on the
282 client to support an RM Destination implementation

2.4 Assertion Example

Table 2 lists an example use of the RM policy assertion.

Table 2: Example policy with RM policy assertion

```
(01)<wsdl:definitions
(02)   targetNamespace="example.com"
(03)   xmlns:tns="example.com"
(04)   xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
(05)   xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
(06)   xmlns:wsrmp="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
(07)   xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-wssecurity-utility-1.0.xsd">
(08)
(09)   <wsp:UsingPolicy wsdl:required="true" />
(10)
(11)   <wsp:Policy wsu:Id="MyPolicy" >
(12)     <wsrmp:RMAssertion>
(13)       <wsp:Policy/>
(14)     </wsrmp:RMAssertion>
(15)     <!-- omitted assertions -->
(16)   </wsp:Policy>
(17)
(18)   <!-- omitted elements -->
(19)
(20)   <wsdl:binding name="MyBinding" type="tns:MyPortType" >
(21)     <wsp:PolicyReference URI="#MyPolicy" />
(22)     <!-- omitted elements -->
(23)   </wsdl:binding>
(24)
(25)</wsdl:definitions>
```

Line (09) in Table 2 indicates that WS-Policy is in use as a required extension.

Lines (11-16) are a policy expression that includes a RM policy assertion (lines 12-14) to indicate that WS-ReliableMessaging must be used.

Lines (20-23) are a WSDL binding. Line (21) indicates that the policy in lines (11-16) applies to this binding, specifically indicating that WS-ReliableMessaging must be used over all the messages in the binding.

2.5 Sequence Security Policy

WS-SecurityPolicy [SecurityPolicy] provides a framework and grammar for expressing the security requirements and characteristics of entities in a XML web services based system. The following assertions MAY be used in conjunction with WS-SecurityPolicy to express additional security requirements particular to RM Sequences.

2.5.1 RM Assertion with Sequence STR Assertion

This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to an explicit token that is referenced from a `wsse:SecurityTokenReference` in the `CreateSequence` message.

This assertion MUST apply to [Endpoint Policy Subject]. The normative outline for this form of the Sequence STR Assertion is:

```

329 <wsrmp:RMAssertion [wsp:Optional="true"]? ...>
330   <wsp:Policy>
331     <wsrmp:SequenceSTR/>
332     <wsp:Policy>
333   </wsrmp:RMAssertion>

```

334 The following describes the content model of the `SequenceSTR` element.

335 `/wsrmp:SequenceSTR`

336 A policy assertion that specifies security requirements which MUST be used with an RM Sequence that
 337 are particular to WS-RM and beyond what can be expressed in WS-SecurityPolicy.

338 2.5.2 RM Assertion with Sequence Transport Security Assertion

339 This version of the RM assertion includes the requirement that an RM Sequence MUST be bound to the
 340 session(s) of the underlying transport-level security protocol (e.g. SSL/TLS) used to carry the
 341 `CreateSequence` and `CreateSequenceResponse` messages.

342 This assertion MUST apply to [Endpoint Policy Subject]. This assertion MUST be used in conjunction with
 343 the `sp:TransportBinding` assertion that requires the use of some transport-level security mechanism
 344 (e.g. `sp:HttpsToken`).

345 The normative outline for this form of the RM Assertion with the Sequence Transport Security Assertion is:

```

346 <wsp:Policy>
347   <wsp:ExactlyOne>
348     <wsp:All>
349       <wsrm:RMAssertion [wsp:Optional="true"]> ...>
350         <wsp:Policy>
351           <wsrmp:SequenceTransportSecurity/>
352         </wsp:Policy>
353       </wsrm:RMAssertion>
354       <sp:TransportBinding ...>
355         ...
356       </sp:TransportBinding>
357     </wsp:All>
358   </wsp:ExactlyOne>
359 </wsp:Policy>

```

360 The following describes the content model of the `SequenceTransportSecurity` element.

361 `/wsrmp:SequenceTransportSecurity`

362 A policy assertion that specifies that any Sequences targeted to the indicated endpoint MUST be bound to
 363 the underlying session(s) of the transport-level security used to carry messages related to the Sequence.

364 This form of the RM Assertion says that an endpoint MAY have RM as an option but always requires
 365 HTTPS to be used. All the `SequenceTransportSecurity` assertion indicates is that RM's rules for protecting
 366 the Sequence over TLS are followed.

3 Security Considerations

It is strongly RECOMMENDED that policies and assertions be signed to prevent tampering.

It is RECOMMENDED that policies SHOULD NOT be accepted unless they are signed and have an associated security token to specify the signer has proper claims for the given policy. That is, a relying party shouldn't rely on a policy unless the policy is signed and presented with sufficient claims to pass the relying parties acceptance criteria.

It should be noted that the mechanisms described in this document could be secured as part of a SOAP message using WS-Security [[WS-Security](#)] or embedded within other objects using object-specific security mechanisms.

4 References

4.1 Normative

[KEYWORDS]

S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels," RFC 2119, Harvard University, March 1997.

<http://www.ietf.org/rfc/rfc2119.txt>

[SOAP 1.1]

W3C Note, "SOAP: Simple Object Access Protocol 1.1" 08 May 2000.

<http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP 1.2]

W3C Recommendation, "SOAP Version 1.2 Part 1: Messaging Framework" June 2003.

<http://www.w3.org/TR/2003/REC-soap12-part1-20030624/>

[URI]

T. Berners-Lee, R. Fielding, L. Masinter, "Uniform Resource Identifiers (URI): Generic Syntax," RFC 3986, MIT/LCS, U.C. Irvine, Xerox Corporation, January 2005.

<http://ietf.org/rfc/rfc3986>

[WS-RM]

OASIS WS-RX Technical Committee Draft, "Web Services Reliable Messaging (WS-ReliableMessaging)," August 2005.

<http://docs.oasis-open.org/ws-rx/wsrp/200702/wsrp-1.1-spec-cd-05.pdf>

[WS-Policy]

W3C Member Submission, "Web Services Policy Framework (WS-Policy)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-Policy-20060425/>

[WS-PolicyAttachment]

W3C Member Submission, "Web Services Policy Attachment (WS-PolicyAttachment)," April 2006.

<http://www.w3.org/Submission/2006/SUBM-WS-PolicyAttachment-20060425/>

[WSDL 1.1]

W3C Note, "Web Services Description Language (WSDL 1.1)," 15 March 2001.

<http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XML]

W3C Recommendation, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", September 2006.

<http://www.w3.org/TR/REC-xml/>

409 **[XML-ns]**

410 W3C Recommendation, "[Namespaces in XML](#)," 14 January 1999.

411 <http://www.w3.org/TR/1999/REC-xml-names-19990114/>

412 **[XML-Schema Part1]**

413 W3C Recommendation, "[XML Schema Part 1: Structures](#)," October 2004.

414 <http://www.w3.org/TR/xmlschema-1/>

415 **[XML-Schema Part2]**

416 W3C Recommendation, "[XML Schema Part 2: Datatypes](#)," October 2004.

417 <http://www.w3.org/TR/xmlschema-2/>

418 **[XPath 1.0]**

419 W3C Recommendation, "[XML Path Language \(XPath\) Version 1.0](#)," 16 November 1999.

420 <http://www.w3.org/TR/xpath>

421 **4.2 Non Normative**

422 **[RDDL 2.0]**

423 Jonathan Borden, Tim Bray, eds. "[Resource Directory Description Language \(RDDL\) 2.0](#)," January 2004

424 <http://www.openhealth.org/RDDL/20040118/rddl-20040118.html>

425 **[SecurityPolicy]**

426 G. Della-Libra, et. al. "[Web Services Security Policy Language \(WS-SecurityPolicy\)](#)", July 2005

427 <http://specs.xmlsoap.org/ws/2005/07/securitypolicy/ws-securitypolicy.pdf>

428 **[WS-Security]**

429 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "[OASIS Web Services Security: SOAP Message Security 1.0 \(WS-Security 2004\)](#)", OASIS Standard 200401, March 2004.

431 <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>

432 Anthony Nadalin, Chris Kaler, Phillip Hallam-Baker, Ronald Monzillo, eds. "[OASIS Web Services Security: SOAP Message Security 1.1 \(WS-Security 2004\)](#)", OASIS Standard 200602, February 2006.

434 [http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

435 [spec-os-SOAPMessageSecurity.pdf](http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)

Appendix A. Acknowledgments

This document is based on initial contribution to OASIS WS-RX Technical Committee by the following authors:

Stefan Batres-Editor(Microsoft), Ruslan Bilorusets(BEA), Don Box(Microsoft), Luis Felipe Cabrera(Microsoft), Derek Collison(TIBCO Software), Donald Ferguson(IBM), Christopher Ferris-Editor(IBM), Tom Freund(IBM), Mary Ann Hondo(IBM), John Ibbotson(IBM), Lei Jin(BEA), Chris Kaler(Microsoft), David Langworthy(Microsoft), Amelia Lewis(TIBCO Software), Rodney Limplecht(Microsoft), Steve Lucco(Microsoft), Don Mullen(TIBCO Software), Anthony Nadalin(IBM), Mark Nottingham(BEA), David Orchard(BEA), Shivajee Samdarshi(TIBCO Software), John Shewchuk(Microsoft), Tony Storey(IBM).

The following individuals have provided invaluable input into the initial contribution:

Keith Ballinger(Microsoft), Allen Brown(Microsoft), Michael Conner(IBM), Francisco Curbera(IBM), Steve Graham(IBM), Pat Helland(Microsoft), Rick Hill(Microsoft), Scott Hinkelman(IBM), Tim Holloway(IBM), Efim Hudis(Microsoft), Johannes Klein(Microsoft), Frank Leymann(IBM), Martin Nally(IBM), Peter Niblett(IBM), Jeffrey Schlimmer(Microsoft), Chris Sharp(IBM), James Snell(IBM), Keith Stobie(Microsoft), Satish Thatte(Microsoft), Stephen Todd(IBM), Sanjiva Weerawarana(IBM), Roger Wolter(Microsoft).

The following individuals were members of the committee during the development of this specification:

Abbie Barbir(Nortel), Charlton Barreto(Adobe), Stefan Batres(Microsoft), Hamid Ben Malek(Fujitsu), Andreas Bjarlestam(Ericsson), Toufic Boubrez(Layer 7), Doug Bunting(Sun), Lloyd Burch(Novell), Steve Carter(Novell), Martin Chapman(Oracle), Dave Chappell(Sonic), Paul Cotton(Microsoft), Glen Daniels(Sonic), Doug Davis(IBM), Blake Dournaee(Intel), Jacques Durand(Fujitsu), Colleen Evans(Microsoft), Christopher Ferris(IBM), Paul Fremantle(WSO2), Robert Freund(Hitachi), Peter Furniss(Erebor), Marc Goodner(Microsoft), Alastair Green(Choreology), Mike Grogan(Sun), Ondrej Hrebicek(Microsoft), Kazunori Iwasa(Fujitsu), Chamikara Jayalath(WSO2), Lei Jin(BEA), Ian Jones(BT plc), Anish Karmarkar(Oracle), Paul Knight(Nortel), Dan Leshchiner(Tibco), Mark Little(JBoss), Lily Liu(webMethods), Matt Lovett(IBM), Ashok Malhotra(Oracle), Jonathan Marsh(Microsoft), Daniel Millwood(IBM), Jeff Mischkinsky(Oracle), Nilo Mitra(Ericsson), Peter Niblett(IBM), Duane Nickull(Adobe), Eisaku Nishiyama(Hitachi), Dave Orchard(BEA), Chouthri Palanisamy(NEC), Sanjay Patil(SAP), Gilbert Pilz(BEA), Martin Raeppele(SAP), Eric Rajkovic(Oracle), Stefan Rossmanith(SAP), Tom Rutt(Fujitsu), Rich Salz(IBM), Shivajee Samdarshi(Tibco), Vladimir Videlov(SAP), Claus von Riegen(SAP), Pete Wenzel(Sun), Steve Winkler(SAP), Ümit Yalçınalp(SAP), Nobuyuki Yamamoto(Hitachi).

470 Appendix B. XML Schema

471 A normative copy of the XML Schema [XML-Schema Part1, XML-Schema Part2] description for this
472 specification may be retrieved from the following address:

473 <http://docs.oasis-open.org/ws-rx/wsrmp/200702/wsrmp-1.1-schema-200702.xsd>

474 The following copy is provided for reference.

```
475 <?xml version="1.0" encoding="UTF-8"?>
476 <!--
477 OASIS takes no position regarding the validity or scope of any
478 intellectual property or other rights that might be claimed to pertain to
479 the implementation or use of the technology described in this document or
480 the extent to which any license under such rights might or might not be
481 available; neither does it represent that it has made any effort to
482 identify any such rights. Information on OASIS's procedures with respect
483 to rights in OASIS specifications can be found at the OASIS website.
484 Copies of claims of rights made available for publication and any
485 assurances of licenses to be made available, or the result of an attempt
486 made to obtain a general license or permission for the use of such
487 proprietary rights by implementors or users of this specification, can be
488 obtained from the OASIS Executive Director.
489 OASIS invites any interested party to bring to its attention any
490 copyrights, patents or patent applications, or other proprietary rights
491 which may cover technology that may be required to implement this
492 specification. Please address the information to the OASIS Executive
493 Director.
494 Copyright (c) OASIS Open 2002-2007. All Rights Reserved.
495 This document and translations of it may be copied and furnished to
496 others, and derivative works that comment on or otherwise explain it or
497 assist in its implementation may be prepared, copied, published and
498 distributed, in whole or in part, without restriction of any kind,
499 provided that the above copyright notice and this paragraph are included
500 on all such copies and derivative works. However, this document itself
501 does not be modified in any way, such as by removing the copyright notice
502 or references to OASIS, except as needed for the purpose of developing
503 OASIS specifications, in which case the procedures for copyrights defined
504 in the OASIS Intellectual Property Rights document must be followed, or
505 as required to translate it into languages other than English.
506 The limited permissions granted above are perpetual and will not be
507 revoked by OASIS or its successors or assigns.
508 This document and the information contained herein is provided on an "AS
509 IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED,
510 INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION
511 HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF
512 MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
513 -->
514 <xs:schema xmlns:tns="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
515 xmlns:xs="http://www.w3.org/2001/XMLSchema"
516 targetNamespace="http://docs.oasis-open.org/ws-rx/wsrmp/200702"
517 elementFormDefault="qualified" attributeFormDefault="unqualified">
518   <xs:element name="RMAssertion">
519     <xs:complexType>
520       <xs:sequence>
521         <xs:any namespace="##other" processContents="lax" minOccurs="0"
522 maxOccur
523         </xs:sequence>
524         <xs:anyAttribute namespace="##any" processContents="lax"/>
525       </xs:complexType>
```

```

526     </xs:element>
527     <xs:element name="SequenceSTR">
528         <xs:complexType>
529             <xs:sequence/>
530             <xs:anyAttribute namespace="##any" processContents="lax"/>
531         </xs:complexType>
532     </xs:element>
533     <xs:element name="SequenceTransportSecurity">
534         <xs:complexType>
535             <xs:sequence/>
536             <xs:anyAttribute namespace="##any" processContents="lax"/>
537         </xs:complexType>
538     </xs:element>
539     <xs:element name="DeliveryAssurance">
540         <xs:complexType>
541             <xs:sequence>
542                 <xs:any namespace="##any" processContents="lax" minOccurs="0"
543 maxOccurs="unbounded" />
544             </xs:sequence>
545         </xs:complexType>
546     </xs:element>
547     <xs:element name="ExactlyOnce">
548         <xs:complexType>
549             <xs:sequence/>
550         </xs:complexType>
551     </xs:element>
552     <xs:element name="AtLeastOnce">
553         <xs:complexType>
554             <xs:sequence/>
555         </xs:complexType>
556     </xs:element>
557     <xs:element name="AtMostOnce">
558         <xs:complexType>
559             <xs:sequence/>
560         </xs:complexType>
561     </xs:element>
562     <xs:element name="InOrder">
563         <xs:complexType>
564             <xs:sequence/>
565         </xs:complexType>
566     </xs:element>
567 </xs:schema>

```

568 **Appendix C. Revision History**

Revision	Date	By Whom	What
wd-01.doc	2005-07-06	Ümit Yalçinalp	Initial version created based on submission by the authors.
1.0-wd-01.swx	2005-09-01	Ümit Yalçinalp	Reformatted using Open Office
1.1-wd-01.swx	2005-09-18	Ümit Yalçinalp	Applied resolution i001 Applied resolution i015/16 (doc identifier) Partial application of i017, final yyyy/mm required, changed doc URI to TBD pending yyyy/mm Deleted original copyright section
1.1-wd-01.swx	2005-10-02	Anish Karmarkar	Applied resolution of i013 + minor editorial changes + fixed resolution of i017
1.1-wd-01.swx	2005-10-04	Ümit Yalçinalp	Applied actual value for yyyy/mm. Added resolution of i009
1.1-wd-01.swx	2005-10-06	Ümit Yalçinalp	Editorial fixes suggested by Anish Updated wd draft date to October 6th
1.1-wd-01.swx	2005-10-19	Ümit Yalçinalp	Editorial change to remove .swx suffix from doc id
wd-02	2005-11-03	Gilbert Pilz	Start wd-02 by changing title page from cd-01.
wd-02	2005-11-30	Gilbert Pilz	i072 – editorial nits
wd-02	2005-11-30	Gilbert Pilz	i074 - Use of [tcShortName] in artifact locations namespaces, etc
wd-02	2005-12-01	Gilbert Pilz	Updated fix to i074 to remove trailing '/' from wsrmp namespace.
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i022
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i024
wd-02	2005-12-01	Anish Karmarkar	Applied resolution for i054
wd-02	2005-12-01	Anish Karmarkar	Applied resolution of i073
wd-2	2005-12-05	Anish Karmarkar	Applied resolution of i055
wd-2	2005-12-05	Ümit Yalçinalp	Changed fixed date in footer to current date
wd-3	2005-12-21	Doug Davis	Added i050
wd-3	2005-12-23	Ümit Yalçinalp	I057 resolution

Revision	Date	By Whom	What
wd-3	2005-12-23	Ümit Yalçınalp	Changed the ref to WS-RM to the WS-RX committee draft instead of original version Fixed Dug's email address
wd-3	2005-12-23	Ümit Yalçınalp	I060 resolution
wd-03	2005-12-27	Gilbert Pilz	Remove schema example and put it in its own artifact (wsrmp-1.1-schema-200510.xsd). Convert source file to OpenDocument format. Make line numbers all the same style.
wd-03	2005-12-28	Anish Karmarkar	Included a section link to c:\temp\wsrmp-1.1-schema-200510.xsd
wd-03	2006-01-04	Gilbert Pilz	Fixed formatting of included section.
wd-03	2006-01-05	Gilbert Pilz	Fix closing tag of normative outline for RMAssertion.
wd-04	2006-11-11	Doug Davis	Minor tweaks/typos
wd-05	2006-01-23	Gilbert Pilz	Start wd-05 by accepting all changes from wd-04
wd-06	2006-01-23	Doug Davis	Minor typos found by Marc
wd-06	2006-02-14	Doug Davis	Issue 075 resolution
wd-06	2006-02-14	Doug Davis	Issues 086, 087 resolutions
wd-06	2006-02-15	Gilbert Pilz	Issue 088; added link for namespace URI; added text describing link; added non-normative reference for RDDL 2.0
wd-06	2006-02-17	Anish Karmarkar	Removed a sentence in section 2.1 that talked about RM assertion parameters, as there aren't any.
wd-06	2006-02-17	Anish Karmarkar	Change the namespace to 200602.
wd-07	2006-02-22	Doug Davis	Accept all changes to create new WD Minor typo fixed – thanks to Paul Cotton
wd-07	2006-02-23	Doug Davis	Added missing namespace table entries - MarcG
wd-07	2006-03-08	Doug Davis	Issue 097 applied
wd-08	2006-04-11	Doug Davis	Issue 021 applied
wd-08	2006-04-24	Gilbert Pilz	Misc cleanups prior to publishing to TC.
wd-09	2006-05-29	Gilbert Pilz	Issue 117 applied
wd-10	2006-06-05	Gilbert Pilz	Accept all changes; bump WD number
wd-10	2006-06-07	Doug Davis	Applied lots of minor edits from Marc Goodner
wd-10	2006-06-13	Doug Davis	Applied a couple of minor edits

Revision	Date	By Whom	What
wd-10	2006-07-21	Doug Davis	Issues 122-124 applied
wd-10	2006-07-27	Doug Davis	Copied list of TC members from RM spec (i134)
wd-10	2006-08-04	Doug Davis	Updated old namespaces – found by PaulC
wd-10	2006-08-04	Doug Davis	Verify all [refs]
wd-10	2006-08-04	Doug Davis	Change namespace to 2006/08
cd-04	2006-08-11	Doug Davis	Issue 158 applied
cd-04	2006-08-16	Gilbert Pilz	Fix date at 08/11/2006; formatting changes for better HTML rendering.
wd-11	2006-10-25	Doug Davis	Accept all changes, update to wd11
wd-11	2006-10-26	Doug Davis	PR004 applied
wd-11	2007-01-26	Doug Davis	PR037 applied
wd-12	2007-01-31	Doug Davis	Lots of typos from MarcG Updated WD number and date
wd-12	2007-02-01	Doug Davis	PR035 (009,020 dups) applied